



Semi-automatic swing arm tire changer for oversized and racing tires

Powerful semiautomatic swing arm tire changer for intensive use. Extra-high tower for extra wide tires, bead seating jet blast from jaws (GT system), bead breaker arm designed for tough jobs.

Description

Powerful tire changer for intensive use, specially designed to handle **oversized and racing tires**. Extra-high tower for extra wide tires, sturdy cabinet, welded in one piece, bead breaker arm designed **for tough jobs**, reliable and durable clamping system with two cylinders (no adjustment on slides), solid swing-arm column, thicker tabletop, bead seating jet blast from jaws (**GT system**), vertical tower with built-in air tank. Version with **Leverless device available**. Designed, built and engineered in Italy. Developed by Giuliano for high volume tire shops, servicing extra wide tires, suitable for all tire professionals, who have to deal with all kinds of CAR, LCV and LIGHT TRUCK tires and wheels every day.

5-YEAR WARRANTY on the core parts of our tire changers.

MAXI PRO GT - The real "work-horse" for your tire shop !!

Functions

- **Extra-high tower for extra wide tires**, swinging horizontal arm with Ø 41 mm operating arm.
- Bead breaker double effect Cylinder Ø 200 mm.
- Reinforced Chassis and Tower.
- Robust bead breaker arm, designed for tough jobs.
- Tabletop thickness 14 mm w/adjust. jaws.
- Reliable and durable clamping system, with two cylinders.
- Bead seating jet blast from jaws and tire inflation by pedal (standard).
- **Vertical tower with built-in air tank**, provides tubeless tire inflation and bead seating.
- PRESS ARM powerful pneumatic helper system to ease mounting operations of low profiled and UHP tires (supplied as standard with Maxi Pro PA and Maxi Pro Duo, optional for Maxi Pro).
- HELP additional auxiliary helper arm to ease mounting operations of low profiled and UHP tires (supplied as standard with MAXI Pro Duo, optional for MAXI Pro and MAXI Pro PA).
- Fitting head designed for both standard and low profiled tire applications.
- **MOTOR INVERTER** speed by pedal (220V) more accurate and reliable drive for your tire changer.
- "Easy Access" extractable pedal box for quick service.
- Complete with storage box for tools and accessories.
- Quick release kit for mounting tools (optional).
- Suitable for **Patented QX mounting device** for low profiled and UHP tires (optional).
- A very practical Wheel Lifter reduces effort and increases productivity (optional).
- Motorcycle wheel clamping adaptors available (optional).
- **5 YEAR WARRANTY** on "Made in Giuliano" gearbox.
- Designed, built and engineered in Italy.
- "Right to repair" - all service parts available for at least 10 years since production, easy maintenance and reduced environmental impact.

Extensive selection of standard accessories: bead lifting lever, lube paste bucket and brush, plastic protectors for mounting/demounting tool, 2 protectors for bead breaker shovel, jaw protectors for alloy rims, lubricator + pressure regulator, bucket support

Giuliano Industrial S.p.A.

Standard Features

External clamping range	10" - 24" By adjustable jaws
Internal clamping range	12" - 26" By adjustable jaws
Max. tire diameter	1200 mm (47")
Max. tire width	390 mm (15")
Bead loosener force	30800 N
Operating pressure	10 bar (145 psi)
Power supply	220V - 1ph - Inverter (STND) 400V - 3ph, 2 speed, 110V - 1ph (OPT)
Motor power	0,75 kW (2 speed)
Balancing speed	7-16 rpm
Air Inflation Pressure	3,5 bar (50 Psi)
Net weight	340 Kg Maxi Pro GT
Dimensions (WxDxH)	1390 x 1310 x 2160 mm Maxi Pro GT
Net weight	400 Kg Maxi Pro PA GT
Dimensions (WxDxH)	1390 x 1600 x 2160 mm Maxi Pro PA GT
Net weight	432 Kg Maxi Pro Duo GT
Dimensions (WxDxH)	1390 x 1750 x 2160 mm Maxi Pro Duo GT



Standard accessories



G-CLAMP (9217471)
G-CLAMP Set. Helps adding extra bead-pressure points on top bead while assembling it. Kit includes 2 regular and 2 extra-size G-clamps.



RJP (9236282)
Kit of rubber coated jaw protectors.



T1 (9217472)
Kit of 4 rubber protections for steel rims.



T2 (9217473)
Kit of 4 rubber protections for aluminium rims.



T3 (9217474)
Kit of 4 rubber protectors for aluminium rims with arched spokes.



LB (9216805)
Lube paste bucket, 5 kg.



AWF (9213425)
Air filter with pressure regulator and CE manometer.



GUN 1 (9236658)
Tubeless inflation external kit.



ORJP (9216166)
Kit of rubber protections for clamping rims from inside using conventional jaws.



MOTO-AD (9235081)
Kit of 4 motorcycle wheels adaptors, 6" - 24", with screw lock.



ATV-AD (9235082)
Kit of 4 adaptors for HARLEY DAVIDSON wheels, oversize height, 6" - 24", with screw lock.



QCK (9208996)
Quick release kit for mounting tools (includes one plastic tool and one hub for connecting the tool delivered with the tire changer).



SHS (9209086)
Mounting/demounting tool for soft tires on steel wheels, including hub for connection to quick release kit (**QCK**).



AHS (9213611)
Mounting/demounting tool for arched spokes rims, including hub for connection to quick release kit (**QCK**).



EHS (9235009)
Mounting/demounting tool for iron wheels with projecting central hub, including hub for connection to quick release kit (**QCK**).



QX (9243338)
QX is a leverless mount/demount device, suitable for conventional, UHP and Run Flat tires. Exclusive GIULIANO **Patent**, it works in the same exact way of your traditional tire bar, but **without operator's manual force....**



QXHS (9230814)
Kit of **QX** adaptors for connection to quick release kit (**QCK**).



HD (9208633)
Manual bead depressor.



PAD (9237711)
Manual bead depressor with extendable travelling pad.



HELP MAXI PRO (9246745)
HELP MAXI PRO additional arm to ease mounting operations of low profiled and UHP tyres



PA MAXI PRO (9246934)
PRESS ARM MAXO PRO additional arm to ease mounting operations of low profiled and UHP tyres



WL 6 (9242824)
Pneumatic wheel lifter for passenger car type changers with foot control for the ascent and descent of the wheel. Pneumatic wheel lifter for car tire changer: facilitates the positioning of the wheel on the tire changer. Foot control for the ascent...



QX-AD (9232767)
QX, QX Plus adjusting tool and **LeverNoLever** System



TPP 4 (9234452)
Kit of 10 rear plastic protections, for **QX, QX Plus** and **LeverNoLever** System



TPP 5 (9234453)
Kit of 10 front plastic protections, for **QX** and **QX Plus** and **LeverNoLever** System



CPC (9214251)
Pressing cone for clamping RUN FLAT tires from outside.



Scan QR code to go to product web page



Giuliano Industrial S.p.A.

via Guerrieri 6

Correggio (RE)

Italy

+39 0522 731111

+39 0522 633198

<https://www.giuliano-automotive.com>



Social Network



Facebook



YouTube



Twitter



www.giuliano-automotive.com