

Semiautomatic swing arm tire changer machine

Semiautomatic swing arm tire changer for low-mid volume shops, garages and repair shops. Ideal for mobile tire service (12V version available upon request). Solid and reliable design. Excellent quality-price ratio. Designed, built and engineered in Italy.

Description

Semi-automatic swing arm tire changer machine for wheels with rim from 10" to 24" (max. wheel diameter 1100 mm./43", max. wheel width 330mm./13").
S116 tire changer machine represents the Giuliano entry-level solution, suggested for low-mid volume shops, garages and repair shops. **Simplicity** is the strong point of this model, which combines **solid and reliable design**, Giuliano experience and classic well known operating mode. Excellent quality-price ratio. Ideal for mobile tire service (12V version available upon request).

Functions

- Robust vertical tower, swinging horizontal arm with ø 41 mm operating arm.
- Bead breaker double effect Cylinder ø 200 mm.
- Reinforced Chassis.
- Tabletop thickness 12 mm.
- Fitting head designed for both standard and low-profiled tire applications.
- "Easy Access" extractable pedal box for quick service.
- 12V version suitable for **mobile service** available upon request. Ideal for mobile tire fitters working from a VAN.
- Plastic protections on fitting head to avoid any damage to alloy rim.
- Two powerful clamping cylinders provide uniform clamping pressure.
- Suitable for Tubeless tire bead seating system (optional).
- Suitable for PRESS ARM ECO additional arm to ease mounting operations of low profiled and UHP tires (optional).
- Pedal Inflation Set. Installed on the side of the tire changer, provides inflation system on board the tire changer, activated by pedal (optional).
- **5 YEARS WARRANTY** on "Made in Giuliano" gearbox.
- Designed, built and engineered in Italy.
- "Right to repair" - all service parts available for at least 10 years since production, easy maintenance and reduced environmental impact.

The information contained in this document is the sole property of Giuliano Automotive. The document is NOT authentic if it has been downloaded from a website different from www.giuliano-automotive.com.

Standard Features

Rim clamping range from outside	10" - 22" Adjustable jaws can be pre-set in 3 different holes on slides, to start clamping range from 10", 11" or 12". Tabletop cylinder stroke = 10"
Rim clamping range from inside	12" - 24" Adjustable jaws can be pre-set in 3 different holes on slides, to start clamping range from 10", 11" or 12". Tabletop cylinder stroke = 10"
Max. tire diameter	1100 mm (43")
Max. tire width	330 mm (13")
Bead loosener cylinder force at 10 Bar	30800 N
Operating pressure	10 bar (145 Psi)
Power supply	400V-3ph 220V-1ph
Motor power	0,55 kW (3ph)
Rotating speed	7 rpm
Pre-set tire inflating pressure	3,5 bar (50 Psi)
Net weight	190 Kg
Max overall dimensions	1170 x 960 x 1760 mm

www.giuliano-automotive.com

The information contained in this document is the sole property of Giuliano Automotive. The document is NOT authentic if it has been downloaded from a website different from www.giuliano-automotive.com.

Standard accessories



www.giuliano-automotive.com
The information contained in this document is the sole property of Giuliano Automotive. The document is NOT authentic if it has been downloaded from a website different from www.giuliano-automotive.com.



G-CLAMP (9217471)
G-CLAMP Set. Helps adding extra bead-pressure points on top bead while assembling it. Kit includes 2 regular and 2 extra-size G-clamps.



RJP (9236282)
Kit of rubber coated jaw protectors.



T1 (9217472)
Kit of 4 rubber protections for steel rims.



T2 (9217473)
Kit of 4 rubber protections for aluminium rims.



T3 (9217474)
Kit of 4 rubber protectors for aluminium rims with arched spokes.



LB (9216805)
Lube paste bucket, 5 kg.



AWF (9213425)
Air filter with pressure regulator and CE manometer.



BAR-G (9298185)
CE inflating gauge



PSI-G (9299684)
Extra-CE inflating gauge.



PED-G (9236373)
Pedal operated inflating device.



GUN 1 (9236658)
Tubeless inflation external kit.



ORJP (9216166)
Kit of rubber protections for clamping rims from inside using conventional jaws.



MOTO-AD (9235081)
Kit of 4 motorcycle wheels adaptors, 6" - 24", with screw lock.



ATV-AD (9235082)
Kit of 4 adaptors for HARLEY DAVIDSON wheels, oversize height, 6" - 24", with screw lock.



QCK (9208996)
Quick release kit for mounting tools (includes one plastic tool and one hub for connecting the tool delivered with the tire changer).



SHS (9209086)
Mounting/demounting tool for soft tires on steel wheels, including hub for connection to quick release kit (**QCK**)



AHS (9213611)
Mounting/demounting tool for arched spokes rims, including hub for connection to quick release kit (**QCK**).



EHS (9235009)
Mounting/demounting tool for iron wheels with projecting central hub, including hub for connection to quick release kit (**QCK**)



QX (9243338)
QX is a leverless mount/demount device, suitable for conventional, UHP and Run Flat tires. Exclusive GIULIANO **Patent**, it works in the same exact way of your traditional tire bar, but **without operator's manual force**.



QXHS (9230814)
Kit of **QX** adaptors for connection to quick release kit (**QCK**).

www.giuliano-automotive.com
The information contained in this document is the sole property of Giuliano Automotive. The document is NOT authentic if it has been downloaded from a website different from www.giuliano-automotive.com.



HD (9208633)
Manual bead depressor.



PAD (9237711)
Manual bead depressor with extendable travelling pad.



QCB (9218518)
Quick release kit for motorcycle tire bead loosener blade.



PA ECO (9236722)
PRESS ARM ECO additional arm to ease mounting operations of low profiled and UHP tires.



ROLL (9207933)
Fixed roller plate, to ease bead loosening of heavy wheels.



WL 6 (9242824)
Pneumatic wheel lifter for passenger car type changers with foot control for the ascent and descent of the wheel. Pneumatic wheel lifter for car tire changer: facilitates the positioning of the wheel on the tire changer. Foot control for the ascent...



QX-AD (9232767)
QX, **QX Plus** adjusting tool and **LeverNoLever** System



TPP 4 (9234452)
Kit of 10 rear plastic protections, for **QX**, **QX Plus** and **LeverNoLever** System



TPP 5 (9234453)
Kit of 10 front plastic protections, for **QX** and **QX Plus** and **LeverNoLever** System



CPC (9214251)
Pressing cone for clamping RUN FLAT tires from outside.

The information contained in this document is the sole property of Giuliano Automotive. The document is NOT authentic if it has been downloaded from a website different from www.giuliano-automotive.com.

Scan QR code to go to product web page

Giuliano Industrial S.p.A.
via Guerrieri 6
Correggio (RE)
Italy
+39 0522 731111
+39 0522 633198
https://www.giuliano-automotive.com

Social Network

Facebook

YouTube

Twitter

The information contained in this document is the sole property of Giuliano Automotive. The document is NOT authentic if it has been downloaded from a website different from www.giuliano-automotive.com.