



PAR-MOVE Concept High Performance superautomatic tire changer with dual assist arm

PAR-MOVE concept high performance superautomatic tire changer with dual assist arm. For high volume tire shops, servicing racing, run flat and UHP tires.

Description

PAR-MOVE concept high performance superautomatic tire changer with dual assist arm. For high volume tire shops, servicing racing, run flat and UHP tires.

Functions

- Robust fixed vertical tower with innovative parallelogram operating arm (**PAR-MOVE Concept**).
- Bead breaker double effect Cylinder Ø 200 mm.
- Reinforced Chassis. Fixed vertical tower and parallelogram operating arm makes S119 Pro extremely robust and stiff, granting increased rigidity and eliminating all flexes.
- Tabletop thickness 14 mm.
- Fitting head designed for both standard and low profiled tire applications.
- Double rotation speed by pedal.
- Tire inflation by pedal (standard).
- Equipped with **HP119** dual assist arm (standard) and storage box.
- Suitable for Tubeless tire bead seating system (optional).
- "Easy Access" extractable pedal box for quick service.
- **PO System**, Giuliano patent, for granting no bead loosener shovel stuck into the rim during bead loosening operations;
- Suitable for Wheel Lifter (optional).

Giuliano Industrial S.p.A.

Standard Features

Rim clamping range from outside	10" - 24" By adjustable jaws
Rim clamping range from inside	12" - 26" By adjustable jaws
Max. tire diameter	1100 mm (43")
Max. tire width	415 mm (16")
Bead loosener cylinder force at 10 Bar	30800 N
Operating pressure	10 bar (145 Psi)
Power supply	400V - 3Ph/2 speed 220V - 1Ph 220V - 1Ph/2 speed
Motor power	0,8 / 1,1 kW (3ph)
Balancing speed	7 - 14 rpm
Pre-set tire inflating pressure	3,5 bar (50 Psi)
Net weight	403 Kg
Max overall dimensions	1390 x 1310 x 2170 mm



Standard accessories



PED-G (9236373)
Pedal operated inflating device.



AWF (9213425)
Air filter with pressure regulator and CE manometer.





G-CLAMP (9217471)
G-CLAMP Set. Helps adding extra bead-pressure points on top bead while assembling it. Kit includes 2 regular and 2 extra-size G-clamps.



GUN 4 (9245186)
Tubeless inflation external kit



RJP (9236282)
Kit of rubber coated jaw protectors.



T1 (9217472)
Kit of 4 rubber protections for steel rims.



T2 (9217473)
Kit of 4 rubber protections for aluminium rims.



T3 (9217474)
Kit of 4 rubber protectors for aluminium rims with arched spokes.



LB (9216805)
Lube paste bucket, 5 kg.



BP1 PLUS (9245184)
Bead pressing arm, complete with selfstorage function, **GIULIANO patent**.



ORJP (9216166)
Kit of rubber protections for clamping rims from inside using conventional jaws.



MOTO-AD (9235081)
Kit of 4 motorcycle wheels adaptors, 6" - 24", with screw lock.



ATV-AD (9235082)
Kit of 4 adaptors for HARLEY DAVIDSON wheels, oversize height, 6" - 24", with screw lock.



QCK (9208996)
Quick release kit for mounting tools (includes one plastic tool and one hub for connecting the tool delivered with the tire changer).



SHS (9209086)
Mounting/demounting tool for soft tires on steel wheels, including hub for connection to quick release kit (**QCK**)



AHS (9213611)
Mounting/demounting tool for arched spokes rims, including hub for connection to quick release kit (**QCK**).



EHS (9235009)
Mounting/demounting tool for iron wheels with projecting central hub, including hub for connection to quick release kit (**QCK**)



QX (9243338)
QX is a leverless mount/demount device, suitable for conventional, UHP and Run Flat tires. Exclusive **GIULIANO Patent**, it works in the same exact way of your traditional tire bar, but **without operator's manual force....**



QXHS (9230814)
Kit of **QX** adaptors for connection to quick release kit (**QCK**).



PAD (9237711)
Manual bead depressor with extendable travelling pad.



HD (9208633)
Manual bead depressor.



UHP6 (9245051)
Kit Run Flat UHP



WL 6 (9242824)

Pneumatic wheel lifter for passenger car type changers with foot control for the ascent and descent of the wheel. Pneumatic wheel lifter for car tire changer: facilitates the positioning of the wheel on the tire changer. Foot control for the ascent...



Scan QR code to go to product web page

**Giuliano Industrial S.p.A.**

via Guerrieri 6

Correggio (RE)

Italy

+39 0522 731111

+39 0522 633198

<https://www.giuliano-automotive.com>

**Social Network**

Facebook



YouTube



Twitter



www.giuliano-automotive.com