



PAR-MOVE concept high performance center post tire machine with additional auxiliary helper system.

Super-automatic center post tire changer machine PAR-MOVE Concept, equipped with auxiliary pneumatic arm. This high-performance tire changer machine is designed for use with wheels equipped with a central hole for tire replacement on passenger cars, light trucks and vans. Reliable and fast clamping without risk to the wheel. Patented ergonomic parallelogram design saves space.

Description

PAR-MOVE concept high-performance center post tire machine with additional auxiliary helper system.

[Discover the advantages of PAR-MOVE system](#)

Tire machine uses a center post to hold the tire in place while the machine performs the tire-changing operation. This tire machine is designed for use with wheels that have a center hole for changing tires on passenger cars, light trucks, and vans. Wheel clamping through the central hole is more reliable compared to clamping on a turntable, convenient operation without space restrictions, reliable and fast clamping without risks to the wheel.

PAR-MOVE Series – STRONGER THAN EVER!

Functions

- Robust fixed vertical tower with innovative **PAR-MOVE** parallelogram operating arm [Giuliano Patent]. **5 YEAR WARRANTY ON PAR-MOVE**
- **SPACE SAVER:** PAR-MOVE design enables the tire machine to be installed against the wall, requiring no additional rear space.
- **Reinforced Chassis.** Fixed vertical tower and parallelogram operating arm [Giuliano Patent] makes this tire machine extremely robust and stiff, granting increased rigidity and eliminating all flexes.
- Manual Press/Twist **ultra-quick wheel-clamping device.**
- Fitting head designed for both standard and low-profiled tire applications.
- **QX** Leverless tire mounting/demounting device [Giuliano Patent] for conventional, low profiled, UHP and Run Flat tires, optional.
- HP119 Additional auxiliary helper system (standard) provides a valuable support in mounting/ demounting Run Flat, UHP and low profiled tires.
- Bead breaker double effect Cylinder \varnothing 200 mm.
- **5 YEARS WARRANTY** on "Made in Giuliano" gearbox.
- **PO System** [Giuliano Patent] for granting no bead breaker shovel stuck into the rim during bead breaking operations.
- Adjustable bead breaker shovel stroke. Super-quick and Simple.
- Double rotation speed by pedal.
- Available in 3ph-2 speed, 1ph-2 speed (inverter) and 1ph - 1 speed version.
- **MOTOINVERTER** for granting faster, more accurate and reliable drive for your tire machine.
- Tire inflation by pedal (standard).
- Vertical tower with built-in air tank, provides tubeless tire inflation and bead seating (optional), eliminating the need for a separate air tank.
- Suitable for Tubeless tire bead seating system (optional).
- **BP1 PLUS** pneumatic bead pressing arm [Giuliano Patent], optional.
- "Easy Access" extractable pedal box for quick service.
- Extensive selection of standard accessories
- A very practical Wheel Lifter reduces effort and increases productivity (optional).
- Designed, built and engineered in Italy.
- "Right to repair" - all service parts available for at least 10 years since production, easy maintenance and reduced environmental impact.

Giuliano Industrial S.p.A.

Standard Features

Rim clamping range	10" - 27"
Max. tire diameter	1100 mm (43")
Max. tire width	390 mm (15") <small>For reverse mounted wheels, variable according to rim features</small>
Bead loosener force	30800 N
Operating pressure	10 bar (145 psi)
Power supply	220V - 1ph - Inverter (STND) 400V - 3ph, 2 speed, 110V - 1ph (OPT)
Motor power	0,75 kW (2 speed)
Balancing speed	7-16 rpm
Air Inflation Pressure	3,5 bar (50 Psi)
Net weight	395 Kg
Dimensions (WxDxH)	1390 x 1310 x 2170 mm



Standard accessories



**G-CLAMP** (9217471)

G-CLAMP Set. Helps adding extra bead-pressure points on top bead while assembling it. Kit includes 2 regular and 2 extra-size G-clamps.

**GUN 4** (9245186)

Tubeless inflation external kit

**T1** (9217472)

Kit of 4 rubber protections for steel rims.

**T2** (9217473)

Kit of 4 rubber protections for aluminium rims.

**T3** (9217474)

Kit of 4 rubber protectors for aluminium rims with arched spokes.

**LB** (9216805)

Lube paste bucket, 5 kg.

**AWF** (9213425)

Air filter with pressure regulator and CE manometer.

**BP1 PLUS** (9245184)

Bead pressing arm, complete with selfstorage function, **GIULIANO patent**.

**QCK** (9208996)

Quick release kit for mounting tools (includes one plastic tool and one hub for connecting the tool delivered with the tire changer).

**SHS** (9209086)

Mounting/demounting tool for soft tires on steel wheels, including hub for connection to quick release kit (**QCK**)

**AHS** (9213611)

Mounting/demounting tool for arched spokes rims, including hub for connection to quick release kit (**QCK**).

**EHS** (9235009)

Mounting/demounting tool for iron wheels with projecting central hub, including hub for connection to quick release kit (**QCK**)

**QX** (9243338)

QX is a leverless mount/demount device, suitable for conventional, UHP and Run Flat tires. Exclusive **GIULIANO Patent**, it works in the same exact way of your traditional tire bar, but **without operator's manual force....**

**QXHS** (9230814)


Kit of **QX** adaptors for connection to quick release kit (**QCK**).

**HD** (9208633)

Manual bead depressor.

**PAD** (9237711)

Manual bead depressor with extendable travelling pad.

**ROLL** (9241924)

Fixed roller plate, to ease bead loosening of heavy wheels.

**SPK 1 (Lamborghini)** (9241383)

NYLON CONE FOR SPECIAL LAMBORGHINI WHEELS, allows clamping wheels with center hole diameter from 55 to 85 mm.

**SPK 2 (Porsche)** (9239459)

NYLON CONE FOR SPECIAL PORSCHE WHEELS, allows clamping wheels with center hole diameter from 60 to 85 mm.

**SPK 3 (BMW)** (9241717)

NYLON CONE FOR SPECIAL BMW WHEELS, allows clamping wheels with center hole diameter from 55 to 70 mm.

**WL 6** (9242824)

Pneumatic wheel lifter for passenger car type changers with foot control for the ascent and descent of the wheel. Pneumatic wheel lifter for car tire changer: facilitates the positioning of the wheel on the tire changer. Foot control for the ascent...

**QX-AD** (9232767)

QX, QX Plus adjusting tool and **LeverNoLever** System

**TPP 4** (9234452)

Kit of 10 rear plastic protections, for **QX, QX Plus** and **LeverNoLever** System

**TPP 5** (9234453)

Kit of 10 front plastic protections, for **QX** and **QX Plus** and **LeverNoLever** System

**CPC** (9214251)

Pressing cone for clamping RUN FLAT tires from outside.

**FRB** (9224675)

FRB is a special wheel centering kit, developed to easily and quickly clamp BMW wheels on Giuliano center post tyre changer, as required by BMW. BMW, particularly attentive to the stability of the clamping and the protection of rims and tyres, requires...



Scan QR code to go to product web page



Giuliano Industrial S.p.A.

via Guerrieri 6

Correggio (RE)

Italy

+39 0522 731111

+39 0522 633198

<https://www.giuliano-automotive.com>



Social Network



Facebook



YouTube



Twitter



www.giuliano-automotive.com