

**Automatic tilt-back tire change machine with dual assist arm**

Automatic tilt-back tire changer designed to efficiently change tires with the assistance of its dual assist arm, which aids in handling tires. Recommended for low-mid volume shops, garages and repair shops. Reliable user-friendly tire changer, advanced technology for enhanced performance.

**Description**

Automatic tilt-back tire change machine with dual assist arm. Recommended for low-mid volume shops, garages and repair shops.

Tire change machine with four control pedals, tilting tower, sliding horizontal arm and operating arm with manual lowering and locking by pushing button. Vertical arm with return spring. Equipped with dual assist arm.

**Functions**

- Tilting tower, sliding horizontal arm with Ø 41 mm operating arm.
- Bead loosener double effect Cylinder Ø 200 mm.
- Reinforced Chassis.
- Tabletop thickness 12 mm.
- Two powerful clamping cylinders provide uniform clamping pressure.
- Fitting head designed for both standard and low-profiled tire applications.
- Pneumatic locking of horizontal and operating arm.
- Plastic protections on fitting head to avoid any damage to alloy rim.
- Tire inflation by pedal (optional).
- Equipped with HP Light dual assist arm to ease mounting operations of low-profiled and UHP tires (standard).
- Additional bead lifting disk arm for the lower bead (optional).
- Additional roller tool arm for lower bead (optional).
- Rubber-coated jaw protectors. Provides extra grip (optional).
- Suitable for Tubeless tire bead seating system (optional).
- Designed, built and engineered in Italy.
- "Right to repair" - all service parts available for at least 10 years since production, easy maintenance and reduced environmental impact.

**Giuliano Industrial S.p.A.**

## Standard Features

Rim clamping range from outside	10" - 22" By adjustable jaws
Rim clamping range from inside	12" - 24" By adjustable jaws
Max. tire diameter	1010 mm (39")
Max. tire width	390 mm (15")
Bead loosener cylinder force at 10 Bar	30800 N
Operating pressure	10 bar (145 Psi)
Power supply	400 - 3Ph 220V - 1Ph
Motor power	0,55 kW (3ph)
Balancing speed	7 rpm
Pre-set tire inflating pressure	3,5 bar (50 Psi)
Net weight	310 Kg
Max overall dimensions	1420 x 1740 x 2010 mm



## Standard accessories





**PSI-G** (9299684)  
Extra-CE inflating gauge.



**BAR-G** (9298185)  
CE inflating gauge



**G-CLAMP** (9217471)  
G-CLAMP Set. Helps adding extra bead-pressure points on top bead while assembling it. Kit includes 2 regular and 2 extra-size G-clamps.



9242351  
Additional roller tool arm for lower bead



**PED-G** (9236373)  
Pedal operated inflating device.



**RJP** (9236282)  
Kit of rubber coated jaw protectors.



9242740  
Additional bead lifting disk arm for lower bead



**AWF** (9213425)  
Air filter with pressure regulator and CE manometer.



**T1** (9217472)  
Kit of 4 rubber protections for steel rims.



**T2** (9217473)  
Kit of 4 rubber protections for aluminium rims.



**T3** (9217474)  
Kit of 4 rubber protectors for aluminium rims with arched spokes.



**LB** (9216805)  
Lube paste bucket, 5 kg.



**GUN 1** (9236658)  
Tubeless inflation external kit.



**ORJP** (9216166)  
Kit of rubber protections for clamping rims from inside using conventional jaws.



**MOTO-AD** (9235081)  
Kit of 4 motorcycle wheels adaptors, 6" - 24", with screw lock.



**ATV-AD** (9235082)  
Kit of 4 adaptors for HARLEY DAVIDSON wheels, oversize height, 6" - 24", with screw lock.



**QCK** (9208996)  
Quick release kit for mounting tools (includes one plastic tool and one hub for connecting the tool delivered with the tire changer).



**SHS** (9209086)  
Mounting/demounting tool for soft tires on steel wheels, including hub for connection to quick release kit (**QCK**)



**AHS** (9213611)  
Mounting/demounting tool for arched spokes rims, including hub for connection to quick release kit (**QCK**).



**EHS** (9235009)  
Mounting/demounting tool for iron wheels with projecting central hub, including hub for connection to quick release kit (**QCK**)



**QXHS** (9230814)  
Kit of **QX** adaptors for connection to quick release kit (**QCK**).



**QX** (9243338)  
QX is a leverless mount/demount device, suitable for conventional, UHP and Run Flat tires. Exclusive GIULIANO **Patent**, it works in the same exact way of your traditional tire bar, but **without operator's manual force....**



**GHS** (9212850)  
Mounting tool for 6"-12" wheels with operating arm extension.



**QCB** (9218518)  
Quick release kit for motorcycle tire bead loosener blade.



**WL 6** (9242824)  
Pneumatic wheel lifter for passenger car type changers with foot control for the ascent and descent of the wheel. Pneumatic wheel lifter for car tire changer: facilitates the positioning of the wheel on the tire changer. Foot control for the ascent...



**QX-AD** (9232767)  
**QX, QX Plus** adjusting tool and **LeverNoLever** System



**TPP 4** (9234452)  
Kit of 10 rear plastic protections, for **QX, QX Plus** and **LeverNoLever** System



**TPP 5** (9234453)  
Kit of 10 front plastic protections, for **QX** and **QX Plus** and **LeverNoLever** System



**CPC** (9214251)  
Pressing cone for clamping RUN FLAT tires from outside.



Scan QR code to go to product web page



**Giuliano Industrial S.p.A.**

via Guerrieri 6

Correggio (RE)

Italy

+39 0522 731111

+39 0522 633198

<https://www.giuliano-automotive.com>



**Social Network**



Facebook



YouTube



Twitter



**[www.giuliano-automotive.com](https://www.giuliano-automotive.com)**