



Semiautomatic swing arm tire machine

Semi-automatic swing arm tire machine, 10"-24", equipped with lubricator, tire bar and inflation pressure regulator 3,5 Bar (50 Psi), double effect BB cylinder d.200 mm., double nylon protected professional fitting head.

Description

Semi-automatic swing arm tire machine, 10"-24", equipped with lubricator, tire bar and inflation pressure regulator 3,5 Bar (50 Psi), double effect BB cylinder d.200 mm., double nylon protected professional fitting head. The special designed mounting/demounting head provides great versatility and performance for even low profiled tires.

Functions

- Robust vertical tower, swinging horizontal arm with \square 35 mm operating arm;
- Bead loosener double effect Cylinder \varnothing 200 mm., made in aluminum;
- Reinforced Chassy;
- Tabletop thickness 12 mm;
- Fitting head designed for both standard and low profiled tire applications;
- Tire inflation by pedal (optional);
- Suitable for Tubeless tire bead seating system (optional);
- Suitable for Press Arm Eco (optional).

Giuliano Industrial S.p.A.

Standard Features

External clamping range	10" - 22" By adjustable jaws
Internal clamping range	12" - 24" By adjustable jaws
Max. tire diameter	1010 mm (39")
Max. tire width	330 mm (13")
Bead loosener cylinder force at 10 Bar	30800 N
Operating pressure	10 bar (145 psi)
Balancing speed	7 rpm
Power supply	400V - 3ph / 220V - 1ph
Motor power	0,55 kW (3 ph)
Air Inflation Pressure	3,5 bar (50 Psi)
Net weight	185 Kg
Dimensions (WxDxH)	1240 x 1060 x 1760 mm



Standard accessories

**G-CLAMP** (9217471)

G-CLAMP Set. Helps adding extra bead-pressure points on top bead while assembling it. Kit includes 2 regular and 2 extra-size G-clamps.

**RJP** (9236282)

Kit of rubber coated jaw protectors.

**T1** (9217472)

Kit of 4 rubber protections for steel rims.

**T2** (9217473)

Kit of 4 rubber protections for aluminium rims.

**T3** (9217474)

Kit of 4 rubber protectors for aluminium rims with arched spokes.

**LB** (9216805)

Lube paste bucket, 5 kg.

**PA ECO** (9236722)

PRESS ARM ECO additional arm to ease mounting operations of low profiled and UHP tires.

**PSI-G** (9299684)

Extra-CE inflating gauge.

**GUN 1** (9236658)

Tubeless inflation external kit.

**ORJP** (9216166)

Kit of rubber protections for clamping rims from inside using conventional jaws.

**MOTO-AD** (9235081)

Kit of 4 motorcycle wheels adaptors, 6" - 24", with screw lock.

**ATV-AD** (9235082)

Kit of 4 adaptors for HARLEY DAVIDSON wheels, oversize height, 6" - 24", with screw lock.

**QCK** (9208996)

Quick release kit for mounting tools (includes one plastic tool and one hub for connecting the tool delivered with the tire changer).

**SHS** (9209086)

Mounting/demounting tool for soft tires on steel wheels, including hub for connection to quick release kit (**QCK**).

**AHS** (9213611)

Mounting/demounting tool for arched spokes rims, including hub for connection to quick release kit (**QCK**).

**EHS** (9235009)

Mounting/demounting tool for iron wheels with projecting central hub, including hub for connection to quick release kit (**QCK**).

**QX** (9243338)

QX is a leverless mount/demount device, suitable for conventional, UHP and Run Flat tires. Exclusive **GIULIANO Patent**, it works in the same exact way of your traditional tire bar, but **without operator's manual force....**

**QXHS** (9230814)

Kit of **QX** adaptors for connection to quick release kit (**QCK**).

**HD** (9208633)

Manual bead depressor.

**PAD** (9237711)

Manual bead depressor with extendable travelling pad.



BAR-G (9298185)
CE inflating gauge



Scan QR code to go to product web page



Giuliano Industrial S.p.A.

via Guerrieri 6

Correggio (RE)

Italy

+39 0522 731111

+39 0522 633198

<https://www.giuliano-automotive.com>



Social Network



Facebook



YouTube



Twitter



www.giuliano-automotive.com