



Automatic tilt back tire machine with dual assist arm for car wheels 10" – 24"

Automatic tilt back tire machine, 10"-24", complete with dual assist pneumatic helper arm for easy operation on low profiled tires. Robust and convenient, reinforced chassis, air operated tilt-back tower, bead breaker double effect cylinder d.200 mm., made in aluminum, clamping capacity 10"-24".

Description

Automatic tilt back tire machine, 10"-24", complete with dual assist pneumatic helper arm (HP4) for easy and professional operation on low profiled, Ultra High Performance (UHP) and sport tires and wheels. Fast and intuitive to use, this represent ideal additional support in professional tire shop's performance business. Robust and convenient, this traditional automatic "Budget line" tire machine is equipped with powerful bead breaker cylinder, multi-assist helper arm, air operated tilt-back tower, turntable clamping capacity 10"-24" and. Special designed fitting head (provides great versatility and performance for even low profiled tires). Product designed for low-medium volume shops and professionals, or as a second machine in your shop.

Functions

- Tilting tower, sliding horizontal arm with \varnothing 41 mm operating arm;
- Bead breaker double effect cylinder \varnothing 200 mm., made in aluminum;
- Reinforced chassis;
- Tabletop thickness 12 mm;
- Fitting head designed for both standard and low profiled tire applications;
- CE inflating gauge (standard);
- Tire inflation by pedal (optional);
- Equipped with HP4 dual assist arm (standard);
- Suitable for Tubeless tire bead seating system (optional).

SILVERLINE

Best choice for great quality at a budget price.

Giuliano Industrial S.p.A.

Standard Features

External clamping range	10" - 22" By adjustable jaws
Internal clamping range	12" - 24" By adjustable jaws
Max. tire diameter	1010 mm (39")
Max. tire width	390 mm (15")
Bead loosener cylinder force at 10 Bar	30800 N
Operating pressure	10 bar (145 psi)
Balancing speed	7-14 rpm
Power supply	400V - 3ph - 2 speed 220V - 1ph
Motor power	0,75 / 1,125 kW (3 ph) 0,9 kW (1 ph)
Air Inflation Pressure	3,5 bar (50 Psi)
Net weight	300 Kg
Dimensions (WxDxH)	1420 x 1740 x 2010 mm



Standard accessories



HP4 (9246608)

HP4 additional double arm to ease mounting operations of low profiled and UHP tyres.

Not available for:

- Maxi Pro Series machines
- S 116
- S 116 Bike

**G-CLAMP** (9217471)

G-CLAMP Set. Helps adding extra bead-pressure points on top bead while assembling it. Kit includes 2 regular and 2 extra-size G-clamps.

**RJP** (9236282)

Kit of rubber coated jaw protectors.

**T1** (9217472)

Kit of 4 rubber protections for steel rims.

**T2** (9217473)

Kit of 4 rubber protections for aluminium rims.

**T3** (9217474)

Kit of 4 rubber protectors for aluminium rims with arched spokes.

**LB** (9216805)

Lube paste bucket, 5 kg.

**GUN 1** (9236658)

Tubeless inflation external kit.

**ORJP** (9216166)

Kit of rubber protections for clamping rims from inside using conventional jaws.

**MOTO-AD** (9235081)

Kit of 4 motorcycle wheels adaptors, 6" - 24", with screw lock.

**ATV-AD** (9235082)

Kit of 4 adaptors for HARLEY DAVIDSON wheels, oversize height, 6" - 24", with screw lock.

**QCK** (9208996)

Quick release kit for mounting tools (includes one plastic tool and one hub for connecting the tool delivered with the tire changer).

**SHS** (9209086)

Mounting/demounting tool for soft tires on steel wheels, including hub for connection to quick release kit (**QCK**).

**AHS** (9213611)

Mounting/demounting tool for arched spokes rims, including hub for connection to quick release kit (**QCK**).

**EHS** (9235009)

Mounting/demounting tool for iron wheels with projecting central hub, including hub for connection to quick release kit (**QCK**).

**QX** (9243338)

QX is a leverless mount/demount device, suitable for conventional, UHP and Run Flat tires. Exclusive GIULIANO **Patent**, it works in the same exact way of your traditional tire bar, but **without operator's manual force....**

**QXHS** (9230814)

Kit of **QX** adaptors for connection to quick release kit (**QCK**).

**PAD** (9237711)

Manual bead depressor with extendable travelling pad.

**QCK** (9208996)

Quick release kit for mounting tools (includes one plastic tool and one hub for connecting the tool delivered with the tire changer).

**SHS** (9209086)

Mounting/demounting tool for soft tires on steel wheels, including hub for connection to quick release kit (**QCK**).

**AHS** (9213611)

Mounting/demounting tool for arched spokes rims, including hub for connection to quick release kit (**QCK**).

**EHS** (9235009)

Mounting/demounting tool for iron wheels with projecting central hub, including hub for connection to quick release kit (**QCK**)

**QX** (9243338)

QX is a leverless mount/demount device, suitable for conventional, UHP and Run Flat tires. Exclusive GIULIANO **Patent**, it works in the same exact way of your traditional tire bar, but **without operator's manual force....**

**QXHS** (9230814)

Kit of **QX** adaptors for connection to quick release kit (**QCK**).

**HD** (9208633)

Manual bead depressor.

**PAD** (9237711)

Manual bead depressor with extendable travelling pad.

**WL 6** (9242824)

Pneumatic wheel lifter for passenger car type changers with foot control for the ascent and descent of the wheel. Pneumatic wheel lifter for car tire changer: facilitates the positioning of the wheel on the tire changer. Foot control for the ascent...

**QX-AD** (9232767)

QX, **QX Plus** adjusting tool and **LeverNoLever** System

**TPP 4** (9234452)

Kit of 10 rear plastic protections, for **QX**, **QX Plus** and **LeverNoLever** System

**TPP 5** (9234453)

Kit of 10 front plastic protections, for **QX** and **QX Plus** and **LeverNoLever** System

**CPC** (9214251)

Pressing cone for clamping RUN FLAT tires from outside.



Scan QR code to go to product web page



Giuliano Industrial S.p.A.

via Guerrieri 6

Correggio (RE)

Italy

+39 0522 731111

+39 0522 633198

<https://www.giuliano-automotive.com>



Social Network



Facebook



YouTube



Twitter



www.giuliano-automotive.com