



## **Automatic center post LEVER - NO LEVER tire changer for car wheels 10" – 28"**

Automatic center post LEVER - NO LEVER tire changer, 10" – 28", the best choice for the average tire shop with budget goal, robust and convenient, equipped with Lever-No-Lever (LNL) system, twisting arm/disk air operated bead breaker system, bead pressing arm, manual Press/Twist clamping device, air operated tilt-back tower, reinforced chassis and tower. MOTOINVERTER, for faster, more accurate and reliable drive for your tyre changer.

### Description

**Giuliano Industrial S.p.A.**

The information contained in this document is the sole property of Giuliano Automotive. The document is NOT authentic if it has been downloaded from a website different from [www.giuliano-automotive.com](http://www.giuliano-automotive.com).

## Standard Features

Rim clamping range	10" - 28"
Max. tire diameter	1200 mm (47")
Max. tire width	406 mm (16") <small>For reverse mounted wheels, variable according to rim features</small>
Bead loosener force	12307 N
Max. wheel weight	80 Kg
Operating pressure	8-10 bar (116-145 psi)
Power supply	230V - 1ph - 50/60 Hz
Motor power	0,75 kW - 2 speed
Balancing speed	7-16 rpm
Air Inflation Pressure	3,5 bar (50 Psi)
Net weight	350 Kg
Dimensions (WxDxH)	1185 x 1960 x 2120 mm



**SL 28 Pro Duo LNL**

Standard Accessories



**QX-AD** (9232767)

**QX, QX Plus** adjusting tool and  
**LeverNoLever** System

[www.giuliano-automotive.com](http://www.giuliano-automotive.com)

The information contained in this document is the sole property of Giuliano Automotive. The document is NOT authentic if it has been downloaded from a website different from [www.giuliano-automotive.com](http://www.giuliano-automotive.com).

**G-CLAMP** (9217471)

G-CLAMP Set. Helps adding extra bead-pressure points on top bead while assembling it. Kit includes 2 regular and 2 extra-size G-clamps.

**T1** (9217472)

Kit of 4 rubber protections for steel rims.

**T2** (9217473)

Kit of 4 rubber protections for aluminium rims.

**T3** (9217474)

Kit of 4 rubber protectors for aluminium rims with arched spokes.

**LB** (9216805)

Lube paste bucket, 5 kg.

**AWF** (9213425)

Air filter with pressure regulator and CE manometer.

**9230790N**

Pneumatic wheel positioner.

**TPP 4** (9234452)

Kit of 10 rear plastic protections, for **QX**, **QX Plus** and **LeverNoLever** System

**TPP 5** (9234453)

Kit of 10 front plastic protections, for **QX** and **QX Plus** and **LeverNoLever** System

**GUN 1** (9241827)

Tubeless inflation external kit.

**CPC** (9214251)

Pressing cone for clamping RUN FLAT tires from outside.

**FRB** (9224675)

FRB is a special wheel centering kit, developed to easily and quickly clamp BMW wheels on Giuliano center post tyre changer, as required by BMW. BMW, particularly attentive to the stability of the clamping and the protection of rims and tyres, requires...



Scan QR code to go to product web page



**Giuliano Industrial S.p.A.**

via Guerrieri 6

Correggio (RE)

Italy

+39 0522 731111

+39 0522 633198

<https://www.giuliano-automotive.com>



**Social Network**



Facebook



YouTube



Twitter



**Giuliano Industrial S.p.A.**

The information contained in this document is the sole property of Giuliano Automotive. The document is NOT authentic if it has been downloaded from a website different from [www.giuliano-automotive.com](http://www.giuliano-automotive.com).