



High-performance leverless tire changer with dual assist arm, patented 4 cylinders clamping turntable and patented PAR-MOVE system

High-performance leverless tire changer with dual assist arm, patented POWERX 4 cylinders clamping turntable and patented space-saving Par-Move system. Equipped with patented Leverless device (Lever-No Lever technology). PowerX four grants double (uniform) clamping power on jaws.

Description

High-performance leverless tire changer with dual assist arm, patented POWERX 4 cylinders clamping turntable and patented space-saving Par-Move system.

PAR-MOVE parallelogram type operating arm assembly enables the tire changer to be installed against the wall, requiring no additional rear space in the workshop. It also grants extremely powerful rigidity of the operating parts, through advanced ergonomic design, helping handle different types of tires in the easiest and most effortless way.

Equipped with patented Leverless device (Lever-No Lever technology) to make your job quick, safe and easy with all types of tires and wheels.

Patented PowerX four cylinders turntable grants double (uniform) clamping power on jaws.

High-performance tire changer for high volume tire shops.

Functions

- Robust fixed vertical tower with innovative **PAR-MOVE** parallelogram operating arm [Giuliano Patent]. **5 YEAR WARRANTY ON PAR-MOVE**
- **SPACE SAVER:** PAR-MOVE design enables the tire changer to be installed against the wall, requiring no additional rear space.
- **Reinforced Chassis.** Fixed vertical tower and parallelogram operating arm [Giuliano Patent] makes SX119Pro LNL extremely robust and stiff, granting increased rigidity and eliminating all flexes.
- Tabletop thickness 14 mm with **POWERX** four cylinders clamping system [Giuliano Patent]. **5 YEAR WARRANTY ON POWERX**
- **Lever-No-Lever** tire mounting/demounting system [Giuliano Patent], standard.
- HP119 Additional auxiliary helper system (standard) provides a valuable support in mounting/ demounting Run Flat, UHP and low profiled tyres.
- Bead breaker double effect Cylinder ø 200 mm.
- **5 YEARS WARRANTY** on "Made in Giuliano" gearbox.
- **PO System** [Giuliano Patent] for granting no bead breaker shovel stuck into the rim during bead breaking operations.
- Adjustable bead breaker shovel stroke. Super-quick and Simple.
- Double rotation speed by pedal.
- Available in 3ph-2 speed, 1ph-2 speed (inverter) and 1ph - 1 speed version.
- **MOTOINVERTER** for granting faster, more accurate and reliable drive for your tyre changer
- Tire inflation by pedal (standard).
- Vertical tower with built-in air tank, provides tubeless tire inflation and bead seating (optional), eliminating the need for a separate air tank.
- Suitable for Tubeless tyre bead seating system (optional).
- "Easy Access" extractable pedal box for quick service.
- Extensive selection of standard accessories
- A very practical Wheel Lifter reduces effort and increases productivity (optional).
- Designed, built and engineered in Italy.
- "Right to repair" - all service parts available for at least 10 years since production, easy maintenance and reduced environmental impact.

Giuliano Industrial S.p.A.

Standard Features

External clamping range	10" - 27"
Internal clamping range	12" - 29"
Max. tire diameter	1100 mm (43")
Max. tire width	415 mm (16")
Bead loosener force	30800 N
Operating pressure	10 bar (145 psi)
Power supply	400V - 3ph - 2 speed 220V - 1ph 220V - 1ph - 2 speed
Motor power	0,8 / 1,1 kW (3ph)
Balancing speed	7-14 rpm
Air Inflation Pressure	3,5 bar (50 Psi)
Net weight	428 Kg
Dimensions (WxDxH)	1390 x 1350 x 2170 mm



Standard accessories



QX-AD (9232767)

QX, QX Plus adjusting tool and
LeverNoLever System



**G-CLAMP** (9217471)

G-CLAMP Set. Helps adding extra bead-pressure points on top bead while assembling it. Kit includes 2 regular and 2 extra-size G-clamps.

**RJP** (9236282)

Kit of rubber coated jaw protectors.

**T1** (9217472)

Kit of 4 rubber protections for steel rims.

**T2** (9217473)

Kit of 4 rubber protections for aluminium rims.

**T3** (9217474)

Kit of 4 rubber protectors for aluminium rims with arched spokes.

**LB** (9216805)

Lube paste bucket, 5 kg.

**AWF** (9213425)

Air filter with pressure regulator and CE manometer.

**GUN 1** (9236658)

Tubeless inflation external kit.

**ORJP** (9216166)

Kit of rubber protections for clamping rims from inside using conventional jaws.

**MOTO-AD** (9235081)

Kit of 4 motorcycle wheels adaptors, 6" - 24", with screw lock.

**ATV-AD** (9235082)

Kit of 4 adaptors for HARLEY DAVIDSON wheels, oversize height, 6" - 24", with screw lock.

**GHS** (9246170)

Mounting tool for 6"-12" wheels with operating arm extension.

**UHP6** (9245051)

Kit Run Flat UHP

**WL 6** (9242824)

Pneumatic wheel lifter for passenger car type changers with foot control for the ascent and descent of the wheel. Pneumatic wheel lifter for car tire changer: facilitates the positioning of the wheel on the tire changer. Foot control for the ascent...

**TPP 4** (9234452)

Kit of 10 rear plastic protections, for **QX**, **QX Plus** and **LeverNoLever** System

**TPP 5** (9234453)

Kit of 10 front plastic protections, for **QX** and **QX Plus** and **LeverNoLever** System

**CPC** (9214251)

Pressing cone for clamping RUN FLAT tires from outside.



Scan QR code to go to product web page



Giuliano Industrial S.p.A.

via Guerrieri 6

Correggio (RE)

Italy

+39 0522 731111

+39 0522 633198

<https://www.giuliano-automotive.com>



Social Network



Facebook



YouTube



Twitter



Giuliano Industrial S.p.A.