





# High performance super automatic tilt back tire changer machine with combined two assist arms and Power X

High performance super automatic tilt back tire changer for tires with rim from 10" to 29" (max. wheel diameter 1120 mm./44", max. wheel width 406mm./16"). Equipped with two assist arms, to provide a valuable support in mounting/demounting Run Flat, UHP and low profiled tires. Power X four cylinders turntable, Giuliano Patent.

#### Description

High performance super automatic tilt back tire changer machine with combined two assist arms and Power X.

High performance tilt back tire changer machine for tires with rim from 10" to 29" (max. wheel diameter 1120 mm./44", max. wheel width 406mm./16"). Equipped with Help and Press Arm powerful pneumatic helper systems, to enhance tire changer machine's performance and provide a valuable support in mounting/demounting most difficult tire applications in the market, such as Run Flat, UHP and low profiled tires.

Power X four cylinders turntable (Giuliano Patent) grants double, uniform clamping power on jaws, and an almost endless durability and reliability of your turntable!

The squared horizontal arm is equipped with Quadra Lock combined rear and front locking mechanism. This system removes every flexion or slack to the working arm during operations with UHP and Run Flat tires, thus granting the same performance level over time, and making the tire changer machine more reliable than ever before.

Reliable, robust and high-performance product with great capacity.

SX 234 Pro Duo is the state-of-the-art conventional tire changer machine, developed by Giuliano for high volume tire shops, and tire specialists, servicing racing, run flat and UHP tires, that is, for all tire professionals, who have to deal with most diverse tires every day, but want to work with simplicity and without efforts.

The real "work-horse" for your tire shop!! New unstoppable, robust, tireless tire changer machine to always support the wheel service specialist. Everything you need for a busy shop dealing with all kinds of CAR, LCV and LIGHT TRUCK tires and wheels (motorcycle tire fitting options available)!!

#### Functions

- Tilt-back tower, sliding horizontal arm with ø 41 mm operating arm.
- Robust bead breaker arm, designed for tough jobs.
- Bead breaker double effect Cylinder ø 200 mm.
- Reinforced Chassy and tower.
- Reliable and durable clamping system. Tabletop thickness 14 mm with POWERX four cylinders clamping system [Giuliano Patent]. 5 YEAR WARRANTY on POWERX.
- Patented PO SYSTEM (standard) automatically moves the bead breaker shovel back to the starting position, after its penetration.
- Adjustable bead breaker shovel stroke.
- QuadraLock system for total stiff locking of horizontal and operating arm. QuadraLock system removes every possible flexion or slack during operations with UHP and Run Flat tires, thus granting the same performance level over time.
- 5 YEARS WARRANTY on "Made in Giuliano" gearbox.
- Fitting head designed for both standard and low profiled tire applications.
- Double rotation speed by pedal.
- Tire inflation by pedal (standard).
- Equipped with Help and Press Arm additional auxiliary helper systems (standard) to ease mounting operations of low profiled, Run Flat and UHP tires.
- "Easy Access" extractable pedal box for quick service.
- Robotic pipe for operating arm positioning/lock.
- Tools Storage Box (standard).
- MOTOINVERTER for granting faster, more accurate and reliable drive for your tire changer machine.
- Suitable for Patented QX Leverless mounting device for low profiled and UHP tires (optional).
- Suitable for Tubeless tire bead seating system (optional).
- A very practical Wheel Lifter reduces effort and increases productivity (optional).
- Fixed roller plate, to ease bead breaking of heavy wheels (optional).
- Designed, built and engineered in Italy.
- 24 months STANDARD WARRANTY on all Giuliano Parts and 5 YEARS WARRANTY on our key and patented components.
- "Right to repair" all service parts available for at least 10 years since production, easy maintenance and reduced environmental impact.

cap	oduct designed for intensive use, for high volume professionals, who need reliable, robust and high-performance product with great pacity, even on toughest tire applications.  OK: Version available upon request
	tensive selection of standard accessories: bead lifting lever, lube paste bucket and brush, plastic protectors for mounting/demounting tool, protectors for bead breaker shovel, jaw protectors for alloy rims, lubricator + pressure regulator, bucket support

External clamping range	10" - 27"
Internal clamping range	12" - 29"
Max. tire diameter	1120 mm (44")
Max. tire width	406 mm (16")
Bead loosener force	30800 N
Operating pressure	10 bar (145 psi)
Power supply	220V - 1ph - 2speed
Motor power	0,75 kW (1ph)
Balancing speed	7-16 rpm
Air Inflation Pressure	3,5 bar (50 Psi)
Net weight	400 Kg
Dimensions (WxDxH)	1900 x 1950 x 2190 mm



### Standard Accessories



Standard accessories





Optional Accessories





### **G-CLAMP** (9217471)

G-CLAMP Set. Helps adding extra beadpressure points on top bead while assembling it. Kit includes 2 regular and 2 extra-size Gclamps.



#### RJP (9236282)

Kit of rubber coated jaw protectors.



#### T1 (9217472)

Kit of 4 rubber protections for steel rims.



#### T2 (9217473)

Kit of 4 rubber protections for aluminium rims.



### T3 (9217474)

Kit of 4 rubber protectors for aluminium rims with arched spokes.



#### LB (9216805)

Lube paste bucket, 5 kg.



#### AWF (9213425)

Air filter with pressure regulator and CE manometer.



# **UHP1** (9240576)

Kit Run Flat UHP



#### **GUN 1** (9236658)

Tubeless inflation external kit.



#### **ORJP** (9216166)

Kit of rubber protections for clamping rims from inside using conventional jaws.



### MOTO-AD (9235081)

Kit of 4 motorcycle wheels adaptors, 6" - 24", with screw lock.



### ATV-AD (9235082)

Kit of 4 adaptors for HARLEY DAVIDSON wheels, oversize height, 6" - 24", with screw lock.



### QCK (9208996)

Quick release kit for mounting tools (includes one plastic tool and one hub for connecting the tool delivered with the tire changer).



# **SHS** (9209086)

Mounting/demounting tool for soft tires on steel wheels, including hub for connection to quick release kit (**QCK**)



### **AHS** (9213611)

Mounting/demounting tool for arched spokes rims, including hub for connection to quick release kit (**QCK**).



### EHS (9235009)

Mounting/demounting tool for iron wheels with projecting central hub, including hub for connection to quick release kit (QCK)



### QX (9243338)

QX is a leverless mount/demount device, suitable for conventional, UHP and Run Flat tires. Exclusive GIULIANO **Patent**, it works in the same exact way of your traditional tire bar, but **without operator's manual force...** 



#### GHS (9212850)

Mounting tool for 6"-12" wheels with operating arm extension.



### **QXHS** (9230814)

Kit of **QX** adaptors for connection to quick release kit (**QCK**).



### HD (9208633)

Manual bead depressor.





**Optional Accessories** 






PAD (9237711)

Manual bead depressor with extendable travelling pad.



### WL 6 (9242824)

Pneumatic wheel lifter for passenger car type changers with foot control for the ascent and descent of the wheel. Pneumatic wheel lifter for car tire changer: facilitates the positioning of the wheel on the tire changer. Foot control for the ascent...



QX, QX Plus adjusting tool and LeverNoLever System



TPP 4 (9234452)

Kit of 10 rear plastic protections, for **QX**, **QX Plus** and **LeverNoLever** System



### **TPP 5** (9234453)

Kit of 10 front plastic protections, for **QX** and **QX Plus** and **LeverNoLever** System



### **CPC** (9214251)

Pressing cone for clamping RUN FLAT tires from outside.



References



Scan QR code to go to product web page



## Giuliano Industrial S.p.A.

via Guerrieri 6 Correggio (RE)

Italy

+39 0522 731111

+39 0522 633198

https://www.giuliano-automotive.com



# **Social Network**















