S 810

Digital electronic wheel balancing machine with LED display

Digital electronic wheel balancing machine with LED display.

Description

The wheel balancing machine is standard supplied with cones and quick clamping ring nut.

Functions

- Manual measuring of wheel diameter and distance;
- Automatic START and STOP;
- Static and dynamic balancing;
- Huge combination of ALU programs;
- Special ALU-S program;
- **FES** function;

Giuliano Industrial S.p.A.

The information contained in this document is the sole property of Giuliano Automotive. The document is NOT authentic if it has been downloaded from a website different from www.giuliano-automotive.com.

Standard Features

Max. wheel weight	75 kg
Max. tire diameter	900 mm
Rim diameter	10"-30" / 255-765 mm
Rim width	1.5"-20" / 40-510 mm
Power supply	230V - 1ph - 50/60 Hz
Unbalance detection time	6s (5 3/4 "x 14") 15 Kg
Balancing speed	< 100 rpm
Balancing precision	± 1g
Net weight	85 kg
Dimensions (WxDxH)	550 x 480 x 987 mm

The information contained in this document is the sole property of Giuliano Automotive. The document is NOT authentic if it has been downloaded from a website different from www.giuliano-automotive.com.

Cones and quick clamping ring nut

Manual gauge for measuring wheel rim width

Counterweight pliers

The information contained in this document is the sole property of Giuliano Automotive. The document is NOT authentic if it has been downloaded from a website different from www.giuliano-automotive.com.

UNILUG (9342855)
Wheel clamping adaptor for wheels without central hole or with special flanging

9342856
Kit of 5 quick-lock centering stud bolts for Unilug

9342860
Set of 5 extra-long spherical nuts for Unilug

9342861
Clamping cone with spacer for SUV and 4WD wheels; central hole diam. 122-174 mm

9342862
Clamping cone with spacer for clamping wheels of LCVs and vans; central hole diam. 198-225 mm

9342863
Special cone for clamping wheels from outside; central hole diam. 100-118 mm

9342867
Spacer kit for clamping SUV or 4WD all terrain wheels, to prevent the wheel from touching wheelbalancer baseframe.

QUICKPLATE (9342864)
Wheel clamping adaptor with flange and 4 centering stud bolts, for wheels with max. 4 lug holes

QUICKPLATE (9342865)
Wheel clamping adaptor with flange and 5 centering stud bolts, for wheels with max. 5 lug holes

QUICKPLATE (9342866)
Wheel clamping adaptor with flange and 6 centering stud bolts, for wheels with max. 6 lug holes

RL (9314901)
RL protective sleeve for alloy rims.

PRU 810 (9336589)
Wheel guard for **S810**

WBL81 (9437137)
WBL81 wheel lift for all Giuliano wheel balancers. Designed and built in Italy. New state of the art technology enables the wheel lift to be installed on almost all wheel balancers in the market. Easy positioning and centering on the shaft, without any...

The information contained in this document is the sole property of Giuliano Automotive. The document is NOT authentic if it has been downloaded from a website different from www.giuliano-automotive.com.

Scan QR code to go to product web page

Giuliano Industrial S.p.A.
via Guerrieri 6
Correggio (RE)
Italy
+39 0522 731111
+39 0522 633198
https://www.giuliano-automotive.com

Social Network

Facebook

YouTube

Twitter

Giuliano Industrial S.p.A.
The information contained in this document is the sole property of Giuliano Automotive. The document is NOT authentic if it has been downloaded from a website different from www.giuliano-automotive.com.