



Digital electronic wheel balancer with led display for motorcycle wheels

Digital electronic wheel balancer with led display for motorcycle wheels.

Description

Digital electronic wheel balancer with led display for motorcycle wheels.

Functions

- Manual measuring of wheel diameter and distance;
- Automatic START and STOP;
- Static and dynamic balancing;
- Huge combination of **ALU programs**;
- Special **ALU-S** program;
- **FES** function;
- **OPTIMATCH** function;
- Self-diagnosis;
- Self-calibration;
- Complete with **ProBike Eco Kit** clamping adaptor for motorcycle wheels;
- Wheel guard available as optional.

Giuliano Industrial S.p.A.

Standard Features

Max. wheel weight	75 kg
Max. tire diameter	900 mm
Rim diameter	10"-30" / 255-765 mm
Rim width	1.5"-20" / 40-510 mm
Power supply	230V - 1ph - 50/60 Hz
Unbalance detection time	6.0s (5 3/4" x 14") 15 Kg
Balancing speed	< 100 rpm
Balancing precision	± 1g
Net weight	85 kg
Dimensions (WxDxH)	970x480x987 mm




PROBIKE EKO KIT (9341191)
Clamping adaptor for motorcycle wheels.
Complete with 14 mm diam. shaft. and Quick
Fix quick clamping device



Counterweight pliers



Manual gauge for measuring wheel rim width



9342850
Set of 28 mm centering rings for ProBike Eco Kit with 14 mm diam. shaft



9342851
19 mm diam. shaft with complete set of centering rings, adaptors and Quick Fix quick clamping device, for ProBike Eco



PROFI KIT (9342852)
Set of special adaptors for 19 mm diam. shaft on ProBike Eco



9342853
10 mm diam. shaft with adaptors, for ProBike Eco



UNILUG (9342855)
Wheel clamping adaptor for wheels without central hole or with special flanging



9342856
Kit of 5 quick-lock centering stud bolts for Unilug



9342860
Set of 5 extra-long spherical nuts for Unilug



9342861
Clamping cone with spacer for SUV and 4WD wheels; central hole diam. 122-174 mm



9342862
Clamping cone with spacer for clamping wheels of LCVs and vans; central hole diam. 198-225 mm



9342867
Spacer kit for clamping SUV or 4WD all terrain wheels, to prevent the wheel from touching wheelbalancer baseframe.



QUICKPLATE (9342864)
Wheel clamping adaptor with flange and 4 centering stud bolts, for wheels with max. 4 lug holes



QUICKPLATE (9342865)
Wheel clamping adaptor with flange and 5 centering stud bolts, for wheels with max. 5 lug holes



QUICKPLATE (9342866)
Wheel clamping adaptor with flange and 6 centering stud bolts, for wheels with max. 6 lug holes



RL (9314901)
RL protective sleeve for alloy rims.



WBL81 (9437137)
WBL81 wheel lift for all Giuliano wheel balancers. Designed and built in Italy. New state of the art technology enables the wheel lift to be installed on almost all wheel balancers in the market. Easy positioning and centering on the shaft, without any...



Scan QR code to go to product web page



Giuliano Industrial S.p.A.

via Guerrieri 6

Correggio (RE)

Italy

+39 0522 731111

+39 0522 633198

<https://www.giuliano-automotive.com>



Social Network



Facebook



YouTube



Twitter



Giuliano Industrial S.p.A.

The information contained in this document is the sole property of Giuliano Automotive. The document is NOT authentic if it has been downloaded from a website different from www.giuliano-automotive.com.