



Super Automatic Leverless Tyre Changer

Super automatic leverless tyre changer, with no use of the bead lifting lever, suitable for passenger car tyres with rims 12"-34" (max. wheel diam. 1200 mm./47", max. wheel width 406 mm./16"). Equipped with ultra-quick wheel clamping system.

Description

Super automatic leverless tyre changer, with **no use** of the **bead lifting lever**, suitable for **passenger car tyres** with rims 12"-34" (max. wheel diam. 1200 mm./47", max. wheel width 406 mm./16"). Equipped with single arm/disk air operated bead breaker system and with patented ultra-quick wheel clamping system. Suggested for top professional tyre specialists, servicing run flat and UHP tyres with no tool/rim contact.

Functions

- Single arm/disk air operated bead breaker system;
- Reinforced Chassy and Tower;
- **Patented SMART LOCK** ultra-quick wheel clamping system, through cone and shaft with Smart Lock nut;
- Equipped with QX **no contact** mount/demount system, **Giuliano Patent**;
- Double rotation speed by pedal, clockwise (motoinverter);
- **Tyre inflation** by pedal (standard);
- Operated by pedal and control console;
- Equipped with Press Arm (standard);
- Suitable for Tyre Lift (optional);
- Suitable for **Tubeless tyre** bead seating system (optional).

WDK: Version available upon request

Giuliano Industrial S.p.A.

The information contained in this document is the sole property of Giuliano Automotive. The document is NOT authentic if it has been downloaded from a website different from www.giuliano-automotive.com.

Standard Features

Rim clamping range	12" - 34"
Max. tyre diameter	1200 mm (47")
Max. tyre width	406 mm (16")
Bead breaker force at 10 bar	12037 N
Operating pressure	8-10 bar (116-145 psi)
Power supply	220V - 1ph / 2 speed
Motor power	0,75 kW
Balancing speed	7-16 rpm
Pre-set tyre inflating pressure	3,5 bar (50 psi)
Net weight	375 Kg
Max overall dimensions	1185x1960x2120 mm



Standard accessories



PED-G (9236373)
Pedal operated inflating device.



AWF (9213425)
Air filter with pressure regulator and CE manometer.



FPM456 (9234045)
Wheel clamping adaptor for reverse mounted wheels and wheels with no center hole



9234046
Kit of 7 long conical pins for **FPM456**



9234047
Kit of 6 spheric pins for **FPM456**



9219117
Truck cone kit, allows clamping VANs and LCVs wheels with center hole diameter from 120 to 190 mm.



LTK5 (9234456)
Double face cone for light trucks, allows clamping VANs and LCVs wheels with center hole diameter from 75 to 145 mm.



LTK6 (9233680)
Cone for steel rims with low thickness and center hole diameter from 75 to 120 mm



G-CLAMP (9217471)
G-CLAMP Set. Helps adding extra bead-pressure points on top bead while assembling it. Kit includes 2 regular and 2 extra-size G-clamps.



T1 (9217472)
Kit of 4 rubber protections for steel rims.



T2 (9217473)
Kit of 4 rubber protections for aluminium rims.



T3 (9217474)
Kit of 4 rubber protectors for aluminium rims with arched spokes.



LB (9216805)
Lube paste bucket, 5 kg.



SPCR (9230635)
Kit of 2 shims for ring nut.



P-Bar (9234455)
Plastic tyre lever for soft tyres removing operations. To be used during tyre demounting in accordance with the WDK procedure.



CPP 2 (9233318)
Kit of 10 ABS protections for cone.



FPP 1 (9234454)
Kit of 10 rubber protections for clamping chuck faceplate



MATCH (9231511)
Additional disk arm for tyre / wheel matching.



PAD (9233410)
Longer bead pressing tool for Press Arm.



WL 1/B (9235495)
Air operated wheel positioner.



WL 3 (9236465)
Pneumatic wheel positioner.



GUN 3 (9236665)
Tubeless inflation external kit.



UHP3 (9238774)
Kit Run Flat UHP



ROLL (9207933)
Fixed roller plate, to ease bead breaking of heavy wheels.



Scan QR code to go to product web page



Giuliano Industrial S.p.A.

via Guerrieri 6

Correggio (RE)

Italy

+39 0522 731111

+39 0522 633198

<https://www.giuliano-automotive.com>



Social Network



Facebook



YouTube



Twitter



www.giuliano-automotive.com