





PAR-MOVE Concept High Performance Super-Automatic Tyre Changer

PAR-MOVE concept high performance super-automatic tyre changer. For high volume tyre shops.

Description

PAR-MOVE concept high performance super-automatic tyre changer. For high volume tyre shops.

Functions

- Robust fixed vertical tower with innovative parallelogram operating arm (PAR-MOVE Concept).
- Bead breaker double effect Cylinder Ø 200 mm.
- Reinforced Chassis. Fixed vertical tower and parallelogram operating arm makes S119 extremely robust and stiff, granting increased rigidity and eliminating all flexes.
- Tabletop thickness 14 mm.
- Fitting head designed for both standard and low profiled tyre applications.
- Double rotation speed by pedal.
- Tyre inflation by pedal (standard).
- Suitable for Tubeless tyre bead seating system (optional).
- "Easy Access" extractable pedal box for quick service.
- PO System, Giuliano patent, for granting no bead breaker shovel stuck into the rim during bead breaking operations.
- Suitable for Wheel Lifter (optional).

Rim clamping range from outside	10" - 24" By adjustable jaws
Rim clamping range from inside	12" - 26" By adjustable jaws
Max. tyre diameter	1100 mm (43")
Max. tyre width	415 mm (16")
Bead breaker cylinder force at 10 Bar	30800 N
Operating pressure	10 bar (145 Psi)
Power supply	400V - 3Ph/2 speed
	220V - 1Ph
	220V - 1Ph/2 speed
Motor power	0,8 / 1,1 kW (3ph)
Balancing speed	7 - 14 rpm
Pre-set tyre inflating pressure	3,5 bar (50 Psi)
Net weight	316 Kg
Max overall dimensions	1390 x 1310 x 2170 mm



5 1 1 9Standard Accessories





Standard accessories



PED-G (9236373) Pedal operated inflating device.



AWF (9213425) Air filter with pressure regulator and CE manometer.



5 1 1 9Optional Accessories





G-CLAMP (9217471)

G-CLAMP Set. Helps adding extra beadpressure points on top bead while assembling it. Kit includes 2 regular and 2 extra-size Gclamps.



GUN 4 (9245186)

Tubeless inflation external kit



RJP (9236282)

Kit of rubber coated jaw protectors.



T1 (9217472)

Kit of 4 rubber protections for steel rims.



T2 (9217473)

Kit of 4 rubber protections for aluminium rims.



T3 (9217474)

Kit of 4 rubber protectors for aluminium rims with arched spokes.



LB (9216805)

Lube paste bucket, 5 kg.



BP1 PLUS (9245184)

Bead pressing arm, complete with selfstorage function, **GIULIANO patent**.



ORJP (9216166)

Kit of rubber protections for clamping rims from inside using conventional jaws.



MOTO-AD (9235081)

Kit of 4 motorcycle wheels clamping adaptors, 6" - 24", with screw lock.



ATV-AD (9235082)

Kit of 4 clamping adaptors for HARLEY DAVIDSON wheels, oversize height, 6" - 24", with screw lock.



QCK (9208996)

Quick release kit for mounting tools (includes one plastic tool and one hub for connecting the tool delivered with the tyre-changer).



SHS (9209086)

Mounting/demounting tool for soft tyres on steel wheels, including hub for connection to quick release kit (**QCK**)



AHS (9213611)

Mounting/demounting tool for arched spokes rims, including hub for connection to quick release kit (**QCK**).



EHS (9235009)

Mounting/demounting tool for iron wheels with projecting central hub, including hub for connection to quick release kit (**QCK**)



QX (9243338)

QX is a leverless mount/demount device, suitable for conventional, UHP and Run Flat tyres. Exclusive GIULIANO **Patent**, it works in the same exact way of your traditional tyre bar, but **without operator's manual force....**



QXHS (9230814)

Kit of **QX** adaptors for connection to quick release kit (**QCK**).



PAD (9237711)

Manual bead depressor with extendable travelling pad.



HD (9208633)


Manual bead depressor.



ROLL (9241924)

Fixed roller plate, to ease bead breaking of heavy wheels.











WL 6 (9242824) Pneumatic wheel lifter for passenger car type changers with foot control for the ascent and descent of the wheel. Pneumatic wheel lifter for car tyre changer: facilitates the positioning of the wheel on the tyre changer. Foot control for the ascent...



HP2 (9219399)

HP2 additional double arm to ease mounting operations of low profiled and UHP tyres.





Scan QR code to go to product web page



Giuliano Industrial S.p.A.

via Guerrieri 6 Correggio (RE)

Italy

+39 0522 731111

+39 0522 633198

https://www.giuliano-automotive.com



Social Network













