



Automatic tilt-back professional tyre changer with helper arm

Automatic tilt-back professional tyre changer with helper arm. For high volume tyre shops, servicing racing, run flat and UHP tyres.

Description

Automatic tilt-back professional tyre changer with helper arm. For high volume tyre shops, servicing racing, run flat and UHP tyres.

Functions

- Tilting tower, sliding horizontal arm with Ø 41 mm operating arm;
- Bead breaker double effect Cylinder Ø 200 mm;
- Reinforced Chassis and Tower;
- Tabletop thickness 14 mm;
- Fitting head designed for both standard and low profiled tyre applications;
- Double rotation speed by pedal;
- Tyre inflation by pedal (standard);
- Equipped with HP Light dual assist arm (standard);
- Suitable for Tubeless tyre bead seating system (optional);
- "Easy Access" extractable pedal box for quick service.

Giuliano Industrial S.p.A.

Standard Features

Rim clamping range from outside	10" - 24" By adjustable jaws
Rim clamping range from inside	12" - 26" By adjustable jaws
Max. tyre diameter	1100 mm (43")
Max. tyre width	415 mm (16")
Bead breaker cylinder force at 10 Bar	30800 N
Operating pressure	10 bar (145 Psi)
Power supply	400V - 3ph / 2 speed 220V - 1ph
Motor power	0,8/1,1 kW (3ph)
Rotating speed	7-14 rpm
Pre-set tyre inflating pressure	3,5 bar (50 Psi)
Net weight	350 Kg
Max overall dimensions	1590 x 1890 x 2040 mm



Standard accessories



PED-G (9236373)
Pedal operated inflating device.



AWF (9213425)
Air filter with pressure regulator and CE
manometer.



G-CLAMP (9217471)
G-CLAMP Set. Helps adding extra bead-pressure points on top bead while assembling it. Kit includes 2 regular and 2 extra-size G-clamps.



9242351
Additional roller tool arm for lower bead



9242740
Additional bead lifting disk arm for lower bead



RJP (9236282)
Kit of rubber coated jaw protectors.



T1 (9217472)
Kit of 4 rubber protections for steel rims.



T2 (9217473)
Kit of 4 rubber protections for aluminium rims.



T3 (9217474)
Kit of 4 rubber protectors for aluminium rims with arched spokes.



LB (9216805)
Lube paste bucket, 5 kg.



GUN 1 (9236658)
Tubeless inflation external kit.



ORJP (9216166)
Kit of rubber protections for clamping rims from inside using conventional jaws.



MOTO-AD (9235081)
Kit of 4 motorcycle wheels clamping adaptors, 6" - 24", with screw lock.



ATV-AD (9235082)
Kit of 4 clamping adaptors for HARLEY DAVIDSON wheels, oversize height, 6" - 24", with screw lock.



QCK (9208996)
Quick release kit for mounting tools (includes one plastic tool and one hub for connecting the tool delivered with the tyre-changer).



SHS (9209086)
Mounting/demounting tool for soft tyres on steel wheels, including hub for connection to quick release kit (**QCK**)



AHS (9213611)
Mounting/demounting tool for arched spokes rims, including hub for connection to quick release kit (**QCK**).



EHS (9235009)
Mounting/demounting tool for iron wheels with projecting central hub, including hub for connection to quick release kit (**QCK**)



QXHS (9230814)
Kit of **QX** adaptors for connection to quick release kit (**QCK**).



QX (9243338)
QX is a leverless mount/demount device, suitable for conventional, UHP and Run Flat tyres. Exclusive GIULIANO **Patent**, it works in the same exact way of your traditional tyre bar, but **without operator's manual force....**



GHS (9212850)
Mounting tool for 6"-12" wheels with operating arm extension.



WL 6 (9242824)
Pneumatic wheel lifter for passenger car type changers with foot control for the ascent and descent of the wheel. Pneumatic wheel lifter for car tyre changer: facilitates the positioning of the wheel on the tyre changer. Foot control for the ascent.



Scan QR code to go to product web page



Giuliano Industrial S.p.A.

via Guerrieri 6

Correggio (RE)

Italy

+39 0522 731111

+39 0522 633198

<https://www.giuliano-automotive.com>



Social Network



Facebook



YouTube



Twitter



Giuliano Industrial S.p.A.