

**Two speed tilt-back tyre changer for racing tyres with new flower power wheel clamping system**

Super automatic Tyre changer, specially designed for Racing and oversized wheels, ideal for tire specialists; suitable for any wheel of passenger cars, motorcycles and LCVs 10"-28" (max. diameter 1200mm./47", max. wheel width 406mm./16").

**Description**

Super automatic Tyre changer, specially designed for Racing and oversized wheels, ideal for tire specialists; suitable for any wheel of passenger cars, motorcycles and LCVs 10"-28" (max. diameter 1200mm./47", max. wheel width 406mm./16"). Equipped with new wheel clamping system **FLOWER POWER**, with 4 air cylinders and racks, and with two speed bidirectional rotation system for turntable (selection by hand).

**Features**

- Turntable with Flower Power four-cylinders and racks clamping system, 26" external clamping;
- Oversize column, tilt back (pedal operated), equipped with integrated locking/adjustment mechanism for horizontal arm and hex bar;
- Pneumatic control for up/down movement of hex bar operating arm;
- Adjustable bead breaker arm, with "traditional rounded" or "GIULIANO parallelogram" movement, to keep a constant angle of the shovel on the tire bead;
- Bead breaker shovel adjustable according to the tire type;
- Oversize body, with bead breaker pedal in user-friendly position;
- Extractable pedal box;
- Motor 400V-3ph-50Hz, 2 speed;
- Standard equipped with Help4 and Press Arm3, pneumatic towers to ease fitting/removing operations on low profiled and Run Flat tires, and with dynamic tire- assist roll-plate, to help rotating tire and wheel while breaking the bead;

WDK: Version available upon request

**Giuliano Industrial S.p.A.**

The information contained in this document is the sole property of Giuliano Automotive. The document is NOT authentic if it has been downloaded from a website different from [www.giuliano-automotive.com](http://www.giuliano-automotive.com).

## Standard Features

---

Rim clamping range	10" - 28"
Max. tyre diameter	1200 mm (47")
Max. tyre width	406 mm (16")
Max. bead-breaker cylinder force	30900 N
Operating pressure	10 bar (145 psi)
Rotating speed	7-14 rpm
Power supply	400 V 3ph
Motor power	0,8-1,1 kW
Max. spindle torque	1200 Nm
Inflating pressure limiting device max.	3,5 bar (50 psi)
Net weight	461 kg



**S 233 FP**  
Standard Accessories



**[www.giuliano-automotive.com](http://www.giuliano-automotive.com)**

The information contained in this document is the sole property of Giuliano Automotive. The document is NOT authentic if it has been downloaded from a website different from [www.giuliano-automotive.com](http://www.giuliano-automotive.com).



**QX** (9243338)

QX is a leverless mount/demount device, suitable for conventional, UHP and Run Flat tyres. Exclusive GIULIANO **Patent**, it works in the same exact way of your traditional tyre bar, but **without operator's manual force....**



Scan QR code to go to product web page



**Giuliano Industrial S.p.A.**

via Guerrieri 6

Correggio (RE)

Italy

+39 0522 731111

+39 0522 633198

<https://www.giuliano-automotive.com>



**Social Network**



Facebook



YouTube



Twitter



**Giuliano Industrial S.p.A.**

The information contained in this document is the sole property of Giuliano Automotive. The document is NOT authentic if it has been downloaded from a website different from [www.giuliano-automotive.com](http://www.giuliano-automotive.com).