

**Truck tyre changer 13" - 27" for truck and bus wheels.**

Truck tyre changer 13" - 27" suitable for truck and bus fleets. Compact tyre changer for intensive use. Suggested for professional truck tyre service and high volume shops. Suitable for both tube and tubeless tyres. Equipped with two-speed hydraulic clamping chuck and movable control unit, for safe and convenient operation.

Description

Tyre changer suitable for truck and bus fleets with 13"-27" rim (max. diameter 1600 mm./63", max. wheel width 780mm./30"). Equipped with **two-speed hydraulic clamping chuck** and movable control unit, for **safe and convenient** operation.

Suggested for professional truck tyre service and high volume shops. Compact tyre changer for intensive use.

Functions

- Hydraulic movement of clamping chuck holding arm (up-down);
- Hydraulic travel movement of operating arm carriage (left-right);
- Operating arm manual tilting and travelling on carriage;
- Double tool (disk + finger) manual rotation;
- Wheel clamping by fully hydraulic operated jaws;
- Operating arm and clamping chuck arm facing each other;
- All motions controlled by console and pedal box;
- Emergency safety button on control console, for stopping all functions;
- Suitable for control console installation on pivoting arm (optional);
- Rim center hole clamping range \varnothing 80 - 700 mm;
- Clamping chuck minimum height from ground 330 mm (center).

Giuliano Industrial S.p.A.

Standard Features

Rim clamping range	13" - 27"
Max. tyre diameter	1600 mm (63")
Max. tyre width	780 mm (30")
Bead breaker force	18300 N
Operating pressure	130 bar (1885 psi)
Power supply	400V - 3ph / 2 speed Other voltages and frequencies available upon request
Hydraulic pump motor power	1,1 kW
Clamping chuck motor power	1,3 / 1,8 kW
Net weight	560 kg
Max. tyre assembly weight	1500 kg
Max overall dimensions	1430÷1750x1550÷1740x1270 mm



Standard accessories





TBSR 2 (9218165)
Roller tool for mounting / demounting tubeless truck tyres



NJP (9234966)
Kit of spacers for the clamping jaws, for locking wheels with various thickness of flanging.



AJP (9234826)
Kit of clamp protections in aluminium for alloy rims.



AGC (9299271)
Clamp for alu-rims.



PJP (9245058)
Set of professional self-adapting clamps protections in aluminium for alloy rims. Variable radius protections. The special polymer spacers adapt to the bending radius of the rim to be clamped, ensuring the firmest and most protective grip possible.



WGC (9219656)
G-Clamp with wider bead-press angle, for agriculture tyres.



Scan QR code to go to product web page



Giuliano Industrial S.p.A.

via Guerrieri 6

Correggio (RE)

Italy

+39 0522 731111

+39 0522 633198

<https://www.giuliano-automotive.com>



Social Network



Facebook



YouTube



Twitter



Giuliano Industrial S.p.A.