



Automatic tilt back tyre fitting machine for car wheels 10" – 24"

Automatic tilt back tyre fitting machine for car wheels 10"-24", bead breaker double effect cylinder d.200 mm., made in aluminum, tabletop thickness 12 mm. Double nylon protected fitting head (to avoid contact with rim; provides great versatility and performance for even low profiled tyres).

Description

Traditional automatic "Budget line" tyre fitting machine, robust and convenient, equipped with air operated tilt-back tower, turntable clamping capacity 10"-24" and powerful bead breaker cylinder. Product designed for low-medium volume shops. Best choice for great quality at a budget price.

Functions

- Tilting tower, sliding horizontal arm with \varnothing 41 mm operating arm;
- Bead breaker double effect cylinder \varnothing 200 mm., made in aluminum;
- Reinforced chassy;
- Tabletop thickness 12 mm;
- Fitting head designed for both standard and low profiled tyre applications;
- CE inflating gauge (standard);
- Tyre inflation by pedal (optional);
- Suitable for HP4 dual assist arm (optional);
- Suitable for tubeless tyre bead seating system (optional).

SILVERLINE

The best choice for the average tyre shop with budget goal.

Standard Features

External clamping range	10" - 22" By adjustable jaws
Internal clamping range	12" - 24" By adjustable jaws
Max. tyre diameter	1010 mm (39")
Max. tyre width	390 mm (15")
Bead breaker force	30800 N
Operating pressure	10 bar (145 psi)
Balancing speed	7 rpm
Power supply	400V - 3ph / 220V - 1ph
Motor power	0,55 kW
Air Inflation Pressure	3,5 bar (50 Psi)
Net weight	220 Kg
Max overall dimensions	1240 x 1740 x 2010 mm



SL 22 SILVERLINE

Standard Accessories



Standard accessories

www.giuliano-automotive.com

The information contained in this document is the sole property of Giuliano Automotive. The document is NOT authentic if it has been downloaded from a website different from www.giuliano-automotive.com.

**G-CLAMP** (9217471)

G-CLAMP Set. Helps adding extra bead-pressure points on top bead while assembling it. Kit includes 2 regular and 2 extra-size G-clamps.

**RJP** (9236282)

Kit of rubber coated jaw protectors.

**T1** (9217472)

Kit of 4 rubber protections for steel rims.

**T2** (9217473)

Kit of 4 rubber protections for aluminium rims.

**T3** (9217474)

Kit of 4 rubber protectors for aluminium rims with arched spokes.

**LB** (9216805)

Lube paste bucket, 5 kg.

**PA ECO** (9236722)

PRESS ARM ECO additional arm to ease mounting operations of low profiled and UHP tyres.

**GUN 1** (9236658)

Tubeless inflation external kit.

**ORJP** (9216166)

Kit of rubber protections for clamping rims from inside using conventional jaws.

**MOTO-AD** (9235081)

Kit of 4 motorcycle wheels clamping adaptors, 6" - 24", with screw lock.

**ATV-AD** (9235082)

Kit of 4 clamping adaptors for HARLEY DAVIDSON wheels, oversize height, 6" - 24", with screw lock.

**QCK** (9208996)

Quick release kit for mounting tools (includes one plastic tool and one hub for connecting the tool delivered with the tyre-changer).

**SHS** (9209086)

Mounting/demounting tool for soft tyres on steel wheels, including hub for connection to quick release kit (**QCK**)

**AHS** (9213611)

Mounting/demounting tool for arched spokes rims, including hub for connection to quick release kit (**QCK**).

**EHS** (9235009)

Mounting/demounting tool for iron wheels with projecting central hub, including hub for connection to quick release kit (**QCK**)

**QX** (9243338)

QX is a leverless mount/demount device, suitable for conventional, UHP and Run Flat tyres. Exclusive GIULIANO **Patent**, it works in the same exact way of your traditional tyre bar, but **without operator's manual force....**

**QXHS** (9230814)

Kit of **QX** adaptors for connection to quick release kit (**QCK**).

**HD** (9208633)

Manual bead depressor.

**PAD** (9237711)

Manual bead depressor with extendable travelling pad.

**HP4** (9246608)

HP4 additional double arm to ease mounting operations of low profiled and UHP tyres.

Not available for:

**QCK** (9208996)

Quick release kit for mounting tools (includes one plastic tool and one hub for connecting the tool delivered with the tyre-changer).

**SHS** (9209086)

Mounting/demounting tool for soft tyres on steel wheels, including hub for connection to quick release kit (**QCK**)

**AHS** (9213611)

Mounting/demounting tool for arched spokes rims, including hub for connection to quick release kit (**QCK**).

**EHS** (9235009)

Mounting/demounting tool for iron wheels with projecting central hub, including hub for connection to quick release kit (**QCK**)

**QX** (9243338)

QX is a leverless mount/demount device, suitable for conventional, UHP and Run Flat tyres. Exclusive **GIULIANO Patent**, it works in the same exact way of your traditional tyre bar, but **without operator's manual force....**

**QXHS** (9230814)

Kit of **QX** adaptors for connection to quick release kit (**QCK**).

**HD** (9208633)

Manual bead depressor.

**PAD** (9237711)

Manual bead depressor with extendable travelling pad.

**WL 6** (9242824)

Pneumatic wheel lifter for passenger car type changers with foot control for the ascent and descent of the wheel. Pneumatic wheel lifter for car tyre changer: facilitates the positioning of the wheel on the tyre changer. Foot control for the ascent...

**QX-AD** (9232767)

QX, QX Plus adjusting tool and **LeverNoLever** System

**TPP 4** (9234452)

Kit of 10 rear plastic protections, for **QX, QX Plus** and **LeverNoLever** System

**TPP 5** (9234453)

Kit of 10 front plastic protections, for **QX, QX Plus** and **LeverNoLever** System

**CPC** (9214251)

Pressing cone for clamping RUN FLAT tires from outside.



Scan QR code to go to product web page



Giuliano Industrial S.p.A.

via Guerrieri 6

Correggio (RE)

Italy

+39 0522 731111

+39 0522 633198

<https://www.giuliano-automotive.com>



Social Network



Facebook



YouTube



Twitter



www.giuliano-automotive.com