



PAR-MOVE concept tyre machine with dual assist arm and PowerX

High performance super-automatic tyre changer PAR-MOVE concept with dual assist pneumatic helper arm and patented POWER X four cylinders clamping system. Robust fixed vertical tower with built-in air tank and PAR-MOVE parallelogram operating arm, Giuliano Patent. Space saving extremely robust tyre changer with reinforced chassis.

Description

PAR-MOVE concept high performance super-automatic tyre machine with dual assist arm and PowerX.

[Discover the advantages of PAR-MOVE system](#)

High-performance electro-pneumatic tyre machine designed for intensive use.

PAR-MOVE Series – STRONGER THAN EVER!

Functions

- Robust fixed vertical tower with innovative **PAR-MOVE** parallelogram operating arm [Giuliano Patent]. **5 YEAR WARRANTY ON PAR-MOVE**
- **SPACE SAVER:** PAR-MOVE design enables the tyre machine to be installed against the wall, requiring no additional rear space.
- **Reinforced Chassis.** Fixed vertical tower and parallelogram operating arm [Giuliano Patent] makes SX119 Pro extremely robust and stiff, granting increased rigidity and eliminating all flexes.
- Tabletop thickness 14 mm with **POWERX** four cylinders clamping system [Giuliano Patent]. **5 YEAR WARRANTY ON POWERX**
- **QX** Leverless tyre mounting/demounting device [Giuliano Patent] for conventional, low profiled, UHP and Run Flat tyres, optional.
- HP119 Additional auxiliary helper system (standard) provides a valuable support in mounting/ demounting Run Flat, UHP and low profiled tyres.
- Bead breaker double effect Cylinder ø 200 mm.
- **5 YEARS WARRANTY** on "Made in Giuliano" gearbox.
- **PO System** [Giuliano Patent] for granting no bead breaker shovel stuck into the rim during bead breaking operations.
- Adjustable bead breaker shovel stroke. Super-quick and Simple.
- Double rotation speed by pedal.
- Available in 3ph-2 speed, 1ph-2 speed (inverter) and 1ph - 1 speed version.
MOTOINVERTER for granting faster, more accurate and reliable drive for your tyre machine.
- Tyre inflation by pedal (standard).
- Vertical tower with built-in air tank, provides tubeless tyre inflation and bead seating (optional), eliminating the need for a separate air tank.
- Suitable for Tubeless tyre bead seating system (optional).
- "Easy Access" extractable pedal box for quick service.
- Extensive selection of standard accessories
- A very practical Wheel Lifter reduces effort and increases productivity (optional).
- Designed, built and engineered in Italy.
- "Right to repair" - all service parts available for at least 10 years since production, easy maintenance and reduced environmental impact.

Giuliano Industrial S.p.A.

Standard Features

External clamping range	10" - 27"
Internal clamping range	12" - 29"
Max. tyre diameter	1100 mm (43")
Max. tyre width	415 mm (16")
Bead breaker force	30800 N
Operating pressure	10 bar (145 psi)
Power supply	400V - 3ph - 2 speed 220V - 1ph 220V - 1ph - 2 speed
Motor power	0,8 / 1,1 kW (3ph)
Balancing speed	7-14 rpm
Air Inflation Pressure	3,5 bar (50 Psi)
Net weight	408 Kg
Dimensions (WxDxH)	1390 x 1350 x 2170 mm



Standard accessories





G-CLAMP (9217471)
G-CLAMP Set. Helps adding extra bead-pressure points on top bead while assembling it. Kit includes 2 regular and 2 extra-size G-clamps.



RJP (9236282)
Kit of rubber coated jaw protectors.



T1 (9217472)
Kit of 4 rubber protections for steel rims.



T2 (9217473)
Kit of 4 rubber protections for aluminium rims.



T3 (9217474)
Kit of 4 rubber protectors for aluminium rims with arched spokes.



LB (9216805)
Lube paste bucket, 5 kg.



AWF (9213425)
Air filter with pressure regulator and CE manometer.



GUN 1 (9236658)
Tubeless inflation external kit.



ORJP (9216166)
Kit of rubber protections for clamping rims from inside using conventional jaws.



MOTO-AD (9235081)
Kit of 4 motorcycle wheels clamping adaptors, 6" - 24", with screw lock.



ATV-AD (9235082)
Kit of 4 clamping adaptors for HARLEY DAVIDSON wheels, oversize height, 6" - 24", with screw lock.



QCK (9208996)
Quick release kit for mounting tools (includes one plastic tool and one hub for connecting the tool delivered with the tyre-changer).



SHS (9209086)
Mounting/demounting tool for soft tyres on steel wheels, including hub for connection to quick release kit (**QCK**).



AHS (9213611)
Mounting/demounting tool for arched spokes rims, including hub for connection to quick release kit (**QCK**).



EHS (9235009)
Mounting/demounting tool for iron wheels with projecting central hub, including hub for connection to quick release kit (**QCK**).



QX (9243338)
QX is a leverless mount/demount device, suitable for conventional, UHP and Run Flat tyres. Exclusive GIULIANO **Patent**, it works in the same exact way of your traditional tyre bar, but **without operator's manual force....**



GHS (9246170)
Mounting tool for 6"-12" wheels with operating arm extension.



QXHS (9230814)
Kit of **QX** adaptors for connection to quick release kit (**QCK**).



HD (9208633)
Manual bead depressor.



PAD (9237711)
Manual bead depressor with extendable travelling pad.



UHP6 (9245051)
Kit Run Flat UHP



WL 6 (9242824)
Pneumatic wheel lifter for passenger car type changers with foot control for the ascent and descent of the wheel. Pneumatic wheel lifter for car tyre changer: facilitates the positioning of the wheel on the tyre changer. Foot control for the ascent...



QX-AD (9232767)
QX, QX Plus adjusting tool and **LeverNoLever** System



TPP 4 (9234452)
Kit of 10 rear plastic protections, for **QX, QX Plus** and **LeverNoLever** System



TPP 5 (9234453)
Kit of 10 front plastic protections, for **QX, QX Plus** and **LeverNoLever** System



CPC (9214251)
Pressing cone for clamping RUN FLAT tires from outside.



Scan QR code to go to product web page

**Giuliano Industrial S.p.A.**

via Guerrieri 6

Correggio (RE)

Italy

+39 0522 731111

+39 0522 633198

<https://www.giuliano-automotive.com>

**Social Network**

Facebook



YouTube



Twitter



www.giuliano-automotive.com