



## High-performance automatic Lever - No Lever tilt back tyre changer with dual assist arm and Power X

High-performance leverless tilt-back tyre changer with patented Lever-No Lever technology, dual assist arm and PowerX four cylinders turntable (Giuliano Patent). Basically, you have two tyre changers in one: leverless and traditional!

### Description

High performance automatic Lever - No Lever tilt back tyre changer with dual assist arm and Power X.

High performance leverless tilt back tyre changer for tyres with rim from 10" to 29" (max. wheel diameter 1120 mm./44", max. wheel width 406mm./16"), equipped with Lever-No Lever technology, the only system that combines the advantages of "leverless" device to those of a standard mount/demount tool.

Basically, you have two tyre changers in one: leverless and traditional !

Our Lever - no Lever technology (LNL), covered by exclusive international patent, enables to quickly and easily turn SX234 Pro LNL leverless tyre changer into a conventional model, for example, when handling tyres which require a traditional bead lifting lever. LNL allows the operator to handle many different types of tyres in an extremely professional way, either with or without a bead lifting lever.

By operating an additional control handle on the front of the device, you can manually select to work either in leverless "No Lever" mode or in traditional mode, using the tyre lever (for example, when handling soft tyres which normally don't need leverless device).

It's the tyre specialist who decides which is the fastest, easiest, or most effortless way to operate on specific tyre applications, the tyre changer will adapt to your working needs! The result will always be the same: simple professional operation without any risk of damaging rim or tyre.

Equipped with HP4 powerful pneumatic helper system, to enhance tyre changer's performance and provide a valuable support in mounting/demounting most difficult tyre applications in the market, such as Run Flat, UHP and low profiled tyres.

Power X four cylinders turntable (Giuliano Patent) grants double, uniform clamping power on jaws, and an almost endless durability and reliability of your turntable!

The squared horizontal arm is equipped with Quadra Lock combined rear and front locking mechanism. This system removes every flexion or slack to the working arm during operations with UHP and Run Flat tyres, thus granting the same performance level over time, and making the tyre changer more reliable than ever before.

Reliable, robust and high-performance product with great capacity.

SX 234 Pro LNL is the state-of-the-art conventional tyre changer, developed by Giuliano for high volume tyre shops, and tyre specialists, servicing racing, run flat and UHP tyres, that is, for all tyre professionals, who have to deal with most diverse tyres every day, but want to work with simplicity and without efforts.

The real "work-horse" for your tyre shop!! New unstoppable, robust, tireless tyre changer to always support the wheel service specialist. Everything you need for a busy shop dealing with all kinds of CAR, LCV and LIGHT TRUCK tyres and wheels (motorcycle tyre fitting options available) !!

### Functions

- Tilt-back tower, sliding horizontal arm with  $\varnothing$  41 mm operating arm.
- Robust bead breaker arm, designed for tough jobs.
- Bead breaker double effect Cylinder  $\varnothing$  200 mm.
- Reinforced Chassy and tower.
- Equipped with **Lever - No Lever tyre mounting/demounting system** (Giuliano Patent). LNL tyre mounting/demounting system can work in an extremely professional way, either with or without a bead lifting lever (standard).
- Reliable and durable clamping system. Tabletop thickness 14 mm with **POWERX four cylinders clamping system** [Giuliano Patent]. **5 YEAR WARRANTY** on POWERX.
- **PO SYSTEM** (standard) automatically moves the bead breaker shovel back to the starting position, after its penetration [Giuliano Patent].
- Adjustable bead breaker shovel stroke.
- **QuadraLock system for total stiff locking** of horizontal and operating arm. QuadraLock system removes every possible flexion or slack during operations with UHP and Run Flat tyres, thus granting the same performance level over time.

- **5 YEARS WARRANTY** on "Made in Giuliano" gearbox.
- Double rotation speed by pedal.
- Tyre inflation by pedal (standard).
- HP4 Additional auxiliary helper system (standard) provides a valuable support in mounting / demounting Run Flat, UHP and low profiled tyres.
- "Easy Access" extractable pedal box for quick service.
- Robotic pipe for operating arm positioning/lock.
- Tools Storage Box (standard).
- MOTOINVERTER for granting faster, more accurate and reliable drive for your tyre changer machine.
- Suitable for Tubeless tyre bead seating system (optional).
- A very practical Wheel Lifter reduces effort and increases productivity (optional).
- Fixed roller plate, to ease bead breaking of heavy wheels (optional).
- Designed, built and engineered in Italy.
- 24 months STANDARD WARRANTY on all Giuliano Parts and **5 YEARS WARRANTY on our key and patented components.**
- "Right to repair" - all service parts available for at least 10 years since production, easy maintenance and reduced environmental impact.

Product designed for intensive use, for high volume professionals, who need reliable, robust and high-performance product with great capacity, even on toughest tyre applications.

WDK: Version available upon request

Extensive selection of standard accessories: bead lifting lever, lube paste bucket and brush, plastic protectors for mounting/demounting tool, 2 protectors for bead breaker shovel, jaw protectors for alloy rims, lubricator + pressure regulator, bucket support

**Giuliano Industrial S.p.A.**

The information contained in this document is the sole property of Giuliano Automotive. The document is NOT authentic if it has been downloaded from a website different from [www.giuliano-automotive.com](http://www.giuliano-automotive.com).

## Standard Features

---

External clamping range	10" - 27"
Internal clamping range	12" - 29"
Max. tyre diameter	1120 mm (44")
Max. tyre width	406 mm (16")
Bead breaker force	30800 N
Operating pressure	10 bar (145 psi)
Power supply	220V - 1ph - 2speed
Motor power	0,75 kW (1ph)
Balancing speed	7-16 rpm
Air Inflation Pressure	3,5 bar (50 Psi)
Net weight	405 Kg
Dimensions (WxDxH)	1610 x 1950 x 2190 mm



**SX 234 PRO LNL**

Standard Accessories



Standard accessories



**QX-AD** (9232767)

**QX, QX Plus** adjusting tool and  
**LeverNoLever** System

**[www.giuliano-automotive.com](http://www.giuliano-automotive.com)**

The information contained in this document is the sole property of Giuliano Automotive. The document is NOT authentic if it has been downloaded from a website different from [www.giuliano-automotive.com](http://www.giuliano-automotive.com).

**G-CLAMP** (9217471)

G-CLAMP Set. Helps adding extra bead-pressure points on top bead while assembling it. Kit includes 2 regular and 2 extra-size G-clamps.

**RJP** (9236282)

Kit of rubber coated jaw protectors.

**T1** (9217472)

Kit of 4 rubber protections for steel rims.

**T2** (9217473)

Kit of 4 rubber protections for aluminium rims.

**T3** (9217474)

Kit of 4 rubber protectors for aluminium rims with arched spokes.

**LB** (9216805)

Lube paste bucket, 5 kg.

**AWF** (9213425)

Air filter with pressure regulator and CE manometer.

**GUN 1** (9236658)

Tubeless inflation external kit.

**ORJP** (9216166)

Kit of rubber protections for clamping rims from inside using conventional jaws.

**MOTO-AD** (9235081)

Kit of 4 motorcycle wheels clamping adaptors, 6" - 24", with screw lock.

**ATV-AD** (9235082)

Kit of 4 clamping adaptors for HARLEY DAVIDSON wheels, oversize height, 6" - 24", with screw lock.

**GHS** (9212850)

Mounting tool for 6"-12" wheels with operating arm extension.

**UHP2** (9240575)

Kit Run Flat UHP

**WL 6** (9242824)

Pneumatic wheel lifter for passenger car type changers with foot control for the ascent and descent of the wheel. Pneumatic wheel lifter for car tyre changer: facilitates the positioning of the wheel on the tyre changer. Foot control for the ascent...

**TPP 4** (9234452)

Kit of 10 rear plastic protections, for **QX**, **QX Plus** and **LeverNoLever** System

**TPP 5** (9234453)

Kit of 10 front plastic protections, for **QX**, **QX Plus** and **LeverNoLever** System

**CPC** (9214251)

Pressing cone for clamping RUN FLAT tires from outside.



Scan QR code to go to product web page



**Giuliano Industrial S.p.A.**

via Guerrieri 6

Correggio (RE)

Italy

+39 0522 731111

+39 0522 633198

<https://www.giuliano-automotive.com>



**Social Network**



Facebook



YouTube



Twitter



**Giuliano Industrial S.p.A.**

The information contained in this document is the sole property of Giuliano Automotive. The document is NOT authentic if it has been downloaded from a website different from [www.giuliano-automotive.com](http://www.giuliano-automotive.com).