S 119 PRO DUO



PAR-MOVE Concept High Performance Super-automatic tire changer with combined two assist arms

PAR-MOVE concept high performance super-automatic tire changer with combined two assist arms. For high volume tire shops, servicing racing, run flat and UHP tires.

Description

PAR-MOVE concept high performance super-automatic tire changer with combined two assist arms. For high volume tire shops, servicing racing, run flat and UHP tires.

Functions

- Robust fixed vertical tower with innovative parallelogram operating arm (**PAR-MOVE Concept**).
- Bead loosener double effect Cylinder Ø 200 mm.
- Reinforced Chassis. Fixed vertical tower and parallelogram operating arm makes S119Pro Duo extremely robust and stiff, granting increased rigidity and eliminating all flexes.
- Tabletop thickness 14 mm.
- Fitting head designed for both standard and low profiled tire applications.
- Double rotation speed by pedal.
- Tire inflation by pedal (standard).
- Equipped with **BP1 Plus** bead pressing arm (standard), complete with self-storage function, GIULIANO patent.
- Equipped with **HP119** dual assist arm (standard) and storage box.
- Suitable for Tubeless tire bead seating system (optional).
- "Easy Access" extractable pedal box for quick service.
- **PO System**, Giuliano patent, for granting no bead loosener shovel stuck into the rim during bead loosening operations.
- Suitable for Wheel Lifter (optional).

The information contained in this document is the sole property of Giuliano Automotive. The document is NOT authentic if it has been downloaded from a website different from www.giuliano-automotive.com.

Standard Features

Rim clamping range from outside	10" - 24" By adjustable jaws
Rim clamping range from inside	12" - 26" By adjustable jaws
Max. tire diameter	1100 mm (43") By adjustable jaws
Max. tire width	415 mm (16") By adjustable jaws
Bead loosener force at 10 bar	30800 N By adjustable jaws
Operating pressure	10 bar (145 Psi) By adjustable jaws
Power supply	400V - 3Ph/2 speed 220V - 1Ph 220V - 1Ph/2 speed By adjustable jaws
Motor power	0,8 / 1,1 kW (3ph) By adjustable jaws
Balancing speed	7 - 14 rpm By adjustable jaws
Pre-set tire inflating pressure	3,5 bar (50 Psi) By adjustable jaws
Net weight	423 Kg By adjustable jaws
Max overall dimensions	1750 x 1310 x 2170 mm By adjustable jaws

www.giuliano-automotive.com

The information contained in this document is the sole property of Giuliano Automotive. The document is NOT authentic if it has been downloaded from a website different from www.giuliano-automotive.com.



Standard accessories



AWF (9213425)
Air filter with pressure regulator and CE manometer.





PED-G (9236373)
Pedal operated inflating device.



BP1 PLUS (9245184)
Bead pressing arm, complete with selfstorage function, **GIULIANO patent**.

The information contained in this document is the sole property of Giuliano Automotive. The document is NOT authentic if it has been downloaded from a website different from www.giuliano-automotive.com.



G-CLAMP (9217471)
G-CLAMP Set. Helps adding extra bead-pressure points on top bead while assembling it. Kit includes 2 regular and 2 extra-size G-clamps.



RJP (9236282)
Kit of rubber coated jaw protectors.



T2 (9217473)
Kit of 4 rubber protections for aluminium rims.



LB (9216805)
Lube paste bucket, 5 kg.



MOTO-AD (9235081)
Kit of 4 motorcycles adaptors with wider clamps, standard height. Suitable for any kind of car tyre changers turntable in GIULIANO range, allows easy clamping of motorcycle and scooter wheels from 6” to 23”, when mounted on standard jaws.



QCK (9208996)
Quick release kit for mounting tools (includes one plastic tool and one hub for connecting the tool delivered with the tire changer).



AHS (9213611)
Mounting/demounting tool for arched spokes rims, including hub for connection to quick release kit (**QCK**).



QX (9243338)
QX is a leverless mount/demount device, suitable for conventional, UHP and Run Flat tires. Exclusive GIULIANO **Patent**, it works in the same exact way of your traditional tire bar, but **without operator's manual force**....



PAD (9237711)
Manual bead depressor with extendable travelling pad.



UHP6 (9245051)
Kit Run Flat UHP



GUN 4 (9245186)
Tubeless inflation external kit



T1 (9217472)
Kit of 4 rubber protections for steel rims.



T3 (9217474)
Kit of 4 rubber protectors for aluminium rims with arched spokes.



ORJP (9216166)
Kit of rubber protections for clamping rims from inside using conventional jaws.



ATV-AD (9235082)
Kit of 4 adaptors for HARLEY DAVIDSON wheels, oversize height, 6" - 24", with screw lock.



SHS (9209086)
Mounting/demounting tool for soft tires on steel wheels, including hub for connection to quick release kit (**QCK**)



EHS (9235009)
Mounting/demounting tool for iron wheels with projecting central hub, including hub for connection to quick release kit (**QCK**)



QXHS (9230814)
Kit of **QX** adaptors for connection to quick release kit (**QCK**).



HD (9208633)
Manual bead depressor.



WL 6 (9242824)
Pneumatic wheel lifter for passenger car type changers with foot control for the ascent and descent of the wheel. Pneumatic wheel lifter for car tire changer: facilitates the positioning of the wheel on the tire changer. Foot control for the ascent...

www.giuliano-automotive.com
The information contained in this document is the sole property of Giuliano Automotive. The document is NOT authentic if it has been downloaded from a website different from www.giuliano-automotive.com.

Scan QR code to go to product web page

Giuliano Industrial S.p.A.
via Guerrieri 6
Correggio (RE)
Italy
+39 0522 731111
+39 0522 633198
https://www.giuliano-automotive.com

Social Network

Facebook

YouTube

Twitter

The information contained in this document is the sole property of Giuliano Automotive. The document is NOT authentic if it has been downloaded from a website different from www.giuliano-automotive.com.