



PAR-MOVE Concept High Performance Super-automatic tire changer with combined two assist arms

PAR-MOVE concept high performance super-automatic tire changer with combined two assist arms. For high volume tire shops, servicing racing, run flat and UHP tires.

Description

PAR-MOVE concept high performance super-automatic tire changer with combined two assist arms. For high volume tire shops, servicing racing, run flat and UHP tires.

Functions

- Robust fixed vertical tower with innovative parallelogram operating arm (**PAR-MOVE Concept**).
- Bead loosener double effect Cylinder Ø 200 mm.
- Reinforced Chassis. Fixed vertical tower and parallelogram operating arm makes S119Pro Duo extremely robust and stiff, granting increased rigidity and eliminating all flexes.
- Tabletop thickness 14 mm.
- Fitting head designed for both standard and low profiled tire applications.
- Double rotation speed by pedal.
- Tire inflation by pedal (standard).
- Equipped with **BP1 Plus** bead pressing arm (standard), complete with self-storage function, GIULIANO patent.
- Equipped with **HP119** dual assist arm (standard) and storage box.
- Suitable for Tubeless tire bead seating system (optional).
- "Easy Access" extractable pedal box for quick service.
- **PO System**, Giuliano patent, for granting no bead loosener shovel stuck into the rim during bead loosening operations.
- Suitable for Wheel Lifter (optional).

Giuliano Industrial S.p.A.

Standard Features

Rim clamping range from outside	10" - 24" By adjustable jaws
Rim clamping range from inside	12" - 26" By adjustable jaws
Max. tire diameter	1100 mm (43")
Max. tire width	415 mm (16")
Bead loosener force at 10 bar	30800 N
Operating pressure	10 bar (145 Psi)
Power supply	400V - 3Ph/2 speed 220V - 1Ph 220V - 1Ph/2 speed
Motor power	0,8 / 1,1 kW (3ph)
Balancing speed	7 - 14 rpm
Pre-set tire inflating pressure	3,5 bar (50 Psi)
Net weight	423 Kg
Max overall dimensions	1750 x 1310 x 2170 mm



Standard accessories



PED-G (9236373)
Pedal operated inflating device.



AWF (9213425)
Air filter with pressure regulator and CE manometer.



BP1 PLUS (9245184)
Bead pressing arm, complete with selfstorage function, **GIULIANO patent**.



**G-CLAMP** (9217471)

G-CLAMP Set. Helps adding extra bead-pressure points on top bead while assembling it. Kit includes 2 regular and 2 extra-size G-clamps.

**GUN 4** (9245186)

Tubeless inflation external kit

**RJP** (9236282)

Kit of rubber coated jaw protectors.

**T1** (9217472)

Kit of 4 rubber protections for steel rims.

**T2** (9217473)

Kit of 4 rubber protections for aluminium rims.

**T3** (9217474)

Kit of 4 rubber protections for aluminium rims with arched spokes.

**LB** (9216805)

Lube paste bucket, 5 kg.

**ORJP** (9216166)

Kit of rubber protections for clamping rims from inside using conventional jaws.

**MOTO-AD** (9235081)

Kit of 4 motorcycle wheels adaptors, 6" - 24", with screw lock.

**ATV-AD** (9235082)

Kit of 4 adaptors for HARLEY DAVIDSON wheels, oversize height, 6" - 24", with screw lock.

**QCK** (9208996)

Quick release kit for mounting tools (includes one plastic tool and one hub for connecting the tool delivered with the tire changer).

**SHS** (9209086)

Mounting/demounting tool for soft tires on steel wheels, including hub for connection to quick release kit (**QCK**)

**AHS** (9213611)

Mounting/demounting tool for arched spokes rims, including hub for connection to quick release kit (**QCK**).

**EHS** (9235009)

Mounting/demounting tool for iron wheels with projecting central hub, including hub for connection to quick release kit (**QCK**)

**QX** (9243338)

QX is a leverless mount/demount device, suitable for conventional, UHP and Run Flat tires. Exclusive GIULIANO **Patent**, it works in the same exact way of your traditional tire bar, but **without operator's manual force....**

**QXHS** (9230814)

Kit of **QX** adaptors for connection to quick release kit (**QCK**).

**PAD** (9237711)

Manual bead depressor with extendable travelling pad.

**HD** (9208633)

Manual bead depressor.

**UHP6** (9245051)

Kit Run Flat UHP

**WL 6** (9242824)

Pneumatic wheel lifter for passenger car type changers with foot control for the ascent and descent of the wheel. Pneumatic wheel lifter for car tire changer: facilitates the positioning of the wheel on the tire changer. Foot control for the ascent.



Scan QR code to go to product web page



Giuliano Industrial S.p.A.

via Guerrieri 6

Correggio (RE)

Italy

+39 0522 731111

+39 0522 633198

<https://www.giuliano-automotive.com>



Social Network



Facebook



YouTube



Twitter



Giuliano Industrial S.p.A.