



Racing Super-Automatic Lever - No Lever Tilt Back Tire Changer Machine with Dual Assist Arm

Racing super-automatic lever - no lever tilt back tire changer machine for tires with rim from 10" to 28". Equipped with dual assist arm for easy mounting/demounting of tire and PO System for granting no BB shovel stuck into the rim.

Description

Racing super-automatic lever - no lever tilt back tire changer machine for tires with rim from 10" to 28" (max. wheel diameter 1100 mm./43", max. wheel width 415mm./16"). In contrast to [S 228 PRO DUO L-N-L](#), this model is equipped with additional double arm (instead of two assist arms) for **easy** and **secure** mount/demount operation. PO system grants no bead loosener blade stuck into the rim during bead-loosening operations.

Suggested for high volume tire shops, servicing racing, run flat and UHP tires.

Functions

- Tilting tower, sliding horizontal arm with \varnothing 41 mm operating arm;
- Bead loosener double effect cylinder \varnothing 200 mm;
- Reinforced Chassy and tower;
- Equipped with **Lever - No Lever** tire mounting/demounting system (**Giuliano Patent**);
- Tabletop thickness 14 mm w/adjust. jaws (**Giuliano Patent**);
- Double rotation speed by pedal;
- **Tire inflation** by pedal (standard);
- Adjustable bead loosener shovel angle;
- Equipped with HP2 **dual assist arm** (standard) and storage box;
- Suitable for **Tubeless tire** bead seating system (optional);
- "Easy Access" extractable pedal box for quick service;
- PO System, **Giuliano patent**, for granting no BB shovel stuck into the rim;
- **Robotic pipe** for operating arm positioning/lock.

WDK: Version available upon request

Giuliano Industrial S.p.A.

Standard Features

Rim clamping range from outside	10" - 26" By adjustable jaws
Rim clamping range from inside	12" - 28" By adjustable jaws
Max. tire diameter	1100 mm (43")
Max. tire width	415 mm (16")
Bead loosener cylinder force at 10 Bar	30800 N
Operating pressure	10 bar (145 Psi)
Power supply	400V - 3ph / 2 speed 220V - 1ph 220V - 1ph / 2 speed
Motor power	0,8/1,1 kW (3ph)
Rotating speed	7-14 rpm
Pre-set tire inflating pressure	3,5 bar (50 Psi)
Net weight	379 Kg
Max overall dimensions	1590 x 1890 x 2160 mm



Standard accessories



HP2 (9219399)

HP2 additional double arm to ease mounting operations of low profiled and UHP tires.



PED-G (9236373)

Pedal operated inflating device.



Lever NoLever (STD_LNL)

LeverNoLever tire mounting/demounting device, GIULIANO patent, can work either with or without a bead lifting lever, so you can decide which is the most effortless way to operate on specific tire applications.

**G-CLAMP** (9217471)

G-CLAMP Set. Helps adding extra bead-pressure points on top bead while assembling it. Kit includes 2 regular and 2 extra-size G-clamps.

**RJP** (9236282)

Kit of rubber coated jaw protectors.

**T1** (9217472)

Kit of 4 rubber protections for steel rims.

**T2** (9217473)

Kit of 4 rubber protections for aluminium rims.

**T3** (9217474)

Kit of 4 rubber protectors for aluminium rims with arched spokes.

**LB** (9216805)

Lube paste bucket, 5 kg.

**WL 6** (9242824)

Pneumatic wheel lifter for passenger car type changers with foot control for the ascent and descent of the wheel. Pneumatic wheel lifter for car tire changer: facilitates the positioning of the wheel on the tire changer. Foot control for the ascent...

**GUN 1** (9236658)

Tubeless inflation external kit.

**ORJP** (9216166)

Kit of rubber protections for clamping rims from inside using conventional jaws.

**MOTO-AD** (9235081)

Kit of 4 motorcycles adaptors with wider clamps, standard height. Suitable for any kind of car tyre changers turntable in GIULIANO range, allows easy clamping of motorcycle and scooter wheels from 6" to 23", when mounted on standard jaws.

**ATV-AD** (9235082)

Kit of 4 adaptors for HARLEY DAVIDSON wheels, oversize height, 6" - 24", with screw lock.

**HD** (9208633)

Manual bead depressor.

**UHP2** (9240572)

Kit Run Flat UHP

**ROLL** (9241924)

Fixed roller plate, to ease bead loosening of heavy wheels.



Scan QR code to go to product web page



Giuliano Industrial S.p.A.

via Guerrieri 6

Correggio (RE)

Italy

+39 0522 731111

+39 0522 633198

<https://www.giuliano-automotive.com>



Social Network



Facebook



YouTube



Twitter



Giuliano Industrial S.p.A.