



High performance super-automatic tilt back tire changer with combined two assist arms

High performance super automatic tilt back tire changer with combined two assist arms, specially designed for low profiled and UHP tires, ideal for high volume tire shop, tire specialists; suitable for wheels with rim from 10" to 28" (max. wheel diameter 1120 mm./44", max. wheel width 406mm./16").

Description

High performance super-automatic tire changer, specially designed for low profiled and UHP tires, ideal for high volume tire shop, tire specialists; suitable for car wheels with rim from 10" to 28" (max. wheel diameter 1120 mm./44", max. wheel width 406mm./16"). Turntable with double-cylinder, adjustable clamps positioning and pedal operated two speed bidirectional rotation system.

Functions

- Tilting tower, sliding horizontal arm with \varnothing 41 mm operating arm;
- Bead loosener double effect Cylinder \varnothing 200 mm;
- Reinforced Chassy and tower;
- Tabletop thickness 14 mm w/adjust. jaws;
- Fitting head designed for both **standard and low profiled tire** applications;
- Double rotation speed by pedal;
- **Tire inflation** by pedal (standard);
- **Patented SBS System** for bead loosener shovel travel memory;
- Equipped with Help and Press Arm (standard)
- Suitable for **Tubeless tire** bead seating system (optional);
- "Easy Access" extractable pedal box for quick service;
- Adjustable bead loosener shovel angle;
- **QuadraLock** system for total stiff locking of horizontal and operating arm;
- PO System, **Giuliano patent**, for granting no BB shovel stuck into the rim;
- **Robotic pipe** for operating arm positioning/lock;
- Suitable for Tire Lift (optional).

WDK: Version available upon request

Giuliano Industrial S.p.A.

The information contained in this document is the sole property of Giuliano Automotive. The document is NOT authentic if it has been downloaded from a website different from www.giuliano-automotive.com.

Standard Features

Rim clamping range from outside	10" - 26" By adjustable jaws
Rim clamping range from inside	12" - 28" By adjustable jaws
Max. tire diameter	1120 mm (44")
Max. tire width	406 mm (16")
Bead loosener cylinder force at 10 Bar	30800 N
Operating pressure	10 bar (145 psi)
Power supply	400V - 3ph / 2 speed 220V - 1ph 220V - 1ph / 2 speed
Motor power	0,8 / 1,1 kW (3 ph)
Balancing speed	7-14 rpm
Pre-set tire inflating pressure	3,5 bar (50 psi)
Net weight	405 Kg
Max overall dimensions	2000x1940x2190 mm



Standard accessories



PED-G (9236373)
Pedal operated inflating device.



PA (9215940)
PRESS ARM3 additional arm to ease mounting operations of low profiled and UHP tires.



HELP (9236416)
HELP4 additional arm to ease mounting operations of low profiled and UHP tires.



AWF (9213425)
Air filter with pressure regulator and CE manometer.



ROLL (9241924)
Fixed roller plate, to ease bead loosening of heavy wheels.



G-CLAMP (9217471)
G-CLAMP Set. Helps adding extra bead-pressure points on top bead while assembling it. Kit includes 2 regular and 2 extra-size G-clamps.



RJP (9236282)
Kit of rubber coated jaw protectors.



T1 (9217472)
Kit of 4 rubber protections for steel rims.



T2 (9217473)
Kit of 4 rubber protections for aluminium rims.



T3 (9217474)
Kit of 4 rubber protectors for aluminium rims with arched spokes.



LB (9216805)
Lube paste bucket, 5 kg.



WL 2 (9241923)
Pneumatic wheel positioner.



GUN 1 (9236658)
Tubeless inflation external kit.



ORJP (9216166)
Kit of rubber protections for clamping rims from inside using conventional jaws.



MOTO-AD (9235081)
Kit of 4 motorcycle wheels adaptors, 6" - 24", with screw lock.



ATV-AD (9235082)
Kit of 4 adaptors for HARLEY DAVIDSON wheels, oversize height, 6" - 24", with screw lock.



QCK (9208996)
Quick release kit for mounting tools (includes one plastic tool and one hub for connecting the tool delivered with the tire changer).



SHS (9209086)
Mounting/demounting tool for soft tires on steel wheels, including hub for connection to quick release kit (**QCK**).



AHS (9213611)
Mounting/demounting tool for arched spokes rims, including hub for connection to quick release kit (**QCK**).



EHS (9235009)
Mounting/demounting tool for iron wheels with projecting central hub, including hub for connection to quick release kit (**QCK**).



GHS (9212850)
Mounting tool for 6"-12" wheels with operating arm extension.



QX (9243338)
QX is a leverless mount/demount device, suitable for conventional, UHP and Run Flat tires. Exclusive GIULIANO **Patent**, it works in the same exact way of your traditional tire bar, but **without operator's manual force....**



QXHS (9230814)
Kit of **QX** adaptors for connection to quick release kit (**QCK**).



HD (9208633)
Manual bead depressor.



PAD (9237711)
Manual bead depressor with extendable travelling pad.



UHP1 (9240576)
Kit Run Flat UHP



WL 6 (9242824)
Pneumatic wheel lifter for passenger car type changers with foot control for the ascent and descent of the wheel. Pneumatic wheel lifter for car tire changer: facilitates the positioning of the wheel on the tire changer. Foot control for the ascent...



Scan QR code to go to product web page



Giuliano Industrial S.p.A.

via Guerrieri 6

Correggio (RE)

Italy

+39 0522 731111

+39 0522 633198

<https://www.giuliano-automotive.com>



Social Network



Facebook



YouTube



Twitter



www.giuliano-automotive.com