



## Heavy duty tire changer machine suitable for truck, bus and agriculture tires, 14"-46"/58"<sup>(1)</sup>

Heavy duty tire changer for truck, bus and agriculture tyres 14"-46"/58". Essential for working with agricultural wheels. Robust and reliable. Suggested for professional truck tire service and high volume shops. Suitable for both tube and tubeless tires.

### Description

Heavy duty tire changer machine suitable for truck and heavy duty wheels with 14"-46"/58"<sup>(1)</sup> rim (max. wheel diameter 2300 mm./90,5", max. wheel width 1100 mm./43"). Equipped with **two-speed hydraulic clamping chuck** and movable control unit, for **safe and convenient** operation. Suitable for both tube and tubeless tires. Essential for working with Agricultural wheels. Robust and reliable.

### Functions

- Hydraulic movement of clamping chuck holding arm (up-down);
- Hydraulic travel movement of operating arm carriage (left-right);
- Operating arm manual tilting and travelling on carriage;
- Double tool (disk + finger) manual rotation;
- Wheel clamping by fully hydraulic operated jaws;
- Operating arm and clamping chuck arm facing each other;
- All motions controlled by console and pedal box;
- Emergency safety button on control console, for stopping all functions;
- Suitable for control console installation on pivoting arm (optional);
- Rim center hole clamping range  $\varnothing$  80 - 1200 mm;
- Clamping chuck minimum height from ground 315 mm (center);
- Suitable for remote control installation (optional).

<sup>(1)</sup> For the rims from 47" to 58" it is necessary to use the **optional** set of 4 jaw extensions for clamping wheels from 47" to 58".

## Standard Features

Rim clamping range without extensions	14" - 46"
Rim clamping range with extensions ( <b>optional</b> )	14" - 58"
Max. tire diameter	2300 mm (90,5")
Max. tire width	1100 mm (43")
Bead loosener force	26900 N
Operating pressure	130 bar (1885 psi)
Power supply	400V - 3ph / 2 speed <small>Other voltages and frequencies available upon request</small>
Hydraulic pump motor power	1,1 kW
Clamping chuck motor power	1,3 / 1,8 kW
Net weight	830 kg
Max. tire assembly weight	1500 kg
Max overall dimensions	2000÷2450x1640÷2390x880÷1840 mm



## Standard accessories





**TBSR 1** (9299274)  
Roller tool for mounting / demounting tubeless truck tires



**NJP** (9234966)  
Kit of spacers for the clamping jaws, for locking wheels with various thickness of flanging.



**DGC** (9299273)  
Set of 2 G-clamps for tires with retaining ring. To hold rim and bead retaining ring during bead loosening operation.



**AJP** (9234826)  
Kit of clamp protections in aluminium for alloy rims.



**AGC** (9299271)  
Clamp for alu-rims.



**CEX** (9235049)  
Kit of 4 clamp extensions for clamping range from 47" to 56".



**AD PLATE** (9234430)  
Additional platform for rim positioning on chuck, when tire is missing. h = 30 mm



**RCS 1** (9234777)  
Multichannel radio control 433 MHz.



**AD PLATE** (9244209)  
Additional platform for rim positioning on chuck, when tire is missing. h = 80 mm



**PJP** (9245058)  
Set of professional self-adapting clamps protections in aluminium for alloy rims. Variable radius protections. The special polymer spacers adapt to the bending radius of the rim to be clamped, ensuring the firmest and most protective grip possible.



**SGC** (9236972)  
Bead clamp with extra slide, for skidder tire applications.



**WGC** (9219656)  
G-Clamp with wider bead-press angle, for agriculture tires.



Scan QR code to go to product web page



**Giuliano Industrial S.p.A.**

via Guerrieri 6

Correggio (RE)

Italy

+39 0522 731111

+39 0522 633198

<https://www.giuliano-automotive.com>



**Social Network**



Facebook



YouTube



Twitter



**Giuliano Industrial S.p.A.**