

Truck tire changer 13"-27" for mobile tire service

Truck tire changer for mobile service of truck, bus and road transportation vehicle tires with 13"-27" rim (max. wheel diameter 1600 mm./63"; max. wheel width 870 mm./34"), fits in most popular commercial vans. Suitable for tubeless tires only.

Description

Truck tire changer for mobile-service of truck, bus and road transportation vehicle tires, fits in most popular commercial vans. Tire changer suitable for truck wheels with 13"-27" rim (max wheel diameter 1600 mm./63", max. wheel width 870 mm./34"), equipped with single speed hydraulic clamping chuck and movable control unit, for safe and convenient operation. Suitable for tubeless tires only.
Functions

- Hydraulic movement of clamping chuck holding arm (up-down);
- Hydraulic travel movement of operating arm carriage (left-right);
- Operating arm manual tilting and travelling on carriage;
- Wheel clamping by fully hydraulic operated jaws;
- Machine installation from the side or back door of the van;
- Clamping chuck holding arm tilts outside the van-door. Folds back inside the van after use;
- All motions controlled by joysticks and pedal box;
- Emergency safety button on control console and generator, for stopping all functions;
- Rim center hole clamping range ø 80 - 700 mm;
- Clamping chuck minimum height from ground 330 mm (according to van's floor height);
- Available in version **without generator and compressor** (optional).
  See generator and compressor specs here below
- Generator
  - Power - 10,6 kW;
  - Supply - Diesel;
  - Cooling - H_2O;
- Compressor
  - Capacity - 100 lt;
  - Air delivery - 650 lt/min;
  - Voltage - 230V 1ph/400V 3 ph;
- Also equipped with 2 air feeding plugs and hoses, complete with coilers mt. 10, plus one extra electric plug for connecting 220V-1ph outlet.

The information contained in this document is the sole property of Giuliano Automotive. The document is NOT authentic if it has been downloaded from a website different from www.giuliano-automotive.com.

Standard Features

Rim clamping range	13" - 27"
Max. tire diameter	1600 mm (63")
Max. tire width	870 mm (34")
Bead loosener force	16900 N
Operating pressure	120 bar (1740 psi)
Power supply	400V - 3ph Other voltages and frequencies available upon request
Hydraulic pump motor power	1,1 kW Other voltages and frequencies available upon request
Clamping chuck motor power	1,1 kW Other voltages and frequencies available upon request
Net weight	860 kg - 492 kg Net weight without compressor/generator
Max. tire assembly weight	1000 kg Net weight without compressor/generator
Max overall dimensions	1700x1070x1580 mm Net weight without compressor/generator

www.giuliano-automotive.com

The information contained in this document is the sole property of Giuliano Automotive. The document is NOT authentic if it has been downloaded from a website different from www.giuliano-automotive.com.



AGC (9299271)
Clamp for alu-rims.



AJP (9234826)
Kit of clamp protections in aluminium for alloy rims.

The information contained in this document is the sole property of Giuliano Automotive. The document is NOT authentic if it has been downloaded from a website different from www.giuliano-automotive.com.



DT 2 (9234434)
Double mounting tool with bead levers.



9230669
Tubeless mounting / demounting roller tool with hook for tube tires, including bead levers



NJP (9234966)
Kit of spacers for the clamping jaws, for locking wheels with various thickness of flanging.



AJP (9234826)
Kit of clamp protections in aluminium for alloy rims.



WGC (9219656)
G-Clamp with wider bead-press angle, for agriculture tires.

The information contained in this document is the sole property of Giuliano Automotive. The document is NOT authentic if it has been downloaded from a website different from www.giuliano-automotive.com.

Scan QR code to go to product web page

Giuliano Industrial S.p.A.
via Guerrieri 6
Correggio (RE)
Italy
+39 0522 731111
+39 0522 633198
https://www.giuliano-automotive.com

Social Network

Facebook

YouTube

Twitter

The information contained in this document is the sole property of Giuliano Automotive. The document is NOT authentic if it has been downloaded from a website different from www.giuliano-automotive.com.