SL 11 SILVERLINE

Semiautomatic swing arm tire machine

Semi-automatic swing arm tire machine, 10"-24", equipped with lubricator, tire bar and inflation pressure regulator 3,5 Bar (50 Psi), double effect BB cylinder d.200 mm., double nylon protected professional fitting head.

Description

Semi-automatic swing arm tire machine, 10"-24", equipped with lubricator, tire bar and inflation pressure regulator 3,5 Bar (50 Psi), double effect BB cylinder d.200 mm., double nylon protected professional fitting head. The special designed mounting/demounting head provides great versatility and performance for even low profiled tires.
Functions

- Robust vertical tower, swinging horizontal arm with □ 35 mm operating arm;
- Bead loosener double effect Cylinder ø 200 mm., made in aluminum;
- Reinforced Chassy;
- Tabletop thickness 12 mm;
- Fitting head designed for both standard and low profiled tire applications;
- Tire inflation by pedal (optional);
- Suitable for Tubeless tire bead seating system (optional);
- Suitable for Press Arm Eco (optional).

The information contained in this document is the sole property of Giuliano Automotive. The document is NOT authentic if it has been downloaded from a website different from www.giuliano-automotive.com.

Standard Features

External clamping range	10" - 22" By adjustable jaws
Internal clamping range	12" - 24" By adjustable jaws
Max. tire diameter	1010 mm (39")
Max. tire width	330 mm (13")
Bead loosener cylinder force at 10 Bar	30800 N
Operating pressure	10 bar (145 psi)
Balancing speed	7 rpm
Power supply	400V - 3ph / 220V - 1ph
Motor power	0,55 kW (3 ph)
Air Inflation Pressure	3,5 bar (50 Psi)
Net weight	185 Kg
Dimensions (WxDxH)	1240 x 1060 x 1760 mm

www.giuliano-automotive.com

The information contained in this document is the sole property of Giuliano Automotive. The document is NOT authentic if it has been downloaded from a website different from www.giuliano-automotive.com.

Standard accessories

The information contained in this document is the sole property of Giuliano Automotive. The document is NOT authentic if it has been downloaded from a website different from www.giuliano-automotive.com.

G-CLAMP (9217471)
G-CLAMP Set. Helps adding extra bead-pressure points on top bead while assembling it. Kit includes 2 regular and 2 extra-size G-clamps.

T1 (9217472)
Kit of 4 rubber protections for steel rims.

T3 (9217474)
Kit of 4 rubber protectors for aluminium rims with arched spokes.

PA ECO (9236722)
PRESS ARM ECO additional arm to ease mounting operations of low profiled and UHP tires.

GUN 1 (9236658)
Tubeless inflation external kit.

MOTO-AD (9235081)
Kit of 4 motorcycle wheels adaptors, 6" - 24", with screw lock.

QCK (9208996)
Quick release kit for mounting tools (includes one plastic tool and one hub for connecting the tool delivered with the tire changer).

AHS (9213611)
Mounting/demounting tool for arched spokes rims, including hub for connection to quick release kit (**QCK**).

QX (9243338)
QX is a leverless mount/demount device, suitable for conventional, UHP and Run Flat tires. Exclusive GIULIANO **Patent**, it works in the same exact way of your traditional tire bar, but **without operator's manual force**....

HD (9208633)
Manual bead depressor.

RJP (9236282)
Kit of rubber coated jaw protectors.

T2 (9217473)
Kit of 4 rubber protections for aluminium rims.

LB (9216805)
Lube paste bucket, 5 kg.

PSI-G (9299684)
Extra-CE inflating gauge.

ORJP (9216166)
Kit of rubber protections for clamping rims from inside using conventional jaws.

ATV-AD (9235082)
Kit of 4 adaptors for HARLEY DAVIDSON wheels, oversize height, 6" - 24", with screw lock.

SHS (9209086)
Mounting/demounting tool for soft tires on steel wheels, including hub for connection to quick release kit (**QCK**)

EHS (9235009)
Mounting/demounting tool for iron wheels with projecting central hub, including hub for connection to quick release kit (**QCK**)

QXHS (9230814)
Kit of **QX** adaptors for connection to quick release kit (**QCK**).

PAD (9237711)
Manual bead depressor with extendable travelling pad.

The information contained in this document is the sole property of Giuliano Automotive. The document is NOT authentic if it has been downloaded from a website different from www.giuliano-automotive.com.

BAR-G (9298185)
CE inflating gauge

The information contained in this document is the sole property of Giuliano Automotive. The document is NOT authentic if it has been downloaded from a website different from www.giuliano-automotive.com.

Scan QR code to go to product web page

Giuliano Industrial S.p.A.
via Guerrieri 6
Correggio (RE)
Italy
+39 0522 731111
+39 0522 633198
https://www.giuliano-automotive.com

Social Network

Facebook

YouTube

Twitter

The information contained in this document is the sole property of Giuliano Automotive. The document is NOT authentic if it has been downloaded from a website different from www.giuliano-automotive.com.