





PAR-MOVE concept tire machine with dual assist arm and PowerX

High performance super-automatic tire changer PAR-MOVE concept with dual assist pneumatic helper arm and patented POWER X four cylinders clamping system. Robust fixed vertical tower with built-in air tank and PAR-MOVE parallelogram operating arm, Giuliano Patent. Space saving extremely robust tire changer with reinforced chassis.

Description

PAR-MOVE concept high performance super-automatic tire machine with dual assist arm and PowerX.

Discover the advantages of PAR-MOVE system

High-performance electro-pneumatic tire machine designed for intensive use.

PAR-MOVE Series - STRONGER THAN EVER!

Functions

- Robust fixed vertical tower with innovative PAR-MOVE parallelogram operating arm [Giuliano Patent]. 5 YEAR WARRANTY ON PAR-MOVE
- SPACE SAVER: PAR-MOVE design enables the tire machine to be installed against the wall, requiring no additional rear space.
- Reinforced Chassis. Fixed vertical tower and parallelogram operating arm [Giuliano Patent] makes SX119 Pro extremely robust and stiff, granting increased rigidity and eliminating all flexes.
- Tabletop thickness 14 mm with POWERX four cylinders clamping system [Giuliano Patent]. 5 YEAR WARRANTY ON POWERX
- QX Leverless tire mounting/demounting device [Giuliano Patent] for conventional, low profiled, UHP and Run Flat tires, optional.
- HP119 Additional auxiliary helper system (standard) provides a valuable support in mounting/ demounting Run Flat, UHP and low profiled tires.
- Bead breaker double effect Cylinder ø 200 mm.
- 5 YEARS WARRANTY on "Made in Giuliano" gearbox.
- PO System [Giuliano Patent] for granting no bead breaker shovel stuck into the rim during bead breaking operations.
- Adjustable bead breaker shovel stroke. Super-quick and Simple.
- Double rotation speed by pedal.
- Available in 3ph-2 speed, 1ph-2 speed (inverter) and 1ph 1 speed version.
 - MOTOINVERTER for granting faster, more accurate and reliable drive for your tire machine.
- Tire inflation by pedal (standard).
- Vertical tower with built-in air tank, provides tubeless tire inflation and bead seating (optional), eliminating the need for a separate air
- Suitable for Tubeless tire bead seating system (optional).
- "Easy Access" extractable pedal box for quick service.
- Extensive selection of standard accessories
- A very practical Wheel Lifter reduces effort and increases productivity (optional).
- Designed, built and engineered in Italy.
- "Right to repair" all service parts available for at least 10 years since production, easy maintenance and reduced environmental impact.

External clamping range	10" - 27"
Internal clamping range	12" - 29"
Max. tire diameter	1100 mm (43")
Max. tire width	415 mm (16")
Bead loosener force	30800 N
Operating pressure	10 bar (145 psi)
Power supply	400V - 3ph - 2 speed
	220V - 1ph
	220V - 1ph - 2 speed
Motor power	0,8 / 1,1 kW (3ph)
Balancing speed	7-14 rpm
Air Inflation Pressure	3,5 bar (50 Psi)
Net weight	408 Kg
Dimensions (WxDxH)	1390 x 1350 x 2170 mm



5X 119 PRO

Standard Accessories



Standard accessories







5X 119 PROOptional Accessories





G-CLAMP (9217471)

G-CLAMP Set. Helps adding extra beadpressure points on top bead while assembling it. Kit includes 2 regular and 2 extra-size Gclamps.



RJP (9236282)

Kit of rubber coated jaw protectors.



T1 (9217472)

Kit of 4 rubber protections for steel rims.



T2 (9217473)

Kit of 4 rubber protections for aluminium rims.



T3 (9217474)

Kit of 4 rubber protectors for aluminium rims with arched spokes.



LB (9216805)

Lube paste bucket, 5 kg.



AWF (9213425)

Air filter with pressure regulator and CE manometer.



GUN 1 (9236658)

Tubeless inflation external kit.



ORJP (9216166)

Kit of rubber protections for clamping rims from inside using conventional jaws.



MOTO-AD (9235081)

Kit of 4 motorcycle wheels adaptors, 6" - 24", with screw lock.



ATV-AD (9235082)

Kit of 4 adaptors for HARLEY DAVIDSON wheels, oversize height, 6" - 24", with screw lock.



QCK (9208996)

Quick release kit for mounting tools (includes one plastic tool and one hub for connecting the tool delivered with the tire changer).



SHS (9209086)

Mounting/demounting tool for soft tires on steel wheels, including hub for connection to quick release kit (**QCK**)



AHS (9213611)

Mounting/demounting tool for arched spokes rims, including hub for connection to quick release kit (**QCK**).



EHS (9235009)

Mounting/demounting tool for iron wheels with projecting central hub, including hub for connection to quick release kit (**QCK**)



QX (9243338)

QX is a leverless mount/demount device, suitable for conventional, UHP and Run Flat tires. Exclusive GIULIANO **Patent**, it works in the same exact way of your traditional tire bar, but **without operator's manual force...**



GHS (9246170)

Mounting tool for 6"-12" wheels with operating arm extension.



QXHS (9230814)

Kit of **QX** adaptors for connection to quick release kit (**QCK**).



HD (9208633)

Manual bead depressor.




PAD (9237711)

Manual bead depressor with extendable travelling pad.



5X 119 PRO







UHP6 (9245051) Kit Run Flat UHP



WL 6 (9242824)

Pneumatic wheel lifter for passenger car type changers with foot control for the ascent and descent of the wheel. Pneumatic wheel lifter for car tire changer: facilitates the positioning of the wheel on the tire changer. Foot control for the ascent...



QX-AD (9232767) QX, QX Plus adjusting tool and LeverNoLever System



TPP 4 (9234452)

Kit of 10 rear plastic protections, for **QX**, **QX Plus** and **LeverNoLever** System



TPP 5 (9234453)
Kit of 10 front plastic protections, for **QX** and **QX Plus** and **LeverNoLever** System



CPC (9214251)

Pressing cone for clamping RUN FLAT tires from outside.





Scan QR code to go to product web page



References

Giuliano Industrial S.p.A.

via Guerrieri 6 Correggio (RE)

Italy

+39 0522 731111

+39 0522 633198

https://www.giuliano-automotive.com



Social Network













