

# **5X 119 PRO DUO**





# PAR-MOVE concept tire changer machine with combined two assist arms and Power X.

PAR-MOVE concept high performance super-automatic tire changer with combined two assist arms and Power X four cylinders clamping system, Giuliano Patent. Ergonomic and space saving design. Fixed vertical tower and parallelogram operating arm, Giuliano Patent, makes the tire changer extremely robust and stiff. BP1 PLUS pneumatic bead pressing arm, Giuliano Patent, lifts up automatically at the end of the mounting procedure.

#### Description

PAR-MOVE concept high-performance super-automatic tire changer machine with combined two assist arms and Power X.

#### Discover the advantages of PAR-MOVE system

Best tire changer machine for high-volume, high-performance tire shops, designed for intensive use.

PAR-MOVE Series - STRONGER THAN EVER!

#### Functions

- Robust fixed vertical tower with innovative PAR-MOVE parallelogram operating arm [Giuliano Patent]. 5 YEAR WARRANTY ON PAR-MOVE
- SPACE SAVER: PAR-MOVE design enables the tire changer machine to be installed against the wall, requiring no additional rear space.
- Reinforced Chassis. Fixed vertical tower and parallelogram operating arm [Giuliano Patent] makes this tire changer machine extremely robust and stiff, granting increased rigidity and eliminating all flexes.
- Tabletop thickness 14 mm with **POWERX**

| External clamping range | 10" - 27"             |
|-------------------------|-----------------------|
| Internal clamping range | 12" - 29"             |
| Max. tire diameter      | 1100 mm (43")         |
| Max. tire width         | 415 mm (16")          |
| Bead loosener force     | 30800 N               |
| Operating pressure      | 10 bar (145 psi)      |
| Power supply            | 400V - 3ph - 2 speed  |
|                         | 220V - 1ph            |
|                         | 220V - 1ph - 2 speed  |
| Motor power             | 0,8 / 1,1 kW (3ph)    |
| Balancing speed         | 7-14 rpm              |
| Air Inflation Pressure  | 3,5 bar (50 Psi)      |
| Net weight              | 432 Kg                |
| Dimensions (WxDxH)      | 1750 x 1350 x 2170 mm |



# **5X 119 PRO DUO**

# Standard Accessories



### Standard accessories







#### Optional Accessories





RJP (9236282)

Kit of rubber coated jaw protectors.



GUN 1 (9236658)

Tubeless inflation external kit.



#### **ORJP** (9216166)

Kit of rubber protections for clamping rims from inside using conventional jaws.



#### MOTO-AD (9235081)

Kit of 4 motorcycles adaptors with wider clamps, standard height. Suitable for any kind of car tyre changers turntable in GIULIANO range, allows easy clamping of motorcycle and scooter wheels from 6" to 23", when mounted on standard jaws.



## ATV-AD (9235082)

Kit of 4 adaptors for HARLEY DAVIDSON wheels, oversize height, 6" - 24", with screw lock



#### QCK (9208996)

Quick release kit for mounting tools (includes one plastic tool and one hub for connecting the tool delivered with the tire changer).



#### **SHS** (9209086)

Mounting/demounting tool for soft tires on steel wheels, including hub for connection to quick release kit (**QCK**)



#### AHS (9213611)

Mounting/demounting tool for arched spokes rims, including hub for connection to quick release kit (**QCK**).



#### EHS (9235009)

Mounting/demounting tool for iron wheels with projecting central hub, including hub for connection to quick release kit (**QCK**)



# OX (9243338)

QX is a leverless mount/demount device, suitable for conventional, UHP and Run Flat tires. Exclusive GIULIANO **Patent**, it works in the same exact way of your traditional tire bar, but **without operator's manual force...** 



# GHS (9246170)

Mounting tool for 6"-12" wheels with operating arm extension.



# **QXHS** (9230814)

Kit of **QX** adaptors for connection to quick release kit (**QCK**).



HD (9208633)

Manual bead depressor.



# PAD (9237711)

Manual bead depressor with extendable travelling pad.



# **UHP6** (9245051)

Kit Run Flat UHP



### WL 6 (9242824)

Pneumatic wheel lifter for passenger car type changers with foot control for the ascent and descent of the wheel. Pneumatic wheel lifter for car tire changer: facilitates the positioning of the wheel on the tire changer. Foot control for the ascent...



### **QX-AD** (9232767)

QX, QX Plus adjusting tool and LeverNoLever System



#### TPP 4 (9234452)

Kit of 10 rear plastic protections, for **QX**, **QX Plus** and **LeverNoLever** System



# **TPP 5** (9234453)

Kit of 10 front plastic protections, for **QX** and **QX Plus** and **LeverNoLever** System



# **CPC** (9214251)

Pressing cone for clamping RUN FLAT tires from outside.





# **5X 119 PRO DUO**

Optional Accessories





# **5X 119 PRO DUO**References



Scan QR code to go to product web page



# Giuliano Industrial S.p.A.

via Guerrieri 6 Correggio (RE)

Italy

+39 0522 731111

+39 0522 633198

https://www.giuliano-automotive.com



# **Social Network**















