



Racing super-automatic tilt-back tire change machine with dual assist arm and Power X.

Racing super automatic tilt back tire changer for intensive use. Additional auxiliary helper system for easy mounting/demounting Run Flat, UHP and low profiled tires. Patented PowerX four cylinders turntable. Reliable, robust and high-performance tire changer with great capacity.

Description

Racing super-automatic tilt back tire change machine with dual assist arm and Power X.

Super automatic tilt back tire change machine equipped with HP4 additional auxiliary helper system for easy mounting/demounting Run Flat, UHP and low profile tires and patented PowerX four cylinders turntable.

The real "work-horse" for your tire shop !! Developed by Giuliano for all tire professionals, who have to deal with most diverse tires every day but want to work with simplicity and without efforts.

New unstoppable, robust, tireless tire change machine to always support the wheel service specialist. Everything you need for a busy shop dealing with all kinds of CAR, LCV and LIGHT TRUCK tires and wheels (motorcycle tire fitting options available) !!

Functions

Solid tilt-back column, sliding horizontal arm with $\varnothing 41$ mm operating arm.

Robust bead breaker arm, **designed for tough jobs.**

Bead breaker double effect Cylinder $\varnothing 200$ mm.

Reinforced chassis and tower.

Reliable and durable clamping system. Tabletop thickness 14 mm with **POWERX four cylinders clamping system** [Giuliano Patent]. **5 YEAR WARRANTY** on POWERX.

POWER X grants double (uniform) clamping power on jaws, and an almost endless durability and reliability of your turntable!!!

PO SYSTEM (standard) automatically moves the bead breaker shovel back to the starting position, after its penetration [Giuliano Patent].

Adjustable bead breaker shovel stroke.

5 YEARS WARRANTY on "Made in Giuliano" gearbox.

Fitting head designed for both **standard and low profiled tire** applications.

Double rotation speed by pedal.

Tire inflation by pedal (standard).

HP4 Additional auxiliary helper system (standard) provides valuable support in mounting / demounting Run Flat, UHP and low-profiled tires.

Additional tilting roller tool for lower bead with an anti-collision joint.

"Easy Access" extractable pedal box for quick service.

Robotic pipe for operating arm positioning/lock.

Tools Storage Box (standard).

Available in 3ph-2 speed, 1ph-2 speed (inverter) and 1ph - 1 speed version.

MOTOINVERTER for granting faster, more accurate and reliable drive for your tire changer machine.

Suitable for **Patented QX** Leverless mounting device for low profiled and UHP tires (optional).

Suitable for Tubeless tire bead seating system (optional).

A very practical Wheel Lifter reduces effort and increases productivity (optional).

Designed, built and engineered in Italy.

"Right to repair" - all service parts available for at least 10 years since production, easy maintenance and reduced environmental impact.

Product designed for intensive use, for high volume professionals, who need reliable, robust and high-performance product with great capacity, even on toughest tire applications.

WDK: Version available upon request

Extensive selection of standard accessories: plastic protectors for mounting/demounting tool, 2 protectors for bead breaker shovel, jaw protectors for alloy rims, lubricator + pressure regulator, bead lifting lever, lube paste bucket and brush, bucket support

Giuliano Industrial S.p.A.

Standard Features

External clamping range	10" - 27"
Internal clamping range	12" - 29"
Max. tire diameter	1100 mm (43")
Max. tire width	415 mm (16")
Bead loosener force	30800 N
Operating pressure	10 bar (145 psi)
Power supply	400V - 3ph - 2 speed 220V - 1ph 220V - 1ph - 2 speed
Motor power	0,8 / 1,1 kW (3 ph)
Balancing speed	7-14 rpm
Air Inflation Pressure	3,5 bar (50 Psi)
Net weight	360 Kg
Dimensions (WxDxH)	1590 x 1930 x 2040 mm



Standard accessories





G-CLAMP (9217471)
G-CLAMP Set. Helps adding extra bead-pressure points on top bead while assembling it. Kit includes 2 regular and 2 extra-size G-clamps.



RJP (9236282)
Kit of rubber coated jaw protectors.



T1 (9217472)
Kit of 4 rubber protections for steel rims.



T2 (9217473)
Kit of 4 rubber protections for aluminium rims.



T3 (9217474)
Kit of 4 rubber protectors for aluminium rims with arched spokes.



LB (9216805)
Lube paste bucket, 5 kg.



AWF (9213425)
Air filter with pressure regulator and CE manometer.



UHP2 (9240572)
Kit Run Flat UHP



ORJP (9216166)
Kit of rubber protections for clamping rims from inside using conventional jaws.



MOTO-AD (9235081)
Kit of 4 motorcycle wheels adaptors, 6" - 24", with screw lock.



ATV-AD (9235082)
Kit of 4 adaptors for HARLEY DAVIDSON wheels, oversize height, 6" - 24", with screw lock.



QCK (9208996)
Quick release kit for mounting tools (includes one plastic tool and one hub for connecting the tool delivered with the tire changer).



SHS (9209086)
Mounting/demounting tool for soft tires on steel wheels, including hub for connection to quick release kit (**QCK**)



AHS (9213611)
Mounting/demounting tool for arched spokes rims, including hub for connection to quick release kit (**QCK**).



EHS (9235009)
Mounting/demounting tool for iron wheels with projecting central hub, including hub for connection to quick release kit (**QCK**)



QX (9243338)
QX is a leverless mount/demount device, suitable for conventional, UHP and Run Flat tires. Exclusive GIULIANO **Patent**, it works in the same exact way of your traditional tire bar, but **without operator's manual force....**



GHS (9212850)
Mounting tool for 6"-12" wheels with operating arm extension.



QXHS (9230814)
Kit of **QX** adaptors for connection to quick release kit (**QCK**).



HD (9208633)
Manual bead depressor.



PAD (9237711)
Manual bead depressor with extendable travelling pad.



WL 6 (9242824)

Pneumatic wheel lifter for passenger car type changers with foot control for the ascent and descent of the wheel. Pneumatic wheel lifter for car tire changer: facilitates the positioning of the wheel on the tire changer. Foot control for the ascent...



QX-AD (9232767)

QX, QX Plus adjusting tool and **LeverNoLever** System



x 10

TPP 4 (9234452)

Kit of 10 rear plastic protections, for **QX, QX Plus** and **LeverNoLever** System



x 10

TPP 5 (9234453)

Kit of 10 front plastic protections, for **QX** and **QX Plus** and **LeverNoLever** System



CPC (9214251)

Pressing cone for clamping RUN FLAT tires from outside.



Scan QR code to go to product web page



Giuliano Industrial S.p.A.

via Guerrieri 6

Correggio (RE)

Italy

+39 0522 731111

+39 0522 633198

<https://www.giuliano-automotive.com>



Social Network



Facebook



YouTube



Twitter



www.giuliano-automotive.com