

**Digital electronic wheel-balancer with microprocessor and LED display**

Digital electronic wheel-balancer with microprocessor, LED display, wheel guard and pedal brake. Equipped with 4 balancing programs for wheels with aluminium rims; static and dynamic balancing, balance optimization.

Description

Digital electronic wheel-balancer with microprocessor, LED display, wheel guard and pedal brake. Equipped with 4 balancing programs for wheels with aluminium rims; static and dynamic balancing, optimization of balancing. It is standard delivered with quick locking universal flange and cones.

Features

- Pedal brake;
- Automatic measuring of wheel diameter and distance;
- Automatic wheel positioning;
- Automatic START and STOP;
- Static and dynamic balancing, 4 ALU programs;
- ALU-S special program;
- FES function (Fast & Easy Split for hidden weight positioning);
- Multi-user function (for simultaneous use of the machine by 2 operators);
- OPTIMATCH function (optimization of the unbalance between rim and tire);
- Self-calibration;
- Max. wheel weight: 65 kg.;
- Cycle time: 6 sec.;
- Balancing speed:

Giuliano Industrial S.p.A.

Standard Features

Max. wheel weight	75 Kg
Max. power absorption	0,8 kW
Power supply	230 V 1ph
Balancing speed	< 100 rpm
Balancing precision	± 1g
Rim diameter	10"-30" / 255±765 mm
Rim width	1,5"-20" / 40-510 mm
Net weight	105 Kg







Scan QR code to go to product web page



Giuliano Industrial S.p.A.

via Guerrieri 6

Correggio (RE)

Italy

+39 0522 731111

+39 0522 633198

<https://www.giuliano-automotive.com>



Social Network



Facebook



YouTube



Twitter



Giuliano Industrial S.p.A.

The information contained in this document is the sole property of Giuliano Automotive. The document is NOT authentic if it has been downloaded from a website different from www.giuliano-automotive.com.