

**PAR-MOVE Concept High Performance Super-Automatic Tyre Changer**

PAR-MOVE concept high performance super-automatic tyre changer. For high volume tyre shops.

**Description**

PAR-MOVE concept high performance super-automatic tyre changer. For high volume tyre shops.

**Functions**

- Robust fixed vertical tower with innovative parallelogram operating arm (**PAR-MOVE Concept**).
- Bead breaker double effect Cylinder Ø 200 mm.
- Reinforced Chassis. Fixed vertical tower and parallelogram operating arm makes S119 extremely robust and stiff, granting increased rigidity and eliminating all flexes.
- Tabletop thickness 14 mm.
- Fitting head designed for both standard and low profiled tyre applications.
- Double rotation speed by pedal.
- Tyre inflation by pedal (standard).
- Suitable for Tubeless tyre bead seating system (optional).
- "Easy Access" extractable pedal box for quick service.
- **PO System**, Giuliano patent, for granting no bead breaker shovel stuck into the rim during bead breaking operations.
- Suitable for Wheel Lifter (optional).

**Giuliano Industrial S.p.A.**

## Standard Features

Rim clamping range from outside	10" - 24" By adjustable jaws
Rim clamping range from inside	12" - 26" By adjustable jaws
Max. tyre diameter	1100 mm (43")
Max. tyre width	415 mm (16")
Bead breaker cylinder force at 10 Bar	30800 N
Operating pressure	10 bar (145 Psi)
Power supply	400V - 3Ph/2 speed 220V - 1Ph 220V - 1Ph/2 speed
Motor power	0,8 / 1,1 kW (3ph)
Balancing speed	7 - 14 rpm
Pre-set tyre inflating pressure	3,5 bar (50 Psi)
Net weight	316 Kg
Max overall dimensions	1390 x 1310 x 2170 mm



Standard accessories



**PED-G** (9236373)  
Pedal operated inflating device.



**AWF** (9213425)  
Air filter with pressure regulator and CE  
manometer.



**G-CLAMP** (9217471)  
G-CLAMP Set. Helps adding extra bead-pressure points on top bead while assembling it. Kit includes 2 regular and 2 extra-size G-clamps.



**GUN 4** (9245186)  
Tubeless inflation external kit



**RJP** (9236282)  
Kit of rubber coated jaw protectors.



**T1** (9217472)  
Kit of 4 rubber protections for steel rims.



**T2** (9217473)  
Kit of 4 rubber protections for aluminium rims.



**T3** (9217474)  
Kit of 4 rubber protectors for aluminium rims with arched spokes.



**LB** (9216805)  
Lube paste bucket, 5 kg.



**BP1 PLUS** (9245184)  
Bead pressing arm, complete with selfstorage function, **GIULIANO patent**.



**ORJP** (9216166)  
Kit of rubber protections for clamping rims from inside using conventional jaws.



**MOTO-AD** (9235081)  
Kit of 4 motorcycle wheels clamping adaptors, 6" - 24", with screw lock.



**ATV-AD** (9235082)  
Kit of 4 clamping adaptors for HARLEY DAVIDSON wheels, oversize height, 6" - 24", with screw lock.



**QCK** (9208996)  
Quick release kit for mounting tools (includes one plastic tool and one hub for connecting the tool delivered with the tyre-changer).



**SHS** (9209086)  
Mounting/demounting tool for soft tyres on steel wheels, including hub for connection to quick release kit (**QCK**)



**AHS** (9213611)  
Mounting/demounting tool for arched spokes rims, including hub for connection to quick release kit (**QCK**).



**EHS** (9235009)  
Mounting/demounting tool for iron wheels with projecting central hub, including hub for connection to quick release kit (**QCK**)



**QX** (9243338)  
QX is a leverless mount/demount device, suitable for conventional, UHP and Run Flat tyres. Exclusive **GIULIANO Patent**, it works in the same exact way of your traditional tyre bar, but **without operator's manual force....**




**QXHS** (9230814)  
Kit of **QX** adaptors for connection to quick release kit (**QCK**).



**PAD** (9237711)  
Manual bead depressor with extendable travelling pad.



**HD** (9208633)  
Manual bead depressor.



**ROLL** (9241924)  
Fixed roller plate, to ease bead breaking of heavy wheels.



**WL 6** (9242824)

Pneumatic wheel lifter for passenger car type changers with foot control for the ascent and descent of the wheel. Pneumatic wheel lifter for car tyre changer: facilitates the positioning of the wheel on the tyre changer. Foot control for the ascent...



**HP2** (9219399)

HP2 additional double arm to ease mounting operations of low profiled and UHP tyres.



Scan QR code to go to product web page



**Giuliano Industrial S.p.A.**

via Guerrieri 6

Correggio (RE)

Italy

+39 0522 731111

+39 0522 633198

<https://www.giuliano-automotive.com>



**Social Network**



Facebook



YouTube



Twitter



**[www.giuliano-automotive.com](https://www.giuliano-automotive.com)**