



High-performance leverless center post tyre machine with combined two assist arms and patented PAR-MOVE system

High-performance leverless center post tyre changer with two combined auxiliary arms. Patented PAR-MOVE parallelogram type operating arm assembly enables the tyre changer to be installed against the wall, requiring no additional rear space in the workshop, and ensures extremely high rigidity of the operating parts, helping handle different types of tyres in the easiest and most effortless way.

Description

High-performance leverless center post tyre machine with combined two assist arms. Equipped with patented space-saving Par-Move tower.

[Discover the advantages of PAR-MOVE system](#)

Our new range of high-performance super-automatic tyre machines with fixed vertical tower and parallelogram operating arm (S119 Series - S121 - S122 - T-REC - S118), developed by our R&D department are the only machines available on the market, which can be installed in a working space perfectly fitting their actual overall dimensions. Thanks to Par-Move, a new working concept based on **articulated parallelogram movement**, these machines do not require any additional rear space, unlike conventional tilt-back models. Par-Move includes the only **patented pneumatic system** in the world that **keeps the correct position of the mounting head** on the rim edge, saving time and effort on sets of tires of the same size.

S119 PRO DUO CP LNL tyre machine is the more complete version of S119 Series, equipped with patented Leverless system (Lever-No Lever technology) to enhance its performance. The system can work either with or without a bead lifting lever, so you can decide which is the most effortless way to operate on specific tyre applications. Lever-No Lever (LNL) technology enables to turn S119 PRO DUO CP LNL quickly and easily into a conventional tyre machine, for example, when handling tyres which require a traditional bead lifting lever.

S119 PRO DUO CP LNL tyre machine, dedicated to top professionals, is supplied with HP119 additional pneumatic helper tower and **patented BP1 Plus bead pressing arm**, complete with self-storage function (standard).

PAR-MOVE Series – STRONGER THAN EVER!

Functions

- Robust fixed vertical tower with innovative **PAR-MOVE** parallelogram operating arm [Giuliano Patent]. **5 YEAR WARRANTY** on PAR-MOVE.
- **SPACE SAVER:** PAR-MOVE design enables the tyre machine to be installed against the wall, requiring no additional rear space.
- **Reinforced Chassis.** Fixed vertical tower and parallelogram operating arm [Giuliano Patent] make S119 Pro DUO CP LNL extremely robust and stiff, granting increased rigidity and eliminating all flexes.
- Manual Press/Twist **ultra-quick wheel-clamping device**.
- **Lever-No-Lever** tyre mounting/demounting system [Giuliano Patent], standard.
- HP119 Additional pneumatic helper tower with 3 functions (standard) provides a valuable support in mounting/ demounting Run Flat, UHP and low profiled tyres. Additional tilting roller tool for lower bead with an anti-collision joint.
- Equipped with **BP1 Plus**, extremely innovative high-performance pneumatic bead pressing arm [Giuliano Patent] complete with self-storage function. BP1 Plus lifts up automatically at the end of the mounting procedure, and moves back in rest position, with no need for the operator to change his working position. The position of BP1 Plus can be adjusted in height by acting on its hand knob.
- Bead breaker double effect Cylinder ø 200 mm.
- **5 YEARS WARRANTY** on "Made in Giuliano" gearbox.
- **PO System** [Giuliano Patent] for granting no bead breaker shovel stuck into the rim during bead breaking operations.
- Adjustable bead breaker shovel stroke. Super-quick and Simple.
- Double rotation speed by pedal.
- Available in 3ph-2 speed, 1ph-2 speed (inverter) and 1ph - 1 speed version.
MOTOINVERTER for granting faster, more accurate and reliable drive for your tyre machine.
- Tyre inflation by pedal (standard).
- Vertical tower with **built-in air tank**, provides tubeless tyre inflation and bead seating (optional), eliminating the need for a separate air tank.
- Suitable for Tubeless tyre bead seating system (optional).
- "Easy Access" extractable pedal box for quick service.
- Extensive selection of standard accessories.
- A very practical Wheel Lifter reduces effort and increases productivity (optional).
- Designed, built and engineered in Italy.
- "Right to repair" - all service parts available for at least 10 years since production, easy maintenance and reduced environmental impact.

Giuliano Industrial S.p.A.

The information contained in this document is the sole property of Giuliano Automotive. The document is NOT authentic if it has been downloaded from a website different from www.giuliano-automotive.com.

Standard Features

Rim clamping range	12" - 30"
Max. tyre diameter	1100 mm (43")
Max. tyre width	390 mm (15") <small>For reverse mounted wheels, variable according to rim features</small>
Bead breaker force	30800 N
Operating pressure	10 bar (145 psi)
Power supply	220V - 1ph - Inverter (STND) 400V - 3ph - 2 speed, 110V - 1ph (OPT)
Motor power	0,75 kW (2 speed)
Balancing speed	7-16 rpm
Air Inflation Pressure	3,5 bar (50 Psi)
Net weight	440 Kg
Dimensions (WxDxH)	1750 x 1310 x 2170 mm



Standard accessories



QX-AD (9232767)

QX, QX Plus adjusting tool and
LeverNoLever System



**G-CLAMP** (9217471)

G-CLAMP Set. Helps adding extra bead-pressure points on top bead while assembling it. Kit includes 2 regular and 2 extra-size G-clamps.

**GUN 4** (9245186)

Tubeless inflation external kit

**T1** (9217472)

Kit of 4 rubber protections for steel rims.

**T2** (9217473)

Kit of 4 rubber protections for aluminium rims.

**T3** (9217474)

Kit of 4 rubber protectors for aluminium rims with arched spokes.

**LB** (9216805)


Lube paste bucket, 5 kg.

**AWF** (9213425)

Air filter with pressure regulator and CE manometer.

**BP1 PLUS** (9245184)

Bead pressing arm, complete with selfstorage function, **GIULIANO patent**.

**ROLL** (9241924)

Fixed roller plate, to ease bead breaking of heavy wheels.

**SPK 1 (Lamborghini)** (9241383)

NYLON CONE FOR SPECIAL LAMBORGHINI WHEELS, allows clamping wheels with center hole diameter from 55 to 85 mm.

**SPK 2 (Porsche)** (9239459)

NYLON CONE FOR SPECIAL PORSCHE WHEELS, allows clamping wheels with center hole diameter from 60 to 85 mm.

**SPK 3 (BMW)** (9241717)

NYLON CONE FOR SPECIAL BMW WHEELS, allows clamping wheels with center hole diameter from 55 to 70 mm.

**WL 6** (9242824)

Pneumatic wheel lifter for passenger car type changers with foot control for the ascent and descent of the wheel. Pneumatic wheel lifter for car tyre changer: facilitates the positioning of the wheel on the tyre changer. Foot control for the ascent...

**TPP 4** (9234452)

Kit of 10 rear plastic protections, for **QX, QX Plus** and **LeverNoLever** System

**TPP 5** (9234453)

Kit of 10 front plastic protections, for **QX, QX Plus** and **LeverNoLever** System

**CPC** (9214251)

Pressing cone for clamping RUN FLAT tires from outside.

**LTK2** (9247902)

Truck cone kit, allows clamping VANs and LCVs wheels with center hole diameter from 190 to 220 mm.

**LTK3** (9247900)

Truck cone kit, allows clamping VANs and LCVs wheels with center hole diameter from 120 to 190 mm.

**FRB** (9224675)

FRB is a special wheel centering kit, developed to easily and quickly clamp BMW wheels on Giuliano center post tyre changer, as required by BMW. BMW, particularly attentive to the stability of the clamping and the protection of rims and tyres, requires...



Scan QR code to go to product web page



Giuliano Industrial S.p.A.

via Guerrieri 6

Correggio (RE)

Italy

+39 0522 731111

+39 0522 633198

<https://www.giuliano-automotive.com>



Social Network



Facebook



YouTube



Twitter



Giuliano Industrial S.p.A.