

**Superautomatic tyre changer suitable for car and motorcycle wheels**

Superautomatic tyre changer suitable for car and motorcycle wheels having rim size from 10" to 24" rim (max. diameter 1000 mm./39", max. wheel width 380 mm./15").

Description

Superautomatic tyre changer suitable for car and motorcycle wheels having rim size from 10" to 24" rim (max. diameter 1000 mm./39", max. wheel width 380 mm./15"). Equipped with turntable double speed bidirectional rotation system with hand switch control.

Features

- Tilting vertical arm with pedal control;
- Pneumatic system for lifting/lowering and locking the operating arm;
- 10-22" turntable, outside clamping;
- Bead-breaker with double effect pneumatic cylinder;
- Oversize body;
- Extractable pedal unit;
- 2 speed motor 230/400V-3ph-50Hz.

WDK: Version available upon request

Giuliano Industrial S.p.A.

The information contained in this document is the sole property of Giuliano Automotive. The document is NOT authentic if it has been downloaded from a website different from www.giuliano-automotive.com.

Standard Features

Rim clamping range	10" - 24"
Max. tyre diameter	1000 mm (39")
Max. tyre width	385 mm (15")
Max. bead-breaker cylinder force	30800 N
Operating pressure	10 bar (145 psi)
Balancing speed	7-14 rpm
Power supply	400 V 3ph
Motor power	0,8 - 1,1 kW
Max. spindle torque	1200 Nm
Inflating pressure limiting device max.	3,5 bar (50 psi)
Net weight	224 Kg STD 264 Kg GT





QX (9243338)

QX is a leverless mount/demount device, suitable for conventional, UHP and Run Flat tyres. Exclusive GIULIANO **Patent**, it works in the same exact way of your traditional tyre bar, but **without operator's manual force....**



Scan QR code to go to product web page



Giuliano Industrial S.p.A.

via Guerrieri 6

Correggio (RE)

Italy

+39 0522 731111

+39 0522 633198

<https://www.giuliano-automotive.com>



Social Network



Facebook



YouTube



Twitter



Giuliano Industrial S.p.A.