S 228 Combi



Automatic tilt-back professional tyre changer with helper arm

Automatic tilt-back professional tyre changer with helper arm. For high volume tyre shops, servicing racing, run flat and UHP tyres.

Description

Automatic tilt-back professional tyre changer with helper arm. For high volume tyre shops, servicing racing, run flat and UHP tyres.

Functions

- Tilting tower, sliding horizontal arm with Ø 41 mm operating arm;
- Bead breaker double effect Cylinder Ø 200 mm;
- Reinforced Chassis and Tower;
- Tabletop thickness 14 mm;
- Fitting head designed for both standard and low profiled tyre applications;
- Double rotation speed by pedal;
- Tyre inflation by pedal (standard);
- Equipped with HP Light dual assist arm (standard);
- Suitable for Tubeless tyre bead seating system (optional);
- "Easy Access" extractable pedal box for quick service.

The information contained in this document is the sole property of Giuliano Automotive. The document is NOT authentic if it has been downloaded from a website different from www.giuliano-automotive.com.

Standard Features

Rim clamping range from outside	10" - 24" By adjustable jaws
Rim clamping range from inside	12" - 26" By adjustable jaws
Max. tyre diameter	1100 mm (43") By adjustable jaws
Max. tyre width	415 mm (16") By adjustable jaws
Bead breaker cylinder force at 10 Bar	30800 N By adjustable jaws
Operating pressure	10 bar (145 Psi) By adjustable jaws
Power supply	400V - 3ph / 2 speed 220V - 1ph By adjustable jaws
Motor power	0,8/1,1 kW (3ph) By adjustable jaws
Rotating speed	7-14 rpm By adjustable jaws
Pre-set tyre inflating pressure	3,5 bar (50 Psi) By adjustable jaws
Net weight	350 Kg By adjustable jaws
Max overall dimensions	1590 x 1890 x 2040 mm By adjustable jaws

www.giuliano-automotive.com

The information contained in this document is the sole property of Giuliano Automotive. The document is NOT authentic if it has been downloaded from a website different from www.giuliano-automotive.com.



Standard accessories



AWF (9213425)
Air filter with pressure regulator and CE manometer.



PED-G (9236373)
Pedal operated inflating device.

The information contained in this document is the sole property of Giuliano Automotive. The document is NOT authentic if it has been downloaded from a website different from www.giuliano-automotive.com.



G-CLAMP (9217471)
G-CLAMP Set. Helps adding extra bead-pressure points on top bead while assembling it. Kit includes 2 regular and 2 extra-size G-clamps.



9242351
Additional roller tool arm for lower bead



9242740
Additional bead lifting disk arm for lower bead



RJP (9236282)
Kit of rubber coated jaw protectors.



T1 (9217472)
Kit of 4 rubber protections for steel rims.



T2 (9217473)
Kit of 4 rubber protections for aluminium rims.



T3 (9217474)
Kit of 4 rubber protectors for aluminium rims with arched spokes.



LB (9216805)
Lube paste bucket, 5 kg.



GUN 1 (9236658)
Tubeless inflation external kit.



ORJP (9216166)
Kit of rubber protections for clamping rims from inside using conventional jaws.



MOTO-AD (9235081)
Kit of 4 motorcycles adaptors with wider clamps, standard height. Suitable for any kind of car tyre changers turntable in GIULIANO range, allows easy clamping of motorcycle and scooter wheels from 6” to 23”, when mounted on standard jaws.



ATV-AD (9235082)
Kit of 4 clamping adaptors for HARLEY DAVIDSON wheels, oversize height, 6" - 24", with screw lock.



QCK (9208996)
Quick release kit for mounting tools (includes one plastic tool and one hub for connecting the tool delivered with the tyre-changer).



SHS (9209086)
Mounting/demounting tool for soft tyres on steel wheels, including hub for connection to quick release kit (**QCK**)



AHS (9213611)
Mounting/demounting tool for arched spokes rims, including hub for connection to quick release kit (**QCK**).



EHS (9235009)
Mounting/demounting tool for iron wheels with projecting central hub, including hub for connection to quick release kit (**QCK**)



QXHS (9230814)
Kit of **QX** adaptors for connection to quick release kit (**QCK**).



QX (9243338)
QX is a leverless mount/demount device, suitable for conventional, UHP and Run Flat tyres. Exclusive GIULIANO **Patent**, it works in the same exact way of your traditional tyre bar, but **without operator's manual force**....



GHS (9212850)
Mounting tool for 6"-12" wheels with operating arm extension.



WL 6 (9242824)
Pneumatic wheel lifter for passenger car type changers with foot control for the ascent and descent of the wheel. Pneumatic wheel lifter for car tyre changer: facilitates the positioning of the wheel on the tyre changer. Foot control for the ascent...

www.giuliano-automotive.com
The information contained in this document is the sole property of Giuliano Automotive. The document is NOT authentic if it has been downloaded from a website different from www.giuliano-automotive.com.

Scan QR code to go to product web page

Giuliano Industrial S.p.A.
via Guerrieri 6
Correggio (RE)
Italy
+39 0522 731111
+39 0522 633198
https://www.giuliano-automotive.com

Social Network

Facebook

YouTube

Twitter

The information contained in this document is the sole property of Giuliano Automotive. The document is NOT authentic if it has been downloaded from a website different from www.giuliano-automotive.com.