

Truck tyre changer 14"-26"

Tyre changer suitable for truck and bus fleets (for both tube and tubeless tyres) with 14" - 26" rim (max. wheel diameter 1200 mm./47"; max. wheel width 780 mm./30").

Description

Tyre changer suitable for truck and bus fleets with 14" - 26" rim (max. wheel diameter 1200 mm./47"; max. wheel width 780 mm./30"). Equipped with manual wheel clamping system by faceplate, cones and ring nut; also equipped with traditional double tool for mounting/removing tubeless and/or tube tyres.

Functions

- Hydraulic movement of clamping chuck holding arm (up-down);
- Hydraulic travel movement of operating arm carriage (left-right);
- Operating arm manual tilting;
- Double tool (disk + finger) manual rotation;
- Wheel clamping by face plate, cones and ring nut;
- Operating arm and clamping chuck arm facing each other;
- All motions controlled by joysticks;
- Safety switches and electric circuit breakers for both pump motor and chuck motor.

The information contained in this document is the sole property of Giuliano Automotive. The document is NOT authentic if it has been downloaded from a website different from www.giuliano-automotive.com.

Standard Features

Rim clamping range	14" - 26"
Max. tyre diameter	1200 mm (47")
Max. tyre width	780 mm (30")
Bead breaker force	18300 N
Operating pressure	130 bar (1885 psi)
Power supply	400V / 230V - 3ph Other voltages and frequencies available upon request
Hydraulic pump motor power	1,1 kW (3 ph) Other voltages and frequencies available upon request
Clamping chuck motor power	1,1 kW (3 ph) Other voltages and frequencies available upon request
Net weight	400 kg Other voltages and frequencies available upon request
Max. tyre assembly weight	1500 kg Other voltages and frequencies available upon request
Max overall dimensions	1330÷1570x1500x1160 mm Other voltages and frequencies available upon request

www.giuliano-automotive.com

The information contained in this document is the sole property of Giuliano Automotive. The document is NOT authentic if it has been downloaded from a website different from www.giuliano-automotive.com.

Standard accessories



www.giuliano-automotive.com
The information contained in this document is the sole property of Giuliano Automotive. The document is NOT authentic if it has been downloaded from a website different from www.giuliano-automotive.com.



TBSR 2 (9218165)
Roller tool for mounting / demounting tubeless truck tyres



AGC (9299271)
Clamp for alu-rims.



WGC (9219656)
G-Clamp with wider bead-press angle, for agriculture tyres.

The information contained in this document is the sole property of Giuliano Automotive. The document is NOT authentic if it has been downloaded from a website different from www.giuliano-automotive.com.

Scan QR code to go to product web page

Giuliano Industrial S.p.A.
via Guerrieri 6
Correggio (RE)
Italy
+39 0522 731111
+39 0522 633198
https://www.giuliano-automotive.com

Social Network

Facebook

YouTube

Twitter

The information contained in this document is the sole property of Giuliano Automotive. The document is NOT authentic if it has been downloaded from a website different from www.giuliano-automotive.com.