SX 119 PRO DUO



PAR-MOVE concept tyre changing machine with combined two assist arms and Power X.

PAR-MOVE concept high performance super-automatic tyre changer with combined two assist arms and Power X four cylinders clamping system, Giuliano Patent. Ergonomic and space saving design. Fixed vertical tower and parallelogram operating arm, Giuliano Patent, makes the tyre changer extremely robust and stiff. BP1 PLUS pneumatic bead pressing arm, Giuliano Patent, lifts up automatically at the end of the mounting procedure.

Description

PAR-MOVE concept high performance super-automatic tyre changing machine with combined two assist arms and Power X.

Discover the advantages of PAR-MOVE system

Best tyre changing machine for high-volume, high-performance tyre shops, designed for intensive use.

PAR-MOVE Series – STRONGER THAN EVER!

Functions

- Robust fixed vertical tower with innovative **PAR-MOVE** parallelogram operating arm [Giuliano Patent]. **5 YEAR WARRANTY ON PAR-MOVE**
- **SPACE SAVER**: PAR-MOVE design enables the tyre changing machine to be installed against the wall, requiring no additional rear space.
- **Reinforced Chassis**. Fixed vertical tower and parallelogram operating arm [Giuliano Patent] makes this tyre changing machine extremely robust and stiff, granting increased rigidity and eliminating all flexes.
- Tabletop thickness 14 mm with **POWERX**

The information contained in this document is the sole property of Giuliano Automotive. The document is NOT authentic if it has been downloaded from a website different from www.giuliano-automotive.com.

Standard Features

External clamping range	10" - 27"
Internal clamping range	12" - 29"
Max. tyre diameter	1100 mm (43")
Max. tyre width	415 mm (16")
Bead breaker force	30800 N
Operating pressure	10 bar (145 psi)
Power supply	400V - 3ph - 2 speed 220V - 1ph 220V - 1ph - 2 speed
Motor power	0,8 / 1,1 kW (3ph)
Balancing speed	7-14 rpm
Air Inflation Pressure	3,5 bar (50 Psi)
Net weight	432 Kg
Dimensions (WxDxH)	1750 x 1350 x 2170 mm

www.giuliano-automotive.com

The information contained in this document is the sole property of Giuliano Automotive. The document is NOT authentic if it has been downloaded from a website different from www.giuliano-automotive.com.



Standard accessories



The information contained in this document is the sole property of Giuliano Automotive. The document is NOT authentic if it has been downloaded from a website different from www.giuliano-automotive.com.



RJP (9236282)
Kit of rubber coated jaw protectors.



ORJP (9216166)
Kit of rubber protections for clamping rims from inside using conventional jaws.



ATV-AD (9235082)
Kit of 4 clamping adaptors for HARLEY DAVIDSON wheels, oversize height, 6" - 24", with screw lock.



SHS (9209086)
Mounting/demounting tool for soft tyres on steel wheels, including hub for connection to quick release kit (**QCK**)



EHS (9235009)
Mounting/demounting tool for iron wheels with projecting central hub, including hub for connection to quick release kit (**QCK**)



GHS (9246170)
Mounting tool for 6"-12" wheels with operating arm extension.



HD (9208633)
Manual bead depressor.



UHP6 (9245051)
Kit Run Flat UHP



QX-AD (9232767)
QX, **QX Plus** adjusting tool and **LeverNoLever** System



TPP 5 (9234453)
Kit of 10 front plastic protections, for **QX**, **QX Plus** and **LeverNoLever** System



GUN 1 (9236658)
Tubeless inflation external kit.



MOTO-AD (9235081)
Kit of 4 motorcycles adaptors with wider clamps, standard height. Suitable for any kind of car tyre changers turntable in GIULIANO range, allows easy clamping of motorcycle and scooter wheels from 6” to 23”, when mounted on standard jaws.



QCK (9208996)
Quick release kit for mounting tools (includes one plastic tool and one hub for connecting the tool delivered with the tyre-changer).



AHS (9213611)
Mounting/demounting tool for arched spokes rims, including hub for connection to quick release kit (**QCK**).



QX (9243338)
QX is a leverless mount/demount device, suitable for conventional, UHP and Run Flat tyres. Exclusive GIULIANO **Patent**, it works in the same exact way of your traditional tyre bar, but **without operator's manual force**....



QXHS (9230814)
Kit of **QX** adaptors for connection to quick release kit (**QCK**).



PAD (9237711)
Manual bead depressor with extendable travelling pad.



WL 6 (9242824)
Pneumatic wheel lifter for passenger car type changers with foot control for the ascent and descent of the wheel. Pneumatic wheel lifter for car tyre changer: facilitates the positioning of the wheel on the tyre changer. Foot control for the ascent...



TPP 4 (9234452)
Kit of 10 rear plastic protections, for **QX**, **QX Plus** and **LeverNoLever** System



CPC (9214251)
Pressing cone for clamping RUN FLAT tires from outside.

The information contained in this document is the sole property of Giuliano Automotive. The document is NOT authentic if it has been downloaded from a website different from www.giuliano-automotive.com.

Pressing cone for clamping RUN FLAT tires from outside.

The information contained in this document is the sole property of Giuliano Automotive. The document is NOT authentic if it has been downloaded from a website different from www.giuliano-automotive.com.

Scan QR code to go to product web page

Giuliano Industrial S.p.A.
via Guerrieri 6
Correggio (RE)
Italy
+39 0522 731111
+39 0522 633198
https://www.giuliano-automotive.com

Social Network

Facebook

YouTube

Twitter

The information contained in this document is the sole property of Giuliano Automotive. The document is NOT authentic if it has been downloaded from a website different from www.giuliano-automotive.com.