SX 234 PRO DUO



High performance super automatic tilt back tyre changer machine with combined two assist arms and Power X

High performance super automatic tilt back tyre changer for tyres with rim from 10" to 29" (max. wheel diameter 1120 mm./44", max. wheel width 406mm./16"). Equipped with two assist arms, to provide a valuable support in mounting/demounting Run Flat, UHP and low profiled tyres. Power X four cylinders turntable, Giuliano Patent.

Description

High performance super automatic tilt back tyre changer machine with combined two assist arms and Power X.

High performance tilt back tyre changer machine for tyres with rim from 10" to 29" (max. wheel diameter 1120 mm./44", max. wheel width 406mm./16"). Equipped with Help and Press Arm powerful pneumatic helper systems, to enhance tyre changer machine's performance and provide a valuable support in mounting/demounting most difficult tyre applications in the market, such as Run Flat, UHP and low profiled tyres.
Power X four cylinders turntable (Giuliano Patent) grants double, uniform clamping power on jaws, and an almost endless durability and reliability of your turntable!

The squared horizontal arm is equipped with Quadra Lock combined rear and front locking mechanism. This system removes every flexion or slack to the working arm during operations with UHP and Run Flat tyres, thus granting the same performance level over time, and making the tyre changer machine more reliable than ever before.

Reliable, robust and high-performance product with great capacity.
SX 234 Pro Duo is the state-of-the-art conventional tyre changer machine, developed by Giuliano for high volume tyre shops, and tyre specialists, servicing racing, run flat and UHP tyres, that is, for all tyre professionals, who have to deal with most diverse tyres every day, but want to work with simplicity and without efforts.

The real "work-horse" for your tyre shop!! New unstoppable, robust, tireless tyre changer machine to always support the wheel service specialist. Everything you need for a busy shop dealing with all kinds of CAR, LCV and LIGHT TRUCK tyres and wheels (motorcycle tyre fitting options available) !!

Functions

- Tilt-back tower, sliding horizontal arm with ø 41 mm operating arm.
- Robust bead breaker arm, designed for tough jobs.
- Bead breaker double effect Cylinder ø 200 mm.
- Reinforced Chassy and tower.
- Reliable and durable clamping system. Tabletop thickness 14 mm with **POWERX four cylinders clamping system** [Giuliano Patent]. **5 YEAR WARRANTY** on POWERX.
- **Patented PO SYSTEM** (standard) automatically moves the bead breaker shovel back to the starting position, after its penetration.
- Adjustable bead breaker shovel stroke.
- **QuadraLock system** for total stiff locking of horizontal and operating arm. QuadraLock system removes every possible flexion or slack during operations with UHP and Run Flat tyres, thus granting the same performance level over time.
- **5 YEARS WARRANTY** on "Made in Giuliano" gearbox.
- Fitting head designed for both standard and low profiled tyre applications.
- Double rotation speed by pedal.
- Tyre inflation by pedal (standard).
- Equipped with Help and Press Arm additional auxiliary helper systems (standard) to ease mounting operations of low profiled, Run Flat and UHP tyres.
- "Easy Access" extractable pedal box for quick service.
- Robotic pipe for operating arm positioning/lock.
- Tools Storage Box (standard).
- MOTOINVERTER for granting faster, more accurate and reliable drive for your tyre changer machine.
- Suitable for **Patented QX Leverless mounting device** for low profiled and UHP tyres (optional).
- Suitable for Tubeless tyre bead seating system (optional).
- A very practical Wheel Lifter reduces effort and increases productivity (optional).
- Fixed roller plate, to ease bead breaking of heavy wheels (optional).
- Designed, built and engineered in Italy.
- 24 months STANDARD WARRANTY on all Giuliano Parts and **5 YEARS WARRANTY on our key and patented components**.
- "Right to repair" - all service parts available for at least 10 years since production, easy maintenance and reduced environmental impact.

Product designed for intensive use, for high volume professionals, who need reliable, robust and high-performance product with great capacity, even on toughest tyre applications.
WDK: Version available upon request

Extensive selection of standard accessories: bead lifting lever, lube paste bucket and brush, plastic protectors for mounting/demounting tool, 2 protectors for bead breaker shovel, jaw protectors for alloy rims, lubricator + pressure regulator, bucket support

The information contained in this document is the sole property of Giuliano Automotive. The document is NOT authentic if it has been downloaded from a website different from www.giuliano-automotive.com.

Standard Features

External clamping range	10" - 27"
Internal clamping range	12" - 29"
Max. tyre diameter	1120 mm (44")
Max. tyre width	406 mm (16")
Bead breaker force	30800 N
Operating pressure	10 bar (145 psi)
Power supply	220V - 1ph - 2speed
Motor power	0,75 kW (1ph)
Balancing speed	7-16 rpm
Air Inflation Pressure	3,5 bar (50 Psi)
Net weight	400 Kg
Dimensions (WxDxH)	1900 x 1950 x 2190 mm

www.giuliano-automotive.com

The information contained in this document is the sole property of Giuliano Automotive. The document is NOT authentic if it has been downloaded from a website different from www.giuliano-automotive.com.

Standard accessories



The information contained in this document is the sole property of Giuliano Automotive. The document is NOT authentic if it has been downloaded from a website different from www.giuliano-automotive.com.



G-CLAMP (9217471)
G-CLAMP Set. Helps adding extra bead-pressure points on top bead while assembling it. Kit includes 2 regular and 2 extra-size G-clamps.



T1 (9217472)
Kit of 4 rubber protections for steel rims.



T3 (9217474)
Kit of 4 rubber protectors for aluminium rims with arched spokes.



AWF (9213425)
Air filter with pressure regulator and CE manometer.



GUN 1 (9236658)
Tubeless inflation external kit.



MOTO-AD (9235081)
Kit of 4 motorcycles adaptors with wider clamps, standard height. Suitable for any kind of car tyre changers turntable in GIULIANO range, allows easy clamping of motorcycle and scooter wheels from 6” to 23”, when mounted on standard jaws.



QCK (9208996)
Quick release kit for mounting tools (includes one plastic tool and one hub for connecting the tool delivered with the tyre-changer).



AHS (9213611)
Mounting/demounting tool for arched spokes rims, including hub for connection to quick release kit (**QCK**).



QX (9243338)
QX is a leverless mount/demount device, suitable for conventional, UHP and Run Flat tyres. Exclusive GIULIANO **Patent**, it works in the same exact way of your traditional tyre bar, but **without operator's manual force**....



QXHS (9230814)
Kit of **QX** adaptors for connection to quick release kit (**QCK**).



RJP (9236282)
Kit of rubber coated jaw protectors.



T2 (9217473)
Kit of 4 rubber protections for aluminium rims.



LB (9216805)
Lube paste bucket, 5 kg.



UHP1 (9240576)
Kit Run Flat UHP



ORJP (9216166)
Kit of rubber protections for clamping rims from inside using conventional jaws.



ATV-AD (9235082)
Kit of 4 clamping adaptors for HARLEY DAVIDSON wheels, oversize height, 6" - 24", with screw lock.



SHS (9209086)
Mounting/demounting tool for soft tyres on steel wheels, including hub for connection to quick release kit (**QCK**)



EHS (9235009)
Mounting/demounting tool for iron wheels with projecting central hub, including hub for connection to quick release kit (**QCK**)



GHS (9212850)
Mounting tool for 6"-12" wheels with operating arm extension.



HD (9208633)
Manual bead depressor.

The information contained in this document is the sole property of Giuliano Automotive. The document is NOT authentic if it has been downloaded from a website different from www.giuliano-automotive.com.



PAD (9237711)
Manual bead depressor with extendable travelling pad.



QX-AD (9232767)
QX, **QX Plus** adjusting tool and **LeverNoLever** System



TPP 5 (9234453)
Kit of 10 front plastic protections, for **QX**, **QX Plus** and **LeverNoLever** System

Pressing cone for clamping RUN FLAT tires from outside.



WL 6 (9242824)
Pneumatic wheel lifter for passenger car type changers with foot control for the ascent and descent of the wheel. Pneumatic wheel lifter for car tyre changer: facilitates the positioning of the wheel on the tyre changer. Foot control for the ascent...



TPP 4 (9234452)
Kit of 10 rear plastic protections, for **QX**, **QX Plus** and **LeverNoLever** System



CPC (9214251)
Pressing cone for clamping RUN FLAT tires from outside.

The information contained in this document is the sole property of Giuliano Automotive. The document is NOT authentic if it has been downloaded from a website different from www.giuliano-automotive.com.

Scan QR code to go to product web page

Giuliano Industrial S.p.A.
via Guerrieri 6
Correggio (RE)
Italy
+39 0522 731111
+39 0522 633198
https://www.giuliano-automotive.com

Social Network

Facebook

YouTube

Twitter

The information contained in this document is the sole property of Giuliano Automotive. The document is NOT authentic if it has been downloaded from a website different from www.giuliano-automotive.com.