

SILVERLINE

The best choice for the average tyre shop with budget goal.

By



SILVERLINE



by

www.giuliano-automotive.com

The best choice for the average tyre shop with budget goal.

SL22



You Tube

Watch the video



Discover on our website!

AUTOMATIC TILT BACK TYRE CHANGER FOR CAR WHEELS 10" – 24"



Suitable for Tubeless tyre bead seating system (optional)

✓ **Tilting tower**, sliding horizontal arm with $\varnothing$ 41 mm operating arm

NEW



Suitable for **HP4 Dual Assist Arm** with 3 tools (optional):

✓ **Spring supported operating arm**

✓ **CE inflating gauge** (standard)

✓ **Fitting head** designed for both standard and **low profiled** tyre applications

✓ **Tabletop thickness 12 mm**

✓ **Reinforced Chassis**

Bead Pressing Roller

Bead Lifting Roller

Bead Pressing Pad



HP4 Video




Additional tilting roller tool for lower bead with an anti-collision joint.

✓ **Bead breaker double effect**
Cylinder $\varnothing$ 200 mm., made in aluminum



Suitable for Tyre inflation by pedal (optional)




STANDARD FEATURES

Rim clamping from outside	10" - 22" *
Rim clamping from inside	12" - 24" *
Max. tyre diameter	1010 mm (39")
Max. tyre width	390 mm (15")
Bead breaker cylinder force at 10 Bar	30800 N
Operating pressure	10 bar (145 Psi)
Power supply	400V-3ph / 220V-1ph
Motor power	0,55 kW (3 ph)
Rotation speed	7 rpm
Pre-set tyre inflating pressure	3,5 bar (50 Psi)
Net weight	220 kg
Max. overall dimensions	1240x1740x2010 mm

* By adjustable jaws

STANDARD ACCESSORIES



• Bead lifting lever • Plastic protectors for mounting/demounting tool • Lubricator + Pressure regulator • CE inflating gauge



Giuliano Industrial S.p.A: Via Guerrieri, 6 - 42015 CORREGGIO (RE) ITALY
Tel. +39 0522 731111 - Telefax +39 0522 633109 - E-mail: info@giuliano-automotive.com - Internet: www.giuliano-automotive.com



SILVERLINE



The best choice for the average tyre shop with budget goal.

www.giuliano-automotive.com

SL22 PRO



Discover on our website!

You Tube
Watch the video



Suitable for Tubeless tyre bead seating system (optional)

Tilting tower, sliding horizontal arm with $\varnothing 41$ mm operating arm

Spring supported operating arm

CE inflating gauge (standard)

Fitting head designed for both standard and **low profiled** tyre applications

Tabletop thickness 12 mm

Efficiency and Speed with double rotation speed (3ph Version)

Reinforced Chassis

NEW


HP4 Dual Assist Arm with 3 tools (standard):

- Bead Pressing Roller
- Bead Lifting Roller
- Bead Pressing Pad

Additional tilting roller tool for lower bead with an anti-collision joint.

Bead breaker **double effect**
Cylinder $\varnothing 200$ mm., made in aluminum

Suitable for Tyre inflation by pedal (optional)




STANDARD FEATURES

Rim clamping from outside	10" - 22" *
Rim clamping from inside	12" - 24" *
Max. tyre diameter	1010 mm (39")
Max. tyre width	390 mm (15")
Bead breaker cylinder force at 10 Bar	30800 N
Operating pressure	10 bar (145 Psi)
Power supply	400V-3ph-2 speed
Motor power	220V-1ph
Rotation speed	0,75/1,125 KW (400V-3Ph-2V)
Pre-set tyre inflating pressure	0,90 KW (230V-1Ph)
Net weight	7 - 14 rpm
Max. overall dimensions	3,5 bar (50 Psi)
	300 kg
	1420x1740x2010 mm

* By adjustable jaws

STANDARD ACCESSORIES



- Bead lifting lever
- Plastic protectors for mounting/demounting tool
- Lubricator + Pressure regulator
- CE inflating gauge



Giuliano Industrial S.p.A: Via Guerrieri, 6 - 42015 CORREGGIO (RE) ITALY
Tel. +39 0522 731111 - Telefax +39 0522 633109 - E-mail: info@giuliano-automotive.com - Internet: www.giuliano-automotive.com



SILVERLINE



by

www.giuliano-automotive.com

The best choice for the average tyre shop with budget goal.

YouTube

Watch the video



Discover on our website!

NEW
SL22 PRO LL



AUTOMATIC LEVER - NO LEVER TILT BACK TYRE CHANGER WITH DUAL ASSIST ARM FOR CAR WHEELS 10" – 24"



Suitable for Tubeless tyre bead seating system (optional)

Tilting tower, sliding horizontal arm with $\varnothing$ 41 mm operating arm

NEW


HP4 Additional auxiliary helper system provides a valuable support in mounting/demounting Run Flat, UHP and low profiled tyres.

Tyre inflation by pedal (standard)

Equipped with **LL LEVERLESS** tyre mounting/demounting system



"LEVERLESS" MODE



Control lever to manage movements of the tool.



HP4 Dual Assist Arm with 3 tools (standard):

- Bead Pressing Roller
- Bead Lifting Roller
- Bead Pressing Pad

Additional tilting roller tool for lower bead with an anti-collision joint.

Tabletop thickness 12 mm

Bead breaker **double effect** Cylinder $\varnothing$ 200 mm., made in aluminum



1010 mm 390 mm 10" - 22" 12" - 24"

Reinforced Chassis



Efficiency and Speed with double rotation speed (3ph Version)

STANDARD FEATURES

Rim clamping from outside	10" - 22" *
Rim clamping from inside	12" - 24" *
Max. tyre diameter	1010 mm (39")
Max. tyre width	390 mm (15")
Bead breaker cylinder force at 10 Bar	30800 N
Operating pressure	10 bar (145 Psi)
Power supply	400V-3ph-2 speed
	220V-1ph
Motor power	0,75/1,125 KW (400V-3Ph-2V)
	0,90 KW (230V-1Ph)
Rotation speed	7 - 14 rpm
Pre-set tyre inflating pressure	3,5 bar (50 Psi)
Net weight	318 kg
Max. overall dimensions	1420x1740x2230 mm

* By adjustable jaws

STANDARD ACCESSORIES



• Lubricator + pressure regulator



• Plastic protectors for LL mounting/demounting tool

• Pedal operated inflating device



• Bead lifting lever



Giuliano Industrial S.p.A: Via Guerrieri, 6 - 42015 CORREGGIO (RE) ITALY
Tel. +39 0522 731111 - Telefax +39 0522 633109 - E-mail: info@giuliano-automotive.com - Internet: www.giuliano-automotive.com



The best choice for the average tyre shop with budget goal.

by

www.giuliano-automotive.com

NEW
SL28 PRO DUO LNL



220V-1ph
Inverter



You Tube

Watch the
video



Discover on our website!

SUPER-AUTOMATIC CENTER POST LEVER - NO LEVER TYRE CHANGER FOR CAR WHEELS 10" – 28"

- Suitable for Tubeless tyre bead seating system (optional).
- Robotic pipe to support operating arm.
- Bead pressing arm to ease mounting operations of low profiled and UHP tyres.
- Tools Storage Box (standard).
- Manual Press/Twist clamping device. Rim clamping up to 28"
- Reinforced chassis and tower.
- A very practical wheel lifter reduces effort and increases productivity (optional).
- "Easy Access" extractable pedal box for quick service.
- Tyre inflation by pedal (standard).
- Double rotation speed by pedal (220V - 1ph - Inverter).
- MOTOINVERTER**
Faster, more accurate and reliable drive for your tyre changer.
- Locking system for total stiff locking of horizontal and operating arm.
- Ergonomic control console for a fast and intuitive work flow.
- Twisting arm/disk air operated bead breaker system.
- Lever-No-Lever tyre mounting / demounting system [Giuliano Patent], standard.
- "NO LEVER" MODE
- "LEVER" MODE
- Control lever to manage movements of the tool.
- "LEVER" & "NO LEVER" Mode control handle
- PATENTED**

1200 mm 406 mm 10" - 28"

STANDARD FEATURES

Rim clamping range	10" - 28"
Max. tyre diameter	47" (1200 mm)
Max. tyre width	406 mm (16") *
Bead breaker cylinder force at 10 Bar	12037 N
Max. wheel weight	80 kg
Operating pressure	8 - 10 bar (116 - 145 Psi)
Power supply	230V - 1Ph - 50/60 Hz with motoinverter
Motor power	0,75 kW - 2 speed
Rotation speed	7÷16 rpm
Pre-set tyre inflating pressure	3,5 bar (50 Psi)
Net weight	350 Kg
Max. overall dimensions	1185 x 1960 x 2120 mm

* For reverse mounted wheels, variable according to rim features

STANDARD ACCESSORIES



EXTENSIVE SELECTION OF STANDARD ACCESSORIES

tool • Plastic protections for centering cone • Rubber protections for clamping chuck • Bead pressing clamp (WDK clamp) • Filter + pressure regulator + lubricator • Press/Twist clamping device

SILVERLINE



The best choice for the average tyre shop with budget goal.

www.giuliano-automotive.com

SL44



1100 mm 510 mm 75 Kg



Discover on our website!

DIGITAL ELECTRONIC 2-D WHEEL BALANCER WITH LED DISPLAY



Advanced software for further upgrades


✓ USB port for firmware updating via PC/notebook

✓ Intuitive, Easy-to-use Control Panel

FUNCTIONS

- Automatic measuring of wheel diameter and distance
- Automatic START and STOP
- Static and dynamic balancing
- OPTIMATCH function
- Self-calibration

✓ WIDTH ESTIMATION




The width of the rim automatically suggested according to the measured diameter and distance.



✓ Complete with Wheel guard, cones and quick clamping ring nut

✓ SPECIAL ALU PROGRAM



Programs for selecting the best correction planes for any kind and shape of alloy rim.

✓ SELF SELECTION MODE

Self-recognition of the Working program.



A very practical **Wheel Lifter** reduces effort and increases productivity (optional).

✓ Pedal brake

✓ HIDDEN WEIGHT



• Fast & Easy Split (FES) function, is really the fastest method on the market to split balancing weights behind the spokes of your aluminum wheel.

✓ OPPOSIT POSITION



• Opposite Weight function (OPF), enables to place the balancing stick—on weight on the lower inside part of the aluminum wheel (at 6:00).

OPTIONAL ACCESSORIES



- Wheel clamping adaptors
- Clamping cones with spacers
- Wheel lifter and much more

STANDARD FEATURES

Max. wheel weight	75 kg
Max. wheel diameter	1100 mm
Rim diameter	10"-30" / 255-765 mm
Rim width	1,5"-20" / 40-510 mm
Power supply	230V 1ph (50/60) Hz
Cycle time	4.7 sec. (5 3/4"x14") 15 kg.
Balancing speed	< 150 rpm
Balancing precision	÷ 1 g
Net weight with guard	85 kg
Max. overall dimensions	1100x1100x1500 H mm

STANDARD ACCESSORIES



- Wheel guard
- Manual gauge for measuring wheel rim width
- Cones and quick clamping ring nut
- Counterweight pliers



Giuliano Industrial S.p.A: Via Guerrieri, 6 - 42015 CORREGGIO (RE) ITALY
Tel. +39 0522 731111 - Telefax +39 0522 633109 - E-mail: info@giuliano-automotive.com -
Internet: www.giuliano-automotive.com



OPTIONAL ACCESSORIES		SL22	SL22 PRO	SL22 PRO LL	SL28 PRO DUO LNL	SL44
	PRESS ARM ECO Additional arm to ease mounting operations of low profiled and UHP tyres.	OPT	-	-	-	-
	BAR-G CE inflating gauge.	STND	STND	-	-	-
	PED-G Pedal operated inflating device	OPT	OPT	STND	STND	-
	GUN 1 Tubeless inflation external kit.	OPT	OPT	OPT	OPT	-
	Kit of jaw protectors, plastic protectors for bead breaker shovel.	OPT	OPT	OPT	-	-
	Air filter with pressure regulator.	OPT	OPT	OPT	STND	-
  HP4 Video	HP4 Additional auxiliary helper system to ease mounting operations of low profiled and UHP tyres.	OPT	STND	STND	-	-
  WL28 Video	WL28 Wheel Lifter	-	-	-	OPT	-
  WBL81 Video	WBL 81 Wheel lift, for wheel easy positioning and centering on the shaft, without any effort for the operator.	-	-	-	-	OPT



Giuliano Industrial S.p.A: Via Guerrieri, 6 - 42015 CORREGGIO (RE) ITALY
Tel. +39 0522 731111 - Telefax +39 0522 633109 - E-mail: info@giuliano-automotive.com -
Internet: www.giuliano-automotive.com

